

Moore

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Moore Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Moore T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
HCS HART Concentrator System	HART-to-MODBUS RTU Converter
*PTX004	
*PTX012	
12372-413	
14811-18.	
14995-120	
16300-442	
2932-16.	
39MBXNAN	
39SAMCAN	
524A48P	
535-2115-00000	

535-2115-0B000
5751-3
58S
661A6
6751-3.
80088-B
804-030-26
85514-BM
85712-DC
9905503
B/M 10342-/24 SH
B/M 10342-/24 SI
HCS / HART / MB232 / 9-30DC / DIN
IPF/4-20MA/3-15PSIG/20PSI/-CE [WPP]
IPT2
IPX036
MIB-E-PTX005
MIB-E-SIEM031
MIB-E-SIEM053
MODEL : IPX2/4-20MA/3-15PSIG/20PSI [EXIP]
MODEL 77-16(M575)
P/N 12444-2.
P/N:16133-71/04
P/N:16171-121/05
PIX/3-15PSIG/4-20MA/12-42DC/-GA1 [EXIP]
PWT/600AC,5A/4-20MA/-1E-50H-240AC-CE [DM]
PWT/600AS, 5A/4-20MA/1E-50N-240AS (DM)
SIEM032

SIEM053	
SPA/HLPRG/2PRG/U [DIN]	
SPA2/HLPRG/2PRG/U [DIN]	
SPD/4-20MA/PRG/2.3VLP/-LMD [FH]	
SRM/CC/3RO/24DC [DIN]	
STA/HLPRG-3PRG-U-AO/(DIN)	
KGT-12.7x12.7-FGR-RH-2-SAG	Eichenberger Carry Ball Screw Nut
DETECTING UNIT FOR DUAL INPUT SMART HART	TEMPERATURE TRANSMITTER SERIES: TDZ3
SENSORE FOR DUAL INPUT SMART HART TEMPERATURE	TRANSMITTER SERIES: TDZ3
20087-50	
Ptx/5k-3-97/4-20ma/12-28dc/-Rf-Isb [fl]	
Typ 600-Bd	2 Precision pressure regulator Type 600-BD Transmission: 1: 6 Connections: 1/4 "NPT Supply air max. : 17.5 bar (253 psi) Temp. Range: -40 to + 90 ° C materials: Housing: die-cast aluminum Membranes: NBR (Buna N), nylon reinforced Internal parts: stainless steel, bronze, cadmium steel and neoprene Flow rate: 76.5 m³ / h at 7 bar supply air and 1.4 bar outlet pressure. Relief performance: 25.5 m³ / h Country of origin: USA Customs Code: 9032 8100
Psd 4-20ma Prg 2.3	
Ptx/7k-2-98/4-20ma/12-28dc/-Rf-Isb [fl]	
???/??-2-98/4- 20??/12- 28dc/Isb- Rfce[fl] Old Part Number, New Ptx/7k-2-98/4-20ma/12-28dc/-Rf-Isb [fl]	
40-450	
888274	
1977-4	
353af1nnnnnnan	
Adapter Plate To Mounting Model 760 In Place Of Model 750	
760p11aaagnd6	
10895-143	
353afnnnnnnnan	
Model : 61h	

1912-7
5360/12a-B-11-A-12
760p15bangnian
74sg
760e15baagnnb
42h100
Model: 73n12f
173n
750p13gnnn B/M No. Mx051071-001/Tk Obsolete Replaced By 760p11aaagnnd6
55af
Ect/4-20ma/4-20ma/12-42dc(Din)
I/P-Iph2
1/8" Npt Connection
55a B/M-14281-29s2 Obsolete- No Replacement Nullmatic Controller
760e (760e11aaagnnd6)
55a B/M-14281-29s2 Obsolete- No Replacement
4505-40
40h50-Da90-450-Psi
3356-2
41-50
73n12f
3356-1
7025-39
42ha100
???/5?-3-97/4- 20??/12- 28dc/Isb- Rfce[fl] Old Part Number, New Ptx/5k-3- 97/4-20ma/12-28dc/-Rf-Isb [fl]
11rs189