



## Munters

Garanti: 12 ay

Bu ¼r¼ne ait T¼rkiye ii kapı teslim fiyat ve teslim s¼resi ieren teklifimizi almak iin [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

**Munters** Markası, tedarik s¼resi iin l¼tfen bizimle iletiŐime geiniz.

*Firmamız Munters T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*

¼r¼n	Aıklama
<a href="#">90780010</a>	Celdek 7060-15; 72"x12"x12"
<a href="#">90780010</a>	Celdek 7060-15; 60"x12"x12"
<a href="#">150-020508-001</a>	Electric Motor Reducer Type : ACE72T Serial number : 1083446 Hz : 50 / 60 V : 400 +10% / 480 +10% A : 0.13 / 0.13 W : 19 / 23 IP : 65 i : 2563 rpm rpm : 1.1 / 1.3 Nm: 30 / 30 The electric motor will be coupled.
<a href="#">150-020508-001</a>	Gear motor ACE72T B3 (380-480V 50/60Hz, 30Nm)
<a href="#">150-018087-001 PLC, HMI, POL871.71/STD, CLIM</a>	
<a href="#">150-039702-001 SENSOR, HUMIDITY&amp;TEMP 4-20MA, DUCT</a>	
<a href="#">19081259 Actuator SCC61</a>	
<a href="#">1901500968-01 Thermostat ML2 175+-8grC fast</a>	
<a href="#">190101143-166 Thermostat TR2 160°C 250V 15A</a>	
<a href="#">150-014921-001 PLC, POL955.00/STD CLIMATIX</a>	
<a href="#">150-014920-001 PLC, POL638.00/STD CLIMATIX</a>	
<a href="#">ACE72T- 150-025445-006</a>	
	190300 Dehumidifier M 120, 230V/50-60Hz Sorption dehumidifier in a compact, ready-to-use version with: <input type="checkbox"/> Housing made of corrosion-resistant die-cast aluminum, painted, with hose connection nozzle and side opening for optical rotor rotation control as well as recessed handles for easier transport <input type="checkbox"/> Titanium silica gel sorption rotor with abrasion-resistant sorbent, including gear ring for direct drive <input type="checkbox"/> Gear motor with pinion for direct rotor drive <input type="checkbox"/> Filter mats,

<a href="#">M120</a>	grade EU3, in the process and regeneration air inlet □ Radial fans for the process and regeneration air flow with a common internal drive motor □ Electric heater for heating the regeneration air □ MAN/AUTO selector switch for optional operation with an external humidity meter □ Hygrostat socket for easy connection of an external control hygrostat □ Control system with all necessary switching, safety and control functions including maximum thermostat in accordance with the relevant Manufactured to EC standards and wired ready for connection with connection cable including plug □ Rotor material, flame retardant, certified according to DIN 4102-1 (BAM) Technical data: Process air Air volume, free blowing 180 m <sup>3</sup> /h Air volume, nominal 120 m <sup>3</sup> /h Pressure, externally available, nominal, Pst. approx.: 200 Pa Regeneration air Air volume, nominal: 35 m <sup>3</sup> /h Pressure, externally available, nominal, Pst. approx. 100 Pa Dehumidification performance Inlet condition of the process air 20°C, 60% r. F. approx.: 20.0 l/24h Energy requirement Electrical connection 1 x 230V, 50Hz, 1.28 kW Dimensions and weight: Height: 425 mm Width: 425 mm Depth: 481 mm Weight: 26.0 kg
<a href="#">150 020508 001</a>	
<a href="#">Vduse-1/2vx28-1002-100;</a>	
<a href="#">Ccx 1.5</a>	
<a href="#">Fca5</a>	
<a href="#">20220018</a>	
<a href="#">4312506</a>	SEAL KIT
<a href="#">Ccx 2,5 20870094</a>	
<a href="#">Munters-Type-Vd3;Se-12quot;-100;-Pp-28ltr2bar-Pack-40-Pcs-Istanbul-Turkiye</a>	
<a href="#">Rh98-Wall Mounted Control Unit And Room Sensor 43154</a>	
<a href="#">13x2240li A88 V Belt</a>	
<a href="#">1679201000</a>	
<a href="#">Mb-954-2a</a>	
<a href="#">Gv1-M01-0,1-0,16a</a>	
<a href="#">Mx2 95</a>	
<a href="#">Mlt1400</a>	
<a href="#">3x16-220v-50/60hz</a>	
<a href="#">M2ta090s-490540041-B No:17599 400v Star 1640 R/Min 1,5hp 1.1kw 2,6 A</a>	
<a href="#">160oc</a>	

<a href="#">Md300</a>	
<a href="#">Drive Motor Kit - 19043350</a>	
<a href="#">0-600 Min 220v</a>	
<a href="#">Zb2-Bz105+zb2-Bd3</a>	
<a href="#">3x9-220v-50/60hz</a>	
<a href="#">Zb2-Bs844+zb2-Bz104</a>	
<a href="#">RotoI MI 1100/1350</a>	
<a href="#">150-020508-001</a>	DRIVE MOTOR 30NM, 50/60HZ, REP:190101467-1
<a href="#">Mx2 95 / 170-013059</a>	
<a href="#">170-190500-001</a>	
<a href="#">Gv1-Mo8-2,5-4.0a</a>	
<a href="#">Fca515</a>	
<a href="#">Fan For Ga 125 Lp</a>	
<a href="#">Fca15</a>	
<a href="#">Ccx 2.5</a>	
<a href="#">Xb2-Bv75-D=22mm</a>	
<a href="#">190101467-1</a>	ML420 GEAR MOTOR
<a href="#">Motor For Ga 125 Lp</a>	
<a href="#">Vduse-1/2quot;-100;</a>	
<a href="#">MI 690</a>	
<a href="#">Ccx 1,5 20870093</a>	
<a href="#">M120</a>	
<a href="#">150oc</a>	
<a href="#">Jdw5 5kpa / Basınç Sivici Jdw5 5kpa Alre Krs.</a>	
<a href="#">103710716</a>	
<a href="#">Dve - 1504145</a>	