



Nabtesco

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Nabtesco Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Nabtesco Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
217158-01 valf	
EGCS-314M-2. 09A	73794212-01 3 way valve. POS 31, x 1pc complete.
NPS -2 check chock valve complete Nabtesco. POS 32	
Coil Nabtesco DC24V AIW 0,32 ϕ 20c Ω	
NABTESCO RV080E-101-B-B	
RV080E INPUT GEAR KIT	
Repair kit 3/2 way valve	see list
CS05A-00	37-24-2 MSP96055
4-way Pnmatik valf	
P55E015F00 / RV-160E-171-B-B (STD)	transmission Country of origin: Japan Gross weight: 29,040KG Net Weight: 26,400KG Gear Type : Precision Gear Kit Transmission Series : RV-E Gear Size : 160E Main bearing, standard input sprocket Your advantages: integrated main storage Hysteresis loss : <1 arcmin Reduction : 1:171.0 Rated torque : 1,568 Nm Acceleration torque : 3,920 Nm Emergency stop torque : 7,840 Nm Torsional stiffness : 392 Nm/arcmin Rocking stiffness : 2,940 Nm/arcmin permitted tilting moment: 3,920 Nm Max. torque (static) : 7,840 Nm Max. speed 100% duty cycle: 25.0 rpm Max. speed 40% duty cycle: 45.0 rpm Radial load : 18,594 N Axial load : 14,700 N Weight : 26.4 kg Lubrication : RV_Grease

	The gear component is delivered without lubrication. The customer has before use for a professional to provide lubrication.
P45E013B00 / RV-80E-101-A-B (STD)	transmission Country of origin: Japan Gross Weight: 15,000KG Net Weight: 15,000KG Gear Type : Precision Gear - Installation Kit Gear series : RV-E, with solid shaft Gear size : 80E Includes : main bearing, standard input sprocket Your advantages: integrated main storage Technical specifications Hysteresis loss : <1 arcmin Reduction : 1:101.0 Rated torque : 784 Nm Acceleration torque : 1,960 Nm Emergency stop torque : 3,920 Nm Torsional stiffness : 196 Nm/arcmin Rocking stiffness : 1,176 Nm/arcmin permitted tilting moment: 2,156 Nm Max. torque (static) : 4,312 Nm Max. speed 100% duty cycle: 40.0 rpm Max. speed 40% duty cycle: 70.0 rpm Radial load : 12,979 N Axial load : 7,840 N Weight : 13.1 kg Lubrication : RV_Grease **The gear component is delivered without lubrication. The customer has before use for a professional to provide lubrication.**
Felt set	Gear box code: RV-320ES-241 Example Product Code: 15Z 245 273 15 80 Rotary shaft seal code
RV 100N 161	
RV-450E-257 (A97L-0218-0266#450E-257 RV J2/J3)	
A97L-0118-0949/70C36 RV 100C-36.75	
A97L-0218-0806/120C36 RV 120C-36.75	
A97L-0218-0265/450C-37 RV-450C-37.34	
A97L-0218-0348/550F-253 RV-550F-253.9	
PF30V00004F5	
NAB RV450E-192.4-B-B	
RV80N-101	
RV160N-102,81	
RV160N-125	
RV-700F-269.21	
P25E016F00 / RV-20E-161-B-B (STD)	Gearbox type: Precision gearbox - installation kit Gearbox series: RV-E, with solid shaft Gearbox size: 20E Includes: Main bearing, customer-specific. Input pinion Your advantages: integrated main bearing +++ highest precision +++ hysteresis loss <1 arc minute Technical data Hysteresis loss: <1 arcmin Reduction ratio: 1:161.0 Nominal torque: 167 Nm Acceleration torque: 412 Nm Emergency stop torque: 833 Nm Torsional rigidity: 49 Nm/arcmin Tilt-down rigidity: 372 Nm/arcmin Permitted tilting torque: 882 Nm Max. torque (static): 1,764 Nm Max. speed 100% duty cycle: 40.0 rpm Max. speed 40% duty cycle: 75.0 rpm Radial load: 7,786 N Axial load: 3,920 N Weight: 4.7 kg Lubrication: RV_Grease
P35E014F00 / RV-40E-121-B-B (STD)	Gearbox type: Precision gearbox - installation kit Gearbox series: RV-E, with solid shaft Gearbox size: 40E Includes: Main bearing, customer-specific. Input pinion Your advantages: integrated main bearing +++ highest precision +++ hysteresis loss <1 arc minute Technical data Hysteresis loss: <1 arcmin Reduction ratio: 1:121.0 Nominal torque: 412 Nm Acceleration torque: 1,029 Nm Emergency stop torque: 2,058 Nm Torsional rigidity: 108 Nm/arcmin Tilt-down rigidity: 931 Nm/arcmin Permitted tilt-down torque: 1,666 Nm Max. torque (static): 3,332 Nm Max. speed 100% duty cycle: 40.0 rpm Max. speed 40% duty cycle: 70.0 rpm Radial load: 11,588 N Axial load: 5,194 N Weight: 9.3 kg Lubrication: RV_Grease

P45E014F00 / RV-80E-121-B-B (STD)	Gearbox type: Precision gearbox - installation kit Gearbox series: RV-E, with solid shaft Gearbox size: 80E Includes: Main bearing, customer-specific. Input pinion Your advantages: integrated main bearing +++ highest precision +++ hysteresis loss <1 arc minute Technical data Hysteresis loss: <1 arcmin Reduction ratio: 1:121.0 Nominal torque: 784 Nm Acceleration torque: 1,960 Nm Emergency stop torque: 3,920 Nm Torsional rigidity: 196 Nm/arcmin Tilt-down rigidity: 1,176 Nm/arcmin Permitted tilt-down torque: 2,156 Nm Max. torque (static): 4,312 Nm Max. speed 100% duty cycle: 40.0 rpm Max. speed 40% duty cycle: 70.0 rpm Radial load: 12,979 N Axial load: 7,840 N Weight : 13.1 kg Lubrication: RV_Grease
RV-320E B type shaft input and 141 bond	
RC-20E A type spindle input and 121 bond	
H349025595 / H811D4100-00-S	(Only the valve cover is required, not as a complete set.)
Gm21va-A-48/83-1	
Cs04-Rb-35-26-1 S/N: 9z001	
309,310a,B,C,D	
M4v290e/Rg6.5 S8x0011 Ksa10220	
Rv-410f053-0	
Gm21va-A-48/26-3	
Rv-110 E-111-A-B	
Rv-80e-57-A-B	
Sn: 06500528, Msp 00139c, Gm09vn-E-21/33-3	
Rv-40e-105	GEAR REDUCER SIZE 40 105:0 RATIO RV-E SERIES
7sh59621-00 ,Axial Vibration Monitor Control Box Nabco Pc No 73758407-01 Code No 727, 36 87001-06581	
S/N: 10b09547 Cs04-Rb-35-26-1 Msp99190a	
Nmt-Ca10.	
0669799ua	
Cs09m-Bb-53-35-1 Msp99169	
Rv-Ge-31-Fa	
Gh-7-11-D-A-P	
Rv-110-E-111-A-B	
Spare Parts As Rotor/Plate And Pressure Pins	
P76e056-00	GEAR REDUCER SIZE 450 KGM 171:1 RATIO RV-E SERIES
Moly White 16kg Pai	
Gh 7-11.2	
Ball Bearing- Dimensions :179 Mmx 151 Mm Width:14 Mmm- (For Cso4-Rb-35-27 Msp02141 S/N:13202746 Hydr	
P55e012d00	GEAR REDUCER SIZE 160 81:1 RATIO RV-E SERIES
6526-2102446-20 Pms-33e(Dc24v 11w)	

A97I-0218-266ã450e-257 ()	
E01x2.E02	
Gm21va-A-42-7	
74y49011-10	
Molywhite Grease (1- Can=2 Kgs)	
Ch S/N S1203a0	
Model Md 404m	
Vigogrease/Molywhite	
Seal Kit For Cs04-Rb-35-27-1	
Gm23vl-C.56/94-6	
M4v290z-Rg10 Motor Unit	
Vico Grease Re0 16 Kgs	
74y59337-10	
Rd-80e-101	GEAR REDUCER CYCLOIDAL SIZE 80 KGM 101:1 RATIO
Repaire Kit For Pump Nabtesco (Piston ,Rotor , Svec Plate , Brake Lining ,Brake Piston Orings ,	
Cs 04-Rb-35-26-1	
Rv-450e-171-Z-B	GEAR REDUCER SIZE 450 KGM 171:1 RATIO RV-E SERIES
Cs04-Rb-35-27-1 Msp02141 S/N 411s-00-Aab	
Gumruk Ve Nakliye Masraflari.	
Gm21va-A-42/72	
Dr-42 P/N:412 000 54150	
P/N: 74758457-01	
Vigo Grease Re No 0 (Dose 2 Kg)	
M4v290/170e A790064	
74y59309-10	
Seriel No:13202746 For Cs04-Rb-35-27 ? Msp02141	
Cs04-Rb-35-27-1 Msp02141 S/N 03b00881	
74796025-01	
74y49003-19	
M4v290 170f	
M4v290erg6.5 S790143 Ksa10220	
M4v245/1400z	
Mcg 402-06	
M4v290-Rg6.5	

S/N Sk16025055 , Type Mbd-Fiva I-45 Paert Nr. 241	
E06	
Rd-040e-153	GEARHEAD RD SERIES 153:1 RATIO
E04	
74y49041-09	
Rv-700f-269.21	
652672084965-40	
0401-1000500-00	
Molywhite ? 2.0kg Can	
Hm18l-J-56-2	
06941	
Gh40-11	
P35e013b00	GEAR REDUCER SIZE 40 105:0 RATIO RV-E SERIES
Gm10va-C-33/54-3	
Repair Kit For Cs04-Rb-35-27-1	
73754849-01	
M4v24j/140z	
Gm10va	
M4v290/170z	
Rv-160e-81-Z-B	GEAR REDUCER SIZE 160 81:1 RATIO RV-E SERIES
Gm09m - L - 40 - 3 Msp96004a 05710425	
P70j107dc0	GEAR REDUCER SIZE 450 KGM 171:1 RATIO RV-E SERIES
Gm09m-E-40-1	
Rv-70f-79.84	