

Neum¼ller

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Neum¼ller Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Neum¼ller T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
BLD-150-C140-NNS/D/U-B00000	LED power supply - 150W, 64-143VDC, 1400mA CC LED power supply, constant current Power: 150W Input voltage range: 90-305VAC Input voltage range: 127-420VDC Output voltage range: 64-143VDC Output current range: 1050-1400mA Power factor:> 0.9 Working temperature range: -40 to + 70C ° Protection class: IP67 MTBF:> 300,000 hours @ Tc = 75C ° Cable type: VDE 3 Wire, Class I (EU)
BLD-150-C140-NNS	LED power supply - 150W, 64-143VDC, 1400mA CC LED power supply, constant current Dimming function: no Programmable: no 12Vaux: No. Dimm-Off: No. Power: 150W Input voltage range: 90-305VAC Input voltage range: 127-420VDC Output voltage range: 64-143VDC Output current range: 1400mA Power factor:> 0.9 Working temperature range: -40 to + 70C ° Protection class: IP67 MTBF:> 280,000 hours @ Tc = 75C ° Cable type: VDE 3 Wire, Class I (EU)
TLD-160-C140-NNS	LED power supply - 160W, 69-152VDC, 1400mA CC LED power supply, constant current Dimming function: no 12Vaux: No. Dimm-off: No. Programmable: no Power: 160W Input voltage range: 200-528VAC (250-740VDC) Output voltage range: 69-152VDC Output current range: 1050-1400mA Power

factor:> 0.9 Working temperature range: -40 to + 70C °
Protection class: IP67 MTBF:> 280,000 hours @ Tc = 75C °
Housing: 251.0x68.0x38.5mm Cable options: VDE 3 Wire,
Class I (EU) RoHS compliant