



Nidec-Avtron

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Nidec-Avtron Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Nidec-Avtron T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	A¼ıklama
M285	1024PPR ROTARY PULSE GENERATOR SMARTACH ENCODER 5-18VDC 250MA
AV56A1KDX6YXGP51	Direct replacement for: AV56A1TDX1YXG015 DESCRIPTION: OPTIONS: Housing type 1 - single output Rotor bore diameter KD - rotor with through hole 15/16 inch, fastening with cam screws, for ADC pitch motor Type of coverage X - Without cover plate Output driver 6 - input 5-24V, output 5-24V (7272), recommended for simple wiring (A, B, Z, without inverse signals) Pulse number left output Y - number of pulses 1024 Pulse number right output X - No exit on the right, only a single exit Connection options G - Industrial EPIC connector with matching mating connector, with Northstar pin assignment, with connection for diagnostic LED Changes P51 - Special option for ADC motor: Improved model with diagnostic LED, especially paint, rotor with cam screw and special magnetic shielding
	DESCRIPTION: M6C Flameproof Explosion Protected Encoder, ATEX/IECEX Zone 1 Hollow Shaft Bore Size: 5 - 1-1/8 inch Hollow Shaft Mounting: S - Standard End-of-Shaft Mounting Line Driver: 8 - 5-24V In/Out Protected Line Driver Left

[M6C-5S8HX51-T005](#)

Output: H - High Res. Right Output: X - No Right Output
Base PPR: 51 - 512 PPR Marker: - - No Marker Connector
Options: T - Terminal Block Modifications: 005 - -40C Tested
Unit with Torque Arm Kit Included