

Nieruf

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Nieruf Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Nieruf T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunulmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
Lug Dn 200 Pn16	VALVE
KP01000110	Compensator DN80 type KP01 steel galvanized NBR Medium: liquid and harmless gaseous media (no steam) Flange material: galvanized steel Sleeve: NBR -10°C to +80°C Nominal diameter: DN80 Connection: Flange DIN EN 1092-1
KP01000010	Compensator DN80 type KP01 steel galvanized EPDM Medium: liquid and harmless gaseous media (no steam) Flange material: galvanized steel Sleeve: EPDM -10°C to +100°C Nominal diameter: DN80 Connection: Flange DIN EN 1092-1
SZ05000004	Fine sieve strainer 3/4" inch Stainless steel type SZ05 Design: Y-design with sealing plug Medium: liquid media Housing: stainless steel 1.4408 Cap: stainless steel 1.4408 Seal: PTFE Nominal width: 3/4" inch Internal thread BSP horizontal or vertical installation removable stainless steel filter
	Corner overflow valve 3/4" inch IG UV02 Red brass/brass 2 - 12 bar Medium: liquid and gaseous media Material: Red

[UV02020004](#)

brass/brass Seal: PTFE -60°C to +225°C Nominal diameter:
3/4" inch IG Internal thread BSP-P Setting range: 2.0 - 12.0
bar Adjustable under operating conditions