



## Nivelco

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye ii kapı teslim fiyat ve teslim s¼resi ieren teklifimizi almak iin [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Nivelco** Markası, tedarik s¼resi iin l¼tfen bizimle iletiŐime geiniz.

*Firmamız Nivelco T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*

¼r¼n	Aıklama
<a href="#">Typ: Rdg-402-0</a>	Artikelnr.: SS-RDG-403-0 Tuning fork limit switch NIVOSWITCH for liquids Connection: flange DN50 PN25 / 40, stainless steel PFA coated Housing aluminum, coated Sensor l = 300mm Microswitch SPDT relay, 250V AC, 8A Customs tariff number 9026 1029 00 Country of origin Hungary
<a href="#">Typ: Rvg-403-0</a>	Artikelnr.: SS-RVG-403-0 Fork & extension ECTFE coated Connection: flange DN50 PN25 / 40, stainless steel PFA coated Housing aluminum, coated Sensor l = 300mm Microswitch SPDT relay, 250V AC, 8A
<a href="#">Typ: Mrc-205-03</a>	Magnet float switch Article number: SS-NIVOPOINT Process connection: 2 "BSP 2 switching points L1 = 224mm L2 = 369mm Lges about 450mm
<a href="#">ArtikeInr.: Ss-Rcp-401-3</a>	Ultrasonic compact transmitter for liquids RCM, probe L = 125mm Stainless steel housing Installation length L = 125mm Connection 1 "NPT 3-wire DIN connector Power supply 12 ... 55 V DC
<a href="#">2972</a>	
<a href="#">4x085q0022ydo/10ppm</a>	
<a href="#">9026102900</a>	
<a href="#">DKD-471-F</a>	
<a href="#">DRC2A22M</a>	
<a href="#">DRH-3A2-2</a>	

<a href="#">DTE6512M</a>
<a href="#">EASY TREK SCD-330-4</a>
<a href="#">EASY TREK SCD-34J-4</a>
<a href="#">EASY TREK SPB-380-4</a>
<a href="#">EasyTREK SCD-340-4</a>
<a href="#">F291765</a>
<a href="#">HBN5104S</a>
<a href="#">HPA4204S</a>
<a href="#">HPN4104S</a>
<a href="#">KLP2040M</a>
<a href="#">KSH303M</a>
<a href="#">KSK-201-0</a>
<a href="#">KSP2010M</a>
<a href="#">MAK-100-0</a>
<a href="#">MBL-515-2</a>
<a href="#">Mi-NWP 130-1</a>
<a href="#">Mi-SONAR-N SGV 342-2</a>
<a href="#">MKA-210-0</a>
<a href="#">MKA2108M</a>
<a href="#">MKA-211-1</a>
<a href="#">MKG-210-0</a>
<a href="#">MLB-112-0</a>
<a href="#">MultiCONT PRW-24A-1</a>
<a href="#">NAA1010M</a>
<a href="#">NAA1050M</a>
<a href="#">NAW 1040S</a>
<a href="#">NIVOMAG MKA-210-0 EXW</a>
<a href="#">NIVOMAG MKU-210-0</a>
<a href="#">NIVOMAG-MKA-210-0</a>
<a href="#">NIVOPRESS NAA-102-0</a>
<a href="#">Nivocap CKK-140-1</a>
<a href="#">NLN1201M</a>
<a href="#">NLP1051M</a>
<a href="#">NLP-110-1</a>
<a href="#">NLP-120-0</a>
<a href="#">NPK4310S</a>

<a href="#">NPK4408S</a>
<a href="#">NPK4690S</a>
<a href="#">NWN-105-1</a>
<a href="#">NWN1051M</a>
<a href="#">NWN1101M</a>
<a href="#">NWP-105-1</a>
<a href="#">NWP-110-1</a>
<a href="#">NWP1101M</a>
<a href="#">NWP-120-1</a>
<a href="#">NWP1201M</a>
<a href="#">PKK 312-3</a>
<a href="#">PKK-312-1</a>
<a href="#">PKK-312-4</a>
<a href="#">RCM 310-3</a>
<a href="#">RCM 401-3X66</a>
<a href="#">RCM4008S</a>
<a href="#">RCM-402 L Ex</a>
<a href="#">RCT-402-M</a>
<a href="#">RCT-403-M</a>
<a href="#">RFM-404-A</a>
<a href="#">RHR-520-1,NIVOCONT (2M)</a>
<a href="#">RHR-525-1,NIVOCONT (2.5M)</a>
<a href="#">RKH-50-1</a>
<a href="#">RLH-303-3</a>
<a href="#">SAP-300-0</a>
<a href="#">SEN-362-8EX</a>
<a href="#">SGP- 390-2</a>
<a href="#">SGP-390-6 Ex</a>
<a href="#">SGV3804M</a>
<a href="#">SPA370AS</a>
<a href="#">SPA-380-4</a>
<a href="#">SPA-380-4M</a>
<a href="#">SPA-390-4</a>
<a href="#">SPA3904S</a>
<a href="#">SPA390M</a>

<a href="#">SPB-380-4</a> <a href="#">SPB-390-4</a>	
<a href="#">SPB-39N-8</a>	
<a href="#">SSA-262</a>	
<a href="#">STA-480-1</a>	
<a href="#">WGM1404M</a>	
<a href="#">WGP1404S</a>	
<a href="#">MKA-220-0</a>	
<a href="#">SS-RCM-401-3</a>	Ultrasonic compact transmitter for liquids RCM, probe L=125mm Housing stainless steel Installation length L=125mm Connection 1" BSP 3-wire DIN connector Power supply 12...55 V DC
<a href="#">SS-NIVOCONT</a>	Type KKH-222-5 2-channel conductive limit switch with 5 electrodes 24V ... 240V AC/DC Medium temperature max. 80°C Pmax 1 bar 2x SPDT 250V, 8A   24VDC, 8A Process connection 1-1/2" BSP polypropylene
<a href="#">SS-RCM-401-3</a>	Housing stainless steel Installation length L=125mm Connection 1" BSP 3-wire DIN connector Power supply 12...55 V DC
<a href="#">PiloTREK WP-200 - İntegrated</a>	
<a href="#">0120002</a>	
<a href="#">Limit Switch MKA210-2LK100</a>	Switching difference 10 mm Micro switch with 2 switching contacts Square flange connection with LK ø92 Mounting length 321 mm Protection class IP 65 Medium temperature -20 to +250 °C Ambient temperature -20 to +80 °C Body aluminum casting Internal parts stainless steel delivery including rod extension LK 100mm including flange gasket (max. 250 °C)
<a href="#">NIVOCONT RHR-504-1</a>	Vibrating rod level Switches for powders and granular solids High-Temperature version (+160°C) Process Connection: 1 ½" BSP Housing: Aluminium (paint coated) Standard Probe Length: 0,4 m Output: SPDT, relay 250 V AC, 8A
<a href="#">Nivomag MKA-210-0</a>	
<a href="#">Mka-211-1 Nivomag Type Level Switch</a>	
<a href="#">Mba-535-6m-400-00</a>	
<a href="#">Drh-3a2-2 Drucksensornipress- Messbereich: 0...10 Barg- Genauigkeit: 0,5 %- Ausgang: 4...20 Ma</a>	
<a href="#">Wgp1404s Pilotrek Pulse Radar Level Transmitter</a>	
<a href="#">Krk5125m</a>	
<a href="#">Wgm1404m Pilotrek Pulse Radar Level Transmitter</a>	
<a href="#">Sep-38n-2</a>	LEVEL TRANSMITTER ULTRASONIC 2WIRE
<a href="#">Npk4310s Nivopress Hydrostatic Level Transmitter</a>	
<a href="#">Mbl-515-2 Nivotrack</a>	
<a href="#">Mka-210-8</a>	
	Nivoswitch Tuning fork limit switch according to the enclosed description

<a href="#">Rcm-401-3</a>	probe length 125mm probe material: stainless steel 4.4571 Degree of protection in connection plug: IP65 Process connection: 3-wire DC / DIN connector Supply voltage: DC 12 - 55V
<a href="#">Rcm-301-3 Sensor</a>	
<a href="#">Ac-22 Sound Siren</a>	
<a href="#">Spa 390-4</a>	
<a href="#">Rcm-400-3</a>	Nivoswitch Tuning fork limit switch according to the enclosed description probe length 69mm probe material: stainless steel 1.4571 Degree of protection in connection plug: IP65 process connection: 1 "BSP Process connection: 3-drach DC, DIN connector Supply voltage: DC 12 - 55V
<a href="#">Kkh-222-5</a>	
<a href="#">Naa1050m Halter</a>	
<a href="#">Krk-522-4</a>	Bivocont Conductive electrode relay according to enclosed legend Assembly: U-rail assembly SUPPLY VOLTAGE: 24 V AC / DC Extent: 2 potential-free contact Protection class: IP20 Origin: Hungary customs tariff number: 90261029
<a href="#">Rcm3103m 9026102190</a>	
<a href="#">Rcm4008s Nivoswitch Vibrating Fork Level Switch9026102900</a>	
<a href="#">Nwp1051m</a>	
<a href="#">Tbj-520-2</a>	
<a href="#">Nwn-105-1 Float Level Sensor Ls1.1, Ls1.2</a>	
<a href="#">Nln1201m Nivofloat Float Level Switch</a>	
<a href="#">4x085q0022ydo/10ppm Sonde</a>	
<a href="#">2860 Type Rcm-401-3</a>	
<a href="#">Ksp2010m Nivocont Conductive Socket</a>	
<a href="#">Npk-46-60</a>	
<a href="#">Sat-304-0</a>	
<a href="#">Npk4305m / 9026102190</a>	
<a href="#">Rcm-301-3</a>	
<a href="#">Rcm-400-3 Level Switch Nivoswitch</a>	
<a href="#">Klp2040m Separator</a>	
<a href="#">Easytrek Spa-370-4</a>	
<a href="#">Rcm4158e</a>	
<a href="#">Ksk-201 Electrode</a>	
<a href="#">Separator Rkk-312-4m</a>	
<a href="#">Krk-512-5</a>	
<a href="#">Echotrek Stp-462-4</a>	
<a href="#">Drucksensor Nivelco Nipress Drh-3a2-2</a>	
<a href="#">Dtf6512m Nivopress Hydrostatic Level Transmitter</a>	

<a href="#">Spb-370-8ex</a>	
<a href="#">Easytrek Spa-380-4</a>	
<a href="#">12440</a>	
<a href="#">Nivofloat Nwn-105-1 Schwimmerschalter</a>	
<a href="#">Ss-Sen-362-8</a>	Integrated 2-wire ultrasonic compact transmitter for liquids EchoTREK - Type SEN-362-8 Measuring range: 0.4 ... 7m (60 kHz) Housing: stainless steel Process connection: flange DN80 / PN16, stainless steel Analog output 4-20mA + HART / Ex
<a href="#">Drc2a22m Drucksensor</a>	
<a href="#">Mi-Switch-Nst Rkh 502-1</a>	Vibrating bar Limit switch for powder and granules, operating temperature: -20 ° C ... 110 ° C, oscillating rod: stainless steel (1.4571), housing made of aluminum, process connection: G 1 1/2 "high power relay output, vertical installation, length: 207 mm, Supply voltage: 20-255 V AC / DC Output: SPDT, potential-free relay; 8A 250V AC
<a href="#">Nwp1051m Nivofloat Tilting Float Level Switch</a>	
<a href="#">Spb-390-4 Easytrek</a>	
<a href="#">Npk4408s Konverter</a>	
<a href="#">Rhr-520-1,Nivocont (2m)</a>	
<a href="#">Hbn5104s Microtek Tdr Level Transmitter</a>	
<a href="#">Spa-380-4 Konverter Ebene Easytrek</a>	
<a href="#">Naw1040s Adapter</a>	
<a href="#">Spb-380-4 Ultrasonic Level Transmitter Easytrek</a>	
<a href="#">Nivotrack Mta-500</a>	
<a href="#">Drl-4a2-2</a>	
<a href="#">Npk-43-10</a>	
<a href="#">Rcp4013m</a>	
<a href="#">Ctr-211-8 Nivocap 1.1m</a>	
<a href="#">Rcm-400-3 (Art. Nr. 9701001850000000)</a>	
<a href="#">Mlb-112-0 Magnetic Level Indicators</a>	
<a href="#">Drucksensor Drh-3a2-2m</a>	
<a href="#">Ksh303m Elektroden-Halter</a>	
<a href="#">Easytrek Scd-310-4</a>	
<a href="#">Rkh-502-1</a>	
<a href="#">Sap- 200-0</a>	
<a href="#">Npk4310m / 9026102190</a>	
<a href="#">Rkr-503-5ex</a>	
<a href="#">Spa370as Easytrek Ultrasonic Level Transmitter</a>	
<a href="#">Nwp-110-1 Float Cable Level Sensor For</a>	

<a href="#">Sewerage And Effluent</a>	
<a href="#">Rcm4003</a>	METER
<a href="#">Klp-201-0</a>	
<a href="#">Krk-512-5 Level Control Relay</a>	
<a href="#">Ss-Spb-370-8</a>	Ultrasonic compact transmitter for liquids Housing PVDF, IP68 Measuring range 0.35 ... 8m (60 KHz) Connection 1 "or 2" BSP Power supply 12 ... 36 V DC Output 4-20 mA + HART / Ex ia
<a href="#">Naa1010m Leitungsverbinder</a>	
<a href="#">Echotrek Stp-480-2</a>	
<a href="#">Spa390m Easytrek</a>	
<a href="#">Krk5125m Grenzschalter</a>	
<a href="#">Npk-44-15</a>	
<a href="#">Kln2100m</a>	
<a href="#">Krk-512-5 Sensor</a>	
<a href="#">Hpn4104s Microtrek Tdr Level Transmitter9026102190</a>	
<a href="#">Mbl-515-2 Magnetostrictive Level Transmitters</a>	
<a href="#">11705</a>	
<a href="#">1262</a>	
<a href="#">Krk-512-5 Conductive Level Switch</a>	
<a href="#">Pew-215-6ex</a>	
<a href="#">Npk4690s Hydrostatic Level Transmitter</a>	
<a href="#">Kln-205-0</a>	
<a href="#">Rfm-404-A Nivoswitch</a>	
<a href="#">Sap-300-0 Display</a>	
<a href="#">Spt-39f-3 Ultraschallwandler-Level, 3-4m, 4-20ma, Easytrek</a>	
<a href="#">Ksh-203</a>	
<a href="#">Rcm4013m</a>	
<a href="#">Krk5125m Grenzschalter Nivocont</a>	
<a href="#">Npk-43-07</a>	
<a href="#">Kkh225m</a>	
<a href="#">Nivomaq Mka-210-4</a>	
<a href="#">Pmm-312-1</a>	
<a href="#">Drh3a22s 9026102190nipress Pressure Transmitter</a>	
<a href="#">Schalter Endplatte Ebene Rcp-401-6m</a>	
<a href="#">Easytrek Spb-380-4</a>	

<a href="#">Nivofloat Nwn-110-1 Float Level Sensor Pear-Shaped For Wastewater, Neoprene.Kabel</a>	
<a href="#">???-220-0 R42573i Schwimmerschalter Niveau</a>	
<a href="#">Nivopress Npk-431-0</a>	
<a href="#">Npk-45-25</a>	
<a href="#">Sgv3804m Echotrek</a>	
<a href="#">Spt-390-4</a>	
<a href="#">Mlb-112-0 Nivoflip</a>	
<a href="#">Krk5125m Nivocont Conductive Level Control Relay</a>	
<a href="#">Spt-390-H</a>	
<a href="#">Kln-220</a>	
<a href="#">505-1</a>	
<a href="#">Tbc-521-2</a>	
<a href="#">4x085g0023ydo/20ppm</a>	
<a href="#">Obsolete - Easy Trek Sca-360-4 - Replaced By - Echotrek Stp-462-4</a>	
<a href="#">Rcm-400-M</a>	Nivoswitch Tuning fork limit switch according to the enclosed description probe length 69mm probe material: stainless steel 1.4571 Degree of protection in connection plug: IP65 process connection: 1 "BSP Process connection: 3-wire DC, M12 connector Supply voltage: DC 12 - 55V
<a href="#">Easytrek Spa-390-4</a>	
<a href="#">Rcm-401-M</a>	Nivoswitch Tuning fork limit switch according to the enclosed description probe length 125mm probe material: stainless steel 4.4571 Degree of protection in connection plug: IP65 process connection: G1 Process connection: 3-wire DC / M12 connection, plug Supply voltage: DC 12 - 55V