



Intra- Automation

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Intra-Automation Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Intra-Automation T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	A¼ıklama
1690ATEX	
641,6502,380LI	
641.6502.380 LI 1	
641.6502.380.LI	
A71G-IEC	
for TAG TW-2301B	
for TAG TW-2302	
for TAG TW-2346C	
for TAG TW-2347C	
for TAG TW-2348B	
for TAG TW-2418A	
for TAG TW-4411	

IBR-25-ID701/5mm-S-1-Y-KI-HL-T0-A04-S	
INT433-1DA02-1AB6-Z	
LMS-A	
LMS-AH-G	
IBR-26-ID2700/8mm-S-1-C-KI-HL-T0-A03 A56	ITABAR-FLOW-SENSOR type: IBR-26-ID2700/8mm-S-1-C-KI-HL-T0-A03- A56 [IBR] - flow sensor for gases and liquids, prepared for welding coupling with cutting ring [26] sensor prepared for end support, profile: 25,4 mm [ID] - pipe inside diam./wall thickness: 2700/8 mm [S] sensor material: 316L [1]-welding coupling, material: C.S. [C]-end support, material: C.S. [KI] - no insulation of line [HL] - line orientation at place of ITABAR installation: horizontal [TO] integrated RTD sensor: without [A03] - instrument connection: sensor head with 1/2" NPT-M [A56] - ball valve, PN40, material body/ packing: 316L/ PTFE, female thread 1/2" NPT
flowmeter	Dust concentration: 10mg/m ³ Speed: Max24m/s Temperature: 40-60C (Max60C) Channel Diameter:2706mm Flow rate: 500000m ³ /h
IBR-26-ID1400/?mm-S-1-C-KI-VL-T0-0-A03-A00	Flow sensor ID pipe internal diameter = 1400 mm WS pipe wall thickness = ? mm S sensor material : 1.4571 1 Mounting coupling PN40 made of carbon steel C end support made of carbon steel KI without insulation VL vertical pipeline T0 without PT-100 0 without temperature transmitter A03 pressure taps 1/2" NPT-M A00 without shut-of valve
641.6502.380li Mag. Level Switchtype 1690 Witch 3m Cable	
1690atex Magn. Switch1690atexincluding Mounting Strapwith 3 M Cable	
Lms-Ah-G Magnetschalter Kontakte Goldplatiert Max. 400 C	
Lah-850-2	
Avk-H10-Int5335-Exd	
Lah-850-2 Lineal	
Ita-10.0 - Level-Anzeige Local- L:1200mm P:75.3 Bar T:292c D:0.75 Kg/Dm³	
57982	
Lms-Ah-G Positionssensor	