

Nuova

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Nuova Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Nuova T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
Mn9/18/A Dn 100 - 150-250 Mmh2o	
Mgs 18/3/A Dn 100 0-40 Bar	
Mgs 18/3/A Dn 100 0-25 Bar	
Mgs 18/3/A Dn 100 0-10 Bar	
Mgs 18/3/A Dn 100 0-16 Bar	
Mgs 18/3/A Dn 100 0-39 Bar	
Mgs 18/3/A Dn 100 -1 - 9 Bar	
Tg 859 Dn 100 -120 - 80 °c	
Tg 859 Dn 100 -100 - 150 °c	
Tg 859 Dn 100 -50 - 50 °c	
Tg 859 Dn 100 0-60 °c	
Tg 859 Dn 100 -80 - 40 °c	

Tg 859 Dn 100 0-120 °c	
Tg 859 Dn 100 0-100 °c	
Md 15/A Dn 100 0-6 Bar	
Md 15/A Dn 100 0-2,5 Bar	
Nuova	
Nuova	
Nuova	
Nuova	
Male ½" fittings	Wire lengths 3,3 mts.
8.X18.---.AAFZ.21M.1.2GD.T6B.NBR	INTRINSICALLY SAFE PRESSURE TRANSMITTER, ATEX VERSION, 0425 ATEX 2635 APPROVAL, MODEL SX 18. 22 MM HOUSING DIAMETER. CERAMIC TRANSDUCING CELL, ST ST. AISI 316L SOCKET. DIRECT MOUNTING BOTTOM CONNECTION, RANGE 0...400 BAR, 1/4" BSP MALE PROCESS CONNECTION, 4...20 mA OUTPUT SIGNAL. 2 WIRE CONNECTION, MARKING - II 1/2 GD Ex ia IIC Ex ia IIIC (TF4 rev.2), T6 (85°C) Ta <=60°C, ELECTRICAL CONNECTION AS PER EN 175301-803 - IP65 PROTECTION DEGREE, NITRILE (NBR) SEAL GASKET, ACCURACY ± 0,5% OF THE RANGE
3-30-H1 46,6 H2 48,8-C/ D-3-43M-S31	
3-28-1BAR-A/B-3-23F-S31	
Nuova/05plus	
160w418200t	
E-17/A2	
D10/C	
Wu-Da160mb E941893 Obsolete, Replacement 160w418200t	
A002-E10/L	
8.S18.---.Aafg.21m.1.Fpm	
D10/Cs	
Nuova 05	