



Nuovo Pignone

Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

Nuovo Pignone Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Nuovo Pignone Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
PSO 618038.000	PSO 00052.000
3GJP 311 210 ADG	MİT MOTOR
Heat Exchanger plug	
TYPE: 2HB/1, 4HA/4, 2HE/1	P/NO: KHA017102600
Type: BCL 303/A	
IRF316714998	COALESCENT CARTRIDGE
INL0200201591	COALESCENT CARTRIDGE
R412006103 Regulators AS2, RGS, G 1/4, GAU	
R412004414 PRESSURE GAUGE	PG1-ROB-G014-SAS-D50P(0-2)
IRM9908202	MODEL: DDHF, MFG SERIAL NO: P18894, OG. DRWG NO: SOA5546364, TAG NO: 109G-005 A, TECH. REQ. NO: P.O. 2030-05160 / 5171
DDHF, MFG SERIAL NO:	P18896, OG. DRWG NO: SOA5546365, TAG NO: 109-G-001 A, TECH. REQ. NO: P.O. 2030-05160 / 5171: BEARING TEMPERATURE DETECTOR, POS IRM9908303
8.Sx18	DMU-S-D-DIVERS Statistische Warennummer: 90322000 8.SX18---.AAFZ.41M.1.1GD.T6B.U68.I.FPM INTRINSICALLY SAFE PRESSURE TRANSMITTER, ATEX VERSION, 0425 ATEX 2635 APPROVAL, MODEL SX 18. 22 MM HOUSING DIAMETER. CERAMIC TRANSDUCING CELL, ST ST. AISI 316L SOCKET. DIRECT MOUNTING BOTTOM CONNECTION RANGE 0...400 BAR 1/2" BSP MALE PROCESS CONNECTION 4...20 mA OUTPUT SIGNAL. 2 WIRE CONNECTION MARKING - II 1 GD Ex ia IIC Ex ia IIIC (TF4 rev.2) T6 (85°C) Ta <=60°C IP68 PROTECTION DEGREE CABLE EXIT COMPENSATED

POLIURETHANE CABLE 1 MT VITON (FKM) SEAL GASKET
ACCURACY $\pm 0,5\%$ OF THE RANGE

[Please See Attached Document](#)

[Type E4x12ddhf ,13](#)
[Stg.Ser.Nos.P14271/72](#)

BERING SHOULDER RING PART NO : SBP 48140