

O&B

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
O&B Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız O&B T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunulmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
Sgmgh-05d2a61-Oy	SERVO MOTOR 2.84NM 0.45KW 1500RPM 400VAC 3PHASE
Zs-Hlds10-2m	SENSOR HEAD, DIFFUSE REFLECTIVE, 10020MM SENSING RANGE, 1UM RESOLUTION
Cj1w-Spu01-V2	CJ1 HIGH-SPEED DATA STORAGE AND PROCESSING UNIT, 1 X 10/100BASE-TX PORT, CF CARD SLOT (REQUIRES CF CARD)
R88d-Kn15h-Ect	G5 ECAT SERVO DRIVE 1.5KW 200V
Ns5-Tq11b-V2	PROGRAMMABLE TERMINAL (HMI), 5.7 INCH, HIGH-BRIGHTNESS TFT, 256 COLOURS (32,768 COLOURS FOR .BMP/.JPG), 320X240 PIXELS, 2 X RS232 PORTS, ETHERNET (10/100 BASE-T), 24 VDC, 60MBYTE MEMORY, 24 VDC, BLACK
Cimr-E7z40220a	INVERTER DRIVE, 22KW, 45A, 415 VAC, 3-PHASE
Cj2h-Cpu65-Eip	CPU WITH BUILT-IN ETHERNET/IP PORT, 100K STEPS PROGRAM, 32K WORDS DATA MEMORY, 32K WORDS X 4 BANKS EM, 2,560 I/O MAX, RS-232C SERIAL PORT, USB PROGRAMMING PORT, 3 EXPANSION RACKS MAX.
Cimr-E7z40450a	INVERTER DRIVE, 45KW, 91A, 415 VAC, 3-PHASE

Cs1h-Cpu64-Ev1	CPU MODULE CS1H 30K STEPS
R88d-Kt10h	G5 SERIES SERVO DRIVE, ANALOGUE/ PULSE TYPE, 1.0KW, 200VAC SINGLE PHASE
Nsa15-Tx11s	INDUSTRIAL PC, 600MHZ INTEL CELERON M, 256MB, 15 TOUCHSCREEN TFT COLOUR LCD (1,024 X 768 PIXELS), RAS BOARD, PCI SLOT, 2 X 100BASE-TX ETHERNET PORT, COMPACT FLASH SLOT, 4 X USB PORTS, 2 X RS-232C PORT
R88d-Ua02ha	SERVO DRIVE 30WATT 1.3AMP 200/230VAC 50/60HZ
Nsh5-Sqr10b-V2	HANDHELD PROGRAMMABLE TERMINAL (HMI), 5.7 INCH, STN, 256 COLOURS (4,096 COLOURS FOR .BMP/.JPG), 320X240 PIXELS, 60MBYTE MEMORY, 24 VDC, REQUIRES NSH5 SPECIAL CABLE, BLACK CASE(REDF SWITCH EMERGENCY)
Fzd-Cbl	FZD, 3D CAMERA BASE PLATE, SHORT DISTANCE VERSION
Fzd-505-10	FZD CONTROLLER, 3-D VISION SYSTEM, INTEGRATED LCD TOUCHSCREEN, PNP
Fz3-350	FZ3 SERIES VISION CONTROLLER, BOX TYPE, STANDARDTYPE, TWO CAMERA, NPN
Zs-Hl1dc41	ZS-H CONTROLLER, ANALOGUE OUTPUT AND PNP DIGITAL OUTPUTS
Fzw-C22p	FZW INTEGRATOR VISION SYSTEM, HIGH RESOLUTION TYPE, 2 CAMERA, HALCON RUN TIME INCLUDED, CAMER LINK, PNP
Fz-Ltw7530br	LED BAR LIGHT, WHITE, 75MM X 30MM
Fq-S25050f	FQ VISION SENSOR, STANDARD FUNCTION, PNP, STANDARD VIEW (50MM)
Fzd-555-10	FZD CONTROLLER, 3-D VISION SYSTEM, CONTROLLER VERSION, PNP
R88d-Kn08h-Ect	G5 ECAT SERVO DRIVE 750W 200VA
Ne1a-Scpu02l	STANDALONE SAFETY NETWORK CONTROLLER, 40 X PNP INPUTS, 8X PNP OUTPUTS, 8X TEST OUTPUTS
Sgmph-08aaa61d-Oy	AC SERVO MOTOR, CUBE-TYPE, 750W, 3000RPM, 2.39NM (EQUIVALENT TO R88M-WP75030H-S2-D)
Zfx-C20-Cd	VISION INSPECTION CONTROLLER, 2 CAMERA, HIGH SPEED, LCD COLOUR TOUCH SCREEN, 24 VDC, NPN OUTPUTS, EMBEDDED BARCODE TOOLS
Fzw-C41p	FZW INTEGRATOR VISION SYSTEM, STANDARD RESOLUTION TYPE, 4 CAMERA, HALCON RUN TIME INCLUDED, CAMER LINK, PNP
Cj1w-Nc881	CJ1 POSITION CONTROL UNIT, 8 AXES, ETHERCAT INTERFACE
3z4m-S22	LASER DISPLACEMENT SENSOR

R88m-Wp75030h-S1-D	SERVO MOTOR 4.1AMP 200V 750W
Fq-S20100f	FQ VISION SENSOR, STANDARD FUNCTION, NPN, WIDE VIEW (240MM), LONG DISTANCE(970MM)
Mc47sr-12-600-X	LIGHT CURTAIN TRASMITTER 600MM LENGTH
Al53	PRINTING LAMP 220V 23AMP TRI-LEVEL 5000WATT OLITE
R88d-Kn10f-MI2	G5 SERIES SERVO DRIVE, ML II TYPE, 1.0KW, 400VAC THREE PHASE
3z4m-J1222-906	LASER DISPLACEMENT SENSOR
F3sj-A0587p14	F3SJ-A0587P14
Cj2h-Cpu64-Eip	CPU WITH BUILT-IN ETHERNET/IP PORT, 50K STEPS PROGRAM, 32K WORDS DATA MEMORY, 32K WORDS X 4 BANKS EM, 2,560 I/O MAX, RS-232C SERIAL PORT, USB PROGRAMMING PORT, 3 EXPANSION RACKS MAX.
Nsa12-Tx11s	INDUSTRIAL PC, 600MHZ INTEL CELERON M, 256MB, 12.1 TOUCHSCREEN TFT COLOUR LCD (1,024 X 768 PIXELS), RAS BOARD, PCI SLOT, 2 X 100BASE-TX ETHERNET PORT, COMPACT FLASH SLOT, 4 X USB PORTS, 2 X RS-232C PO
Ns5-Mq10b-V2	PROGRAMMABLE TERMINAL (HMI), 5.7 INCH, STN, MONOCHROME (16 SHADES OF GREY), 320X240 PIXELS, 2 X RS232 PORTS, 60MBYTE MEMORY, 24 VDC, BLACK CASE
Fz3-L355	XPECTIA FZ-LITE CONTROLLER 4AMP 24VAC 2CAM PNP
Sgmah-03daa6cd-Oy	SERVO MOTOR AC 1.3A 400V 300W 3000RPM 0.955NM