

Olympic Controls

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Olympic Controls Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Olympic Controls Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.



rn	Aıklama
T-80148c24	RELAY T-BAR 24VDC 94OHM
901-24c-12	POWER RELAY, 24PDT, 12VDC, 1A, PLUG IN, PRODUCT RANGE:900 SERIES, CONTACT CONFIGURATION:24PDT, COIL VOLTAGE:12V, CONTACT CURRENT:-, RELAY MOUNTING:PAN
802-24c	SWITCH, TOGGLE, 24PDT, 5A, PRODUCT RANGE:802 SERIES, ILLUMINATION:NON ILLUMINATED, CONTACT CONFIGURATION:24PDT, SWITCH OPERATION:ON-(ON), SWITCH MOUNT
T-8601-51	SNAP IN CONTACT HAND RATCHET CRIMPING TOOL, FOR USE WITH TBAR 88601 AND 88631 SERIES CONNECTORS
801-36c24	POWER RELAY, 36PDT, 24VDC, 5A, PLUG IN, PRODUCT RANGE:800 SERIES, CONTACT CONFIGURATION:36PDT, COIL VOLTAGE:24V, CONTACT CURRENT:-, RELAY MOUNTING:PAN
902-36c	SWITCH, TOGGLE, 36PDT, 1A, PRODUCT RANGE:902 SERIES, ILLUMINATION:NON ILLUMINATED, CONTACT CONFIGURATION:36PDT, SWITCH OPERATION:ON-(ON), SWITCH MOUNT

802-36c	SWITCH, TOGGLE, 36PDT, 5A, PRODUCT RANGE:802 SERIES, ILLUMINATION:NON ILLUMINATED, CONTACT CONFIGURATION:36PDT, SWITCH OPERATION:ON-(ON), SWITCH MOUNT
902-24c	SWITCH, TOGGLE, 24PDT, 1A, PRODUCT RANGE:902 SERIES, ILLUMINATION:NON ILLUMINATED, CONTACT CONFIGURATION:24PDT, SWITCH OPERATION:ON-(ON), SWITCH MOUNT
901-36c-24	POWER RELAY, 36PDT, 24VDC, 1A, PLUG IN, PRODUCT RANGE:900 SERIES, CONTACT CONFIGURATION:36PDT, COIL VOLTAGE:24V, CONTACT CURRENT:-, RELAY MOUNTING:PAN
801-12c24	POWER RELAY, 12PDT, 24VDC, 5A, PLUG IN, PRODUCT RANGE:800 SERIES, CONTACT CONFIGURATION:12PDT, COIL VOLTAGE:24V, CONTACT CURRENT:-, RELAY MOUNTING:PAN
801-48c24	POWER RELAY, 48PDT, 24VDC, 5A, PLUG IN, PRODUCT RANGE:800 SERIES, CONTACT CONFIGURATION:48PDT, COIL VOLTAGE:24V, CONTACT CURRENT:-, RELAY MOUNTING:PAN
801-24c12	POWER RELAY, 24PDT, 12VDC, 5A, PLUG IN, PRODUCT RANGE:800 SERIES, CONTACT CONFIGURATION:24PDT, COIL VOLTAGE:12V, CONTACT CURRENT:-, RELAY MOUNTING:PAN
901-12c-12	POWER RELAY, 12PDT, 12VDC, 1A, PLUG IN, PRODUCT RANGE:900 SERIES, CONTACT CONFIGURATION:12PDT, COIL VOLTAGE:12V, CONTACT CURRENT:-, RELAY MOUNTING:PAN
801-24c24	POWER RELAY, 24PDT, 24VDC, 5A, PLUG IN, PRODUCT RANGE:800 SERIES, CONTACT CONFIGURATION:24PDT, COIL VOLTAGE:24V, CONTACT CURRENT:-, RELAY MOUNTING:PAN
902-48c	SWITCH, TOGGLE, 48PDT, 1A, PRODUCT RANGE:902 SERIES, ILLUMINATION:NON ILLUMINATED, CONTACT CONFIGURATION:48PDT, SWITCH OPERATION:ON, SWITCH MOUNTING:-
802-48c	SWITCH, TOGGLE, 48PDT, 5A, PRODUCT RANGE:802 SERIES, ILLUMINATION:NON ILLUMINATED, CONTACT CONFIGURATION:48PDT, SWITCH OPERATION:ON, SWITCH MOUNTING:-
901-24c-24	POWER RELAY, 24PDT, 24VDC, 1A, PLUG IN, PRODUCT RANGE:900 SERIES, CONTACT CONFIGURATION:24PDT, COIL VOLTAGE:24V, CONTACT CURRENT:-, RELAY MOUNTING:PAN
802-12c	SWITCH, TOGGLE, 12PDT, 5A, PRODUCT RANGE:802 SERIES, ILLUMINATION:NON ILLUMINATED, CONTACT CONFIGURATION:12PDT, SWITCH OPERATION:ON-(ON), SWITCH MOUNT
901-48c-24	RELAY, 48PDT, 24VDC, PANEL, PRODUCT RANGE:900 SERIES, CONTACT CONFIGURATION:48PDT, COIL VOLTAGE:24V, CONTACT CURRENT:-, RELAY MOUNTING:PANEL, COIL TYP
801-48c12	POWER RELAY, 48PDT, 12VDC, 5A, PLUG IN, RELAY TYPE:GENERAL PURPOSE, COIL VOLTAGE VDC NOM:12V, CONTACT CURRENT MAX:5A, CONTACT VOLTAGE AC

	NOM:120V, CON
801-36c12	DUST TIGHT POWER RELAY, RELAY TYPE:GENERAL PURPOSE, COIL VOLTAGE VDC NOM:12V, CONTACT CURRENT MAX:5A, CONTACT VOLTAGE AC NOM:120V, CONTACT VOLTAGE DC
801-36c-115	POWER RELAY, 36PDT, 115VAC, 5A, PLUG IN, PRODUCT RANGE:800 SERIES, CONTACT CONFIGURATION:36PDT, COIL VOLTAGE:-, CONTACT CURRENT:-, RELAY MOUNTING:PANE
901-12c-24	POWER RELAY, 12PDT, 24VDC, 1A, PLUG IN, PRODUCT RANGE:900 SERIES, CONTACT CONFIGURATION:12PDT, COIL VOLTAGE:24V, CONTACT CURRENT:-, RELAY MOUNTING:PAN
801-48c115	POWER RELAY, 48PDT, 115VAC, 5A, PLUG IN, RELAY TYPE:GENERAL PURPOSE, COIL VOLTAGE VAC NOM:115V, CONTACT CURRENT MAX:5A, CONTACT VOLTAGE AC NOM:120V, C
801-24c28	POWER RELAY, 24PDT, 28VDC, 5A, PLUG IN, PRODUCT RANGE:800 SERIES, CONTACT CONFIGURATION:24PDT, COIL VOLTAGE:28V, CONTACT CURRENT:-, RELAY MOUNTING:PAN
802-72c	SWITCH, TOGGLE, 72PDT, 5A, PRODUCT RANGE:802 SERIES, ILLUMINATION:NON ILLUMINATED, CONTACT CONFIGURATION:72PDT, SWITCH OPERATION:ON, SWITCH MOUNTING:-
901-36c-12	RELAY, 36PDT, 12VDC, PANEL, PRODUCT RANGE:900 SERIES, CONTACT CONFIGURATION:36PDT, COIL VOLTAGE:12V, CONTACT CURRENT:-, RELAY MOUNTING:PANEL, COIL TYP