

Opto 22

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Opto 22 Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Opto 22 T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.





| rn | Aıklama |
|-------------------------------------------------|-------------------------------------------------------------------------------------|
| Opto 22, G4ODC5R , 139-2292000 | |
| Opto 22, G4OAC5A5, 139N-2085938 | |
| MP240D4 | ELECTRONIC LOAD RELAY 24-280 VAC 4 A |
| 000777555-81 | Manufacturer: OPTO 22 # Manufacturer part number: SNAP-AIMA # Order number: 3405273 |
| AIMA-4 | OPTO 22# Manufacturer Part Number:SNAP-AIMA-4# Order number:4472123 |
| MP240D4-17 | Solid State Role |
| G4 ODC24 | OUTPUT 60VDC 3A 24V LOGIC |
| IDC5B I/O MODULE | |
| 007376B | |
| DC60S524 | |
| G4-Pb4 | |
| Snap-Rackdinb-Each | |
| Snap-Aima-32-Fm | SNAP 32-CH -20MA TO +20MA ANALOG CURRENT INPUT MODULE-FM APPROVED |
| G4-Odc5a | |
| Odc-24 | |
| G4 Idc5 | Input Module |
| Snap-B4m | B-Series 4 Module Rack |
| Snap-Aod-29 | |
| G4d16r | Opto 22 Mystic Brick Controller Kit |
| G4a8l-Cover | |
| Oac-5q | |
| Iac5p | |
| Snap-Odc5r5fm | |
| G4-Ad4 | |
| G4lc32f1m | |
| Snap-D8mc-P | |
| Iac-5a | |
| Snap-Idc-32-Fm | |

| | |
|------------------------------------|----------------------------------------------------|
| Snap-B3000ha | |
| G4-Batt32 | |
| Ad-18t | |
| Oac24a | |
| G4ls | |
| G4oac24ama | |
| Snap-Pac-Rck12-Fm | |
| Snap-Psudin | |
| Strap8 | |
| 240d45-18 | |
| Snap-Rackdin | |
| Ad-4 | |
| Pb32h | |
| Odc-5 | |
| Groov-Svr-Win-Snap | GROOV SERVER FOR WINDOWS FOR SNAP PAC ONLY |
| Pb16mds | |
| Snap-It-Wm4 | |
| Snap-Aoa-23 | |
| N-Tron700-Pm | |
| 005157d | |
| G4-Odc24-1.5a | |
| Snap-Odc5rfm | |
| Fuseg4 | |
| Pb-16p1 | |
| Ca2 | |
| Snap-Idc5q | |
| Snap-Aitm-C | |
| 001818b | |
| Optoemu-Snr-Dr1 | ENERGY MONITORING UNIT WITH DEMAND RESPONSE CAPABI |
| Ex-2 | |
| 001836cw | |
| Brickstrap | |
| Fuse01g4 | |
| G4-Mod-Sockets | |
| 005246c | |
| Pb-32p2 | |

| | |
|--------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|
| R0430 | |
| 001828d | |
| N-Tron7506gx2 | |
| Groov-Ar1 | GROOV BOX |
| 380d25 | |
| B1 | |
| Ac38a | |
| Snap-Pac-R2-W | PROGRAMMABLE CONTROLLER, WIRELESS, ACCESSORY TYPE:PROGRAMMABLE AUTOMATION COMMUNICATION, FOR USE WITH:SNAP PAC SYSTEM, SIGNAL INPUT TYPE:ETHERNET, RS- |
| Iac-5aq | |
| Ad2t | |
| Pb-16s | |
| 4860000-7617 | CLASSIC CONTROLLER |
| 240a45 | |
| Snap-It-Pm-Ads | CONTROLLERS, PEAK REFLOW COMPATIBLE (260 C):NO, LEADED PROCESS COMPATIBLE:NO, ROHS COMPLIANT: NO |
| Ad17t | |
| Snap-Aiv-32 | I/O MODULE, VOLTAGE RATING:5V, CURRENT RATING:150MA, LENGTH:83.13MM, EXTERNAL WIDTH:82.55MM, EXTERNAL DEPTH:18.29MM, FOR USE WITH:OPTO22 SNAP PAC SYST |
| Snap-Enet-D64 | |
| Ad14t | |
| Snap-Idc-16 | |
| 005157c | |
| G4d16l-Cover | |
| 240d50 | |
| M4sarc | |
| G4brickbase | |
| Til114 | |
| Da-6 | |
| G4iac24 | I/O Module |
| Snap-Aitm-8-Fm | |
| Snap-Idc5ma | |
| Snap-Hd-Acf6 | |
| Ioprojectpro | IOPROJECT PROFESSIONAL SOFTWARE SUITE, FOR USE WITH:OPTO22 SNAP PAC LEGACY SYSTEM CONTROLLERS AND I/O UNITS, KIT CONTENTS:IOPROJECT PROFESSIONAL COMPL |

| | |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Iac15a | |
| G41dc5-Input10-32vdc | |
| Ac40b | |
| Snap-Odc5snkfm | |
| G4-Pb16hc | |
| G4ad24 | |
| Dc60s-3 | |
| Snappacr2 | |
| 001788b | |
| Snap-Aov-25 | Dual Channel Output Module SNAP-A0V-25 |
| G4 Oac5afm | |
| 139 | |
| Snap-Idc5-Ht | |
| Snap-Brs | |
| Dc60s-5 | |
| Z240d10-17 | |
| Oac15c | |
| Ad-3 | |
| Ac-8a | |
| G4d16r-Brain-Board | |
| Fuse05 | |
| Oac5 | OAC5 AC Output Relay Module OAC5 OPTO 22 |
| Odc5p | |
| G4abrick | |
| G4-Ad16 | |
| G4lc325x | CONTROLLER 200 MYSTIC |
| Pci-Ac5 | |
| Snap-Scm-Profi | |
| Ssr-Hs | |
| Snap-TeX-Fb16-H | |
| Snap-Fieldconb | |
| Optoterminal-G75 | CONTROLLERS, DISPLAY, METER DISPLAY TYPE:TFT-LCD COLOUR, DISPLAY RESOLUTION:640 X 480 PIXELS, SUPPLY VOLTAGE RANGE:10VDC TO 26VDC, OPERATING TEMPERATU |
| Snap-Hd-Cbf6 | |
| Od6 | |
| Optoemu-Cts-2000-600 | |

| | |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| G4-Ad18 | |
| Snap-Pac-S1-W | PROGRAMMABLE CONTROLLER, WIRELESS, NO. OF DIGITAL INPUTS:-, NO. OF DIGITAL OUTPUTS:-, ACCESSORY TYPE:PROGRAMMABLE AUTOMATION COMMUNICATION, FOR USE W1 |
| 120d3 | |
| Snap-Rokdin | |
| Snap-Pac-Eb1-W | I/O PROCESSOR WIRELESS, CURRENT RATING:750MA, LENGTH:93.98MM, EXTERNAL WIDTH:83.82MM, EXTERNAL DEPTH:46.36MM, FOR USE WITH:OPTO22 SNAP PAC SYSTEMS, AC |
| Cac15 | |
| G4odc5afm | |
| Ad-10t | |
| Od2 | |
| Circuitcard | |
| Snap-Odc5src | |
| 8 | |
| G4-Oac5a5 | |
| Snap-Scm-W2 | |
| Fuseg4b | |
| G4-Swin | |
| 007308d | |
| Oac-5 | |
| Snap-Pac-S2 | PROGRAMMABLE CONTROLLER, WIRELESS, ACCESSORY TYPE:PROGRAMMABLE AUTOMATION COMMUNICATION, FOR USE WITH:SNAP PAC SYSTEM, LEADED PROCESS COMPATIBLE:NO, P |
| Icmoc3012 | |
| B3000 | |
| Snap-Aitm | |
| N-Tron702m12-Pk | |
| N-Tron516tx-A | |
| 120a10 | |
| Ca10 | |
| G4-Lc32sxf1m | |
| 001830f | |
| 005158g1 | |
| Snap-Fuse10ab | |
| Da8 Power Module | |
| Optotermcable-G70 | |
| Snap-Odc-32-Src | |

| | |
|-------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Snap-D4mc | |
| Ad15t | |
| Ad-16t | |
| Snap-Odc5r | 4-Ch Reed Relay Digital Output Module SNAP-0DC5R |
| Snap-Oac5ma | |
| Oac5-10pack | 10PK AC Output Relay Module OAC5 OPTO 22 |
| G4rcommkit | |
| G4oac15a | |
| Iac-5 | |
| G4-Idc5k | |
| Snap-Tex-32 | |
| Snap-B4 | |
| 001772a | |
| Snap-Iac-K-16 | |
| M4-Ethernet | |
| Snap-Enet-S64 | |
| N-Tron517fx-A-St-S | INDUSRTIAL WIRELESS RADIO, NETWORK SPEEDS:10 / 100 GIGABIT, NO. OF PORTS:1, SUPPLY VOLTAGE MAX:49VDC, SUPPLY VOLTAGE MIN:20VDC |
| G4-D16r | |
| G4-Ad11 | |
| Pb24-Hq | |
| Model : Mp 240 D4 | |
| Pb-16md | |
| 4187 | |
| Snap-Aod-29-Hfi | |
| Snap-Aoa-23-Isrc-Fm | |
| 240di45 | |
| G4strip | |
| G4-Aitm | |
| N-Tron716tx | INDUSRTIAL ETHERNET SWITCH, NO. OF PORTS:8, NETWORK SPEEDS:10 / 100 GIGABIT, NO. OF PORTS 10/100TX:6, NO. OF PORTS 100FX:2, SUPPLY VOLTAGE MAX:30VDC |
| Hh6 | |
| 575di45-12 | |
| G4idc5d | |
| 006015b | |

| | |
|----------------------------------|------------------------------------------------------------|
| 480d15-12 | |
| 100023 | |
| Odc24 | |
| G4-Idc-5ma | |
| Strap2q | |
| E2 | |
| G4-Lc32isa | |
| Snap-Airtd-1k | |
| 22lc4a | |
| Snap-B12-Mc | |
| G4-Idc5g | |
| B5 | |
| Oac5ah | |
| Pb4h-6771 | |
| G4-Iac24 | |
| G4p2245a | |
| B6 | |
| Snap-B12m | SNAP B-Series 12-module Rack |
| 32n107e | |
| Fuse02b | |
| N-Tronntsfp-Tx | |
| Od8 | |
| 005081aw | |
| 001234b | |
| Snap-Aoa-23-Isrc | |
| Snap-Pac-Eb1-Fm | |
| Snap-Aima-Isrc | |
| G4lc32sx | Opto 22 Mystic 200SX Processor Module 200SX |
| Snap-Hd-G4f6 | |
| Snap-Aoa-23-Ih | |
| Pactermssd | PAC TERMINAL SECURE STRATEGY DISTRIBUTION (SSD) (DOWNLOAD) |
| Pb16l | |
| 185175a01 | PC BOARD G4HDM |
| Ic545j | |
| B3000-B-Gt | |
| Strap4q | |

| | |
|---------------------------------|-----------------------------------------------------------------------------------------------------|
| 001830a | |
| Snap-It-Rm-D64 | CONTROLLERS, PEAK REFLOW COMPATIBLE (260 C):NO, LEADED PROCESS COMPATIBLE:NO, ROHS COMPLIANT: NO |
| 001774b | |
| 57456 | |
| G4-Idc24 | |
| Snap-Rck-B2m | |
| P240d4-17 | |
| Idc-5d | |
| Snap-TeX-Drc10 | |
| Snap-Idc-32d | |
| Hh8 | |
| G4aiva | CIRCUIT BOARD ANALOG I/O |
| Snap-TeX-Cbe6 | |
| Snap-Brs-Ha | |
| Ac-24at | |
| P120d2 | |
| G4-Odc5r5 | |
| G4-Ps245a | |
| G4b200 | |
| Ac-42 | |
| Pb-16t | |
| 001848g | |
| 200sx | |
| B2 | |
| G4-Ad7 | |
| Pb-Sa | |
| G4-Ior | |
| Ac36 | |
| Snap-Rpsw | |
| 001842d | |
| Snap-Aiv-Hdb-Fm | |
| Pbmoa | |
| Snap-M64 | |
| Snap-Idc5fm | |
| Ac422 | |

| | |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| 8883 | |
| G4-Oac5a | |
| 84113310 | |
| Mp380d4 | |
| Da-3 | |
| Snap-Up1-M64 | PROGRAMMABLE LOGIC CONTROLLER, METER DISPLAY TYPE:LED, PEAK REFLOW COMPATIBLE (260 C):NO, LEADED PROCESS COMPATIBLE:NO, FEATURES:MULTIFUNCTION 64-POIN |
| Oac-27 | |
| G4-A8p | |
| Snap-Odc5snk | |
| Snap-Hd-Bf6 | |
| Ac-34 | |
| Snap-Pac-Eb1 | |
| 001836fwo | |
| M4lcsx | |
| G4-Odc5 | |
| G4-Oac24a | |
| 308tx-N | |
| Snap-Aima-Ih | |
| G4-Ad12 | |
| G4rax | Opto 22 Mystic Brick Controller Kit |
| Snap-TeX-Mr10-16c | |
| Oac5 | |
| Ac-37 | |
| Smiac5 | |
| Icmoc3040 | |
| G4oac5ama | |
| G4-Oac5ma | |
| Snap-Aiv-72h | |
| G4-Odc24a | |
| G4ps24xb | |
| Optointmb | |
| G4idc5 | |
| Optoterminal-G70 | CONTROLLER OPERATOR INTERFACE, DISPLAY RESOLUTION:320X240, OPERATING TEMPERATURE RANGE:-10C TO +60C, PEAK REFLOW COMPATIBLE (260 C):NO, FOR USE WITH:S |
| Odc-5a | |

| | |
|----------------------------------|-------------------------------------------|
| G4lc32sxser | |
| M4ps48d | |
| Snap-Fuse1ac | |
| Snap | |
| G4-Idc5b | |
| G4odc5r | |
| G4lc32arc | Opto 22 Mystic Brick 485 Interface Module |
| Snap-Airt-d-10 | |
| Idc-5q | |
| Snap-Rck-M2b | |
| Snap-Oac5-Ifm | |
| Icilq55 | |
| G4-Pem-Nuts | |
| 6017c | |
| G4odc5r5fm | |
| G4-Iac5a | |
| Ad-6t | |
| Snap-Aivrms-I-Fm | |
| Aml21fba2aa | |
| G4-Ad25 | |
| 480d25-12 | |
| Snap-Hd-Bf1 | |
| G4lc32ram | |
| Pb-16a | |
| Snap-Scm-232 | |
| G4lc4c | |
| Snap-Aima-Hdb-Fm | |
| Snap-Air400k-8 | |
| G4 0ac5 | Output Module |
| 001792d | |
| Pb16he | |
| M4ps125d2 | |
| 889 | |
| Dc60p | |
| 001830j | |

| | |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| G4da10 | |
| Snap-Odc5-Ifm | |
| Snap-Lcm-4 | |
| 240d3 | |
| Snap-Aivrms-I | |
| Ic4n27 | |
| Da4t0 | |
| Ad-5t | |
| Snap-Omr6-A | |
| 001836kwo | |
| Snap-Modtool | |
| Groov-Ar1-Snap | GROOV BOX FOR SNAP PAC ONLY |
| G4pb32dec | 32-channel I/O Module Rack for DEC Computers 5292 |
| G4-Da4 | |
| G4hdm | |
| Pb-4r | |
| G4da6 | |
| Ps115-1.5a | |
| G4strapb | |
| Odc-24a | |
| Odc22 | |
| N-Tron306fx2-N-St | |
| Mp240d2 | |
| G4-Lc32isaser | |
| Snap-Pac-S2-W | PROGRAMMABLE CONTROLLER, WIRELESS, NO. OF DIGITAL INPUTS:-, NO. OF DIGITAL OUTPUTS:-, ACCESSORY TYPE:PROGRAMMABLE AUTOMATION COMMUNICATION, FOR USE WI |
| N-Tron702m12-W | WIRELESS RADIO WITH 3 MIMO ANTENNAS |
| Pb-16h | |
| Oac24h | |
| 001784a | |
| Snap-Pac-Rck8 | |
| Snapaima4 | |
| G4iac15a | |
| Snap-Iac-A-16 | |
| Safetycover | |
| Mp240d4 | |

| | |
|--------------------------------------|--------------------------------|
| 575d4521 | |
| Snap-It-Emu1 | OPTO 22 ENERGY MONITORING UNIT |
| Lcm4proc | PC BOARD |
| Ictd | |
| Snap-Idc5g | |
| Mp240d4-17 | |
| Optoemu-Cts-0750-150 | |
| 240d107 | |
| Ac-8 | |
| Oac-5adc | |
| Pb-16hc | |
| 1662 | |
| Pb-4h | |
| Snap-Rackdinb | |
| M4-Ps120a | |
| 240d10-17 | |
| G4-Lc32mb | |
| Pb32p2w | |
| Snap-Aiv-4 | |
| Snap-Pac-Rck4 | |
| Snap-B8m | |
| 007308e | |
| Icmoc2a4010 | |
| Snap-Pid-V | |
| Da-4 | |
| Term1 | |
| Pb4md | |
| G4fuse4a | |
| Fuse125 | |
| 380d45 | |
| Snap-Airate | |
| 000201uwo | |
| G4-Idc5d | |
| Snap-Pac-Eb2-Fm | |
| Odc-15 | |
| 001848d | |

| | |
|----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|
| G4-Ad3 | |
| Sb1-Rs485 | |
| N-Tron304tx-N | |
| Dc200p | |
| Z240d10 | |
| G4-D16l | |
| G4b2 | |
| G4oac5a | |
| 5300-0003 | |
| Ich11av2 | |
| 575d30-Hs | |
| Groov-At1 | GROOV BOX |
| G4 Iac5 | Input 120 VAC 5Volt Logic 591 |
| Snapscm232 | |
| Ad-13t | |
| Ad-7 | |
| M4-Rtu | MODULAR CONTROLLER, FOR USE WITH:FACTORYFLOOR SOFTWARE, LEADED PROCESS COMPATIBLE:NO, PEAK REFLOW COMPATIBLE (260 C):NO, ROHS COMPLIANT: NO |
| Snap-Iac5fm | |
| Oac5a | Opto 22 OAC5A Output Relay Module |
| Snap-B3000-Brain | |
| Snap-Aima-I | |
| Snap-D12mc | |
| Groov-At1-Snap | GROOV BOX FOR SNAP PAC ONLY |
| G4ad26 | |
| G4-Iol | |
| 001828h | |
| G4 Odc5 | ODC5 Output Module |
| Ac24t | |
| Snap-Aoa-3 | |
| 001838d | |
| Pb4a | |
| G4-Oac-5afm | |
| G4 Oac5 | Opto 120V Fuse 890 |
| Da7t | |

| | |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Snap-Pac-R2 | |
| Strap2 | |
| Snap-Fuse2ab | |
| Optoemu-Cts-1250-400 | |
| Idc5f | |
| Icmct273 | |
| Snap-Pdprs64 | |
| G4-Idc5g | |
| Snap-Omr6-C | |
| G4-Pb32r | |
| Iac-5g | |
| 001784b | |
| Pb16ma | I/O BOARD |
| Optoterminal-G20 | |
| Idc-24 | |
| G4dbrick | |
| Odc5r | ODCR5 Dry Contact Output |
| P240d4 | |
| Snap-Rck-M2pb | |
| Snap-Ailc-2 | |
| Lc2dc | |
| M4senet-100 | COMPUTERS, NETWORK INTERFACE CARDS, LEADED PROCESS COMPATIBLE:NO, PEAK REFLOW COMPATIBLE (260 C):NO, ROHS COMPLIANT: NO |
| G4-Ra | |
| G4d32eb2 | ETHERNET I/O MODULE, 32 CH, LENGTH:266.7MM, EXTERNAL WIDTH:177.8MM, EXTERNAL DEPTH:100.3MM, FOR USE WITH:G4D32RS MISTIC DIGITAL RACK, ACCESSORY TYPE:E |
| G4hdmr | |
| Snap-Idc5d | 4 Channel DC Input Module IDC5D |
| Fuse05b | |
| Snap-Scm-Ssi | |
| Snapodc5r Snap-Odc5r | |
| Snap-Pac-R1-W | PROGRAMMABLE CONTROLLER, WIRELESS, ACCESSORY TYPE:PROGRAMMABLE AUTOMATION COMMUNICATION, FOR USE WITH:SNAP PAC SYSTEM, SIGNAL INPUT TYPE:ETHERNET, RS- |
| Oac-15 | |
| 005158f | |
| G4-Ram4m | |

| | |
|----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| Opto22odc5 | |
| 120d10 | |
| 001788k | |
| G4-Odc5fm | |
| Snap-Idc-32n | |
| G4-Pb8h | |
| Iac5e/24 | |
| G4odc5 | |
| Snap-Paclc | LEARNING CENTER, KIT CONTENTS:SNAP PAC LEARNING CENTER GUIDE, PAC PROJECT 8.0 SOFTWARE WITH PAC PROJECT DOCUMENT, FOR USE WITH:ETHERNET-BASED SYSTEMS |
| Snap-S2din | |
| Snap-Up1-D64 | CONTROLLERS, FOR USE WITH:SNAP ULTIMATE I/O ETHERNET BRAIN 64 POINT DIGITAL, LEADED PROCESS COMPATIBLE:NO, PEAK REFLOW COMPATIBLE (260 C):NO ROHS COMP |
| Snap-A0a-23-Isrc | |
| Pb4moa | |
| Snap-Aov-27 | |
| Snap-It-Rm-Ads | MONITORING UNIT RACK-MOUNTED |
| Pb-32hq | |
| G4-Da5 | |
| Idc-5b | |
| G4lc4a | |
| Opto-22-B6 | |
| Snap-Odc5srcfm | |
| Ad1 | |
| N-Tron7026tx | ETHERNET SWITCH, MANAGED, 24 COPPER PORTS, 2 MINI-GBIC PORTS, RACKMOUNT |
| Snap-Pac-R2-Fm | SNAP PAC R-SERIES PROGRAMMABLE AUTOMATION CONTROLLER ON-THE-RACK-FM APPROVED |
| Ac-6 | |
| Optodriver | |
| Odc-5q | |
| G4-Ad5 | |
| G4 Idc5d | Input Module |
| Snap-Odc-Hdb-Fm | |
| Snap-Aiv-I | |
| G4idc5-Swnc | |
| Dc60s3 | |

| | |
|-------------------------------------|---------------------------------------------------------------------------------------------|
| 240d10 | |
| Plc-Manual-Cd | |
| Snap-Up1-Ads | |
| Snap-Iac5ma | |
| E-31a | |
| G4pb16l | |
| Snap-Aiarms | |
| Snap-D12mc-P | |
| Fuse01g4b | |
| Snap-Pac-Sb2 | |
| Odc15a | |
| G4-Odc-5ma | |
| Oac-15a | |
| Snap-TeX-Mr10-16 | |
| Snappacr1 | |
| M4-Sser | |
| G4-Rs | |
| Snap-D12m | |
| N-Tron508fx2-A-St-S | ETHERNET SWITCH, MANAGED, 6 COPPER, 2 FIBER, MULTIMODE, ST, PLUG-AND-PLAY, STD. TEMPERATURE |
| Lcm4-Serial | |
| Snap-Aiv2-I | |
| Ac40c | |
| Iac5 | AC Input Module IAC5 OPTO 22 |
| Oac5a-11 | |
| G4-Ad13 | |
| Snap-Scm-St2 | |
| Snap-Aov-5 | |
| Snap-Aivrms | |
| Fuse01g4 | |
| Snap-TeX-Cbs6 | |
| 141 | |
| 25904 | |
| Snap-Aiv | 2 Channel Analog Input Module AIV |
| Snap-Odc-32-Src-Fm | |
| Snap-D6mc | |

| | |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| 416105 | |
| Snap-Pac-Rck8-Fm | |
| Snap-Odc5asnk | |
| Snap-Aiarms-I | |
| G4-Hdal | |
| 32n106e | |
| Til111 | |
| Snap-Pac-Eb2-W | I/O PROCESSOR WIRELESS, CURRENT RATING:750MA, LENGTH:93.98MM, EXTERNAL WIDTH:83.82MM, EXTERNAL DEPTH:46.36MM, FOR USE WITH:OPTO22 SNAP PAC SYSTEMS, AC |
| G4-Hdar | |
| G4-D16I-Base | |
| Idc-15 | |
| Oac-5a5 | |
| Snap-Aictd-4 | |
| Snap-Io4ab-Lc | LEARNING CENTER, KIT CONTENTS:LEARNING CENTRE USERS GUIDE, ETHERNET/IP PROTOCOL GUIDE, ETHERNET/IP CONFIGURATOR, FOR USE WITH:OPTO22 SNAP INPUT / OUTP |
| Optoemu-Pt600 | |
| 007308f | |
| G4ac5 | |
| Snap-D4mc-P | |
| M4ps240a | |
| Optoemu-Act-0750-100 | |
| Snap-Aiv-8 | |
| G4-Lc32arc | |
| G4-Idc15 | |
| G4-Pb32h | |
| Ac-30a | |
| G4-Strap | |
| Snap-Odc-32-Snk | |
| 24oa45 | |
| Snap-Enet-Rtc | |
| N-Tron900b-N | |
| Snap-Ailc | |
| G4ram1m | |
| Snap-D8mc | |

| | |
|-------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| G40ac24a | |
| G4ra-Card | |
| Mp-120d2 | |
| Odc5 | ODC5 Output Module |
| Ca8 | |
| G4-A8I-Base | |
| P240d2 | |
| 120d45 | |
| Snap-Odc5a-Ifm | |
| Optoemu-Cts-0750-70 | |
| 22-Iac5 | |
| Snap-Aima-4 | |
| Snap-Ps5-24dc | 24 VDC Logic Power Supply OPTO 22 |
| Snap-TeX-Cbo6 | |
| Ad8 | |
| 8882 | |
| Masarcf | |
| G4-Ad22 | |
| Snap-Aimv2-4 | |
| G4-Rd | |
| Oac-5p | |
| Da-8 | |
| Dc60mp | |
| 551ps5014 | |
| Dc 60 Mp | |
| Optointab | |
| Snap-Scm-Can2b | |
| 240di10 | |
| N-Tron716fx2-St | INDUSRTIAL ETHERNET SWITCH, NO. OF PORTS:8, NETWORK SPEEDS:10 / 100 GIGABIT, NO. OF PORTS 10/100TX:8, SUPPLY VOLTAGE MAX:30VDC, SUPPLY VOLTAGE MIN:10V |
| Idc-5bq | |
| Fuse01b | |
| Idc5q | |
| Pb-8ah | |
| Hh4 | |
| G4a8r | Opto 22 Mystic Brick Controller Kit |

| | |
|----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|
| M4-Enclosure | |
| 005247b | |
| Groov-Svr-Win | GROOV SERVER FOR WINDOWS |
| B200 | |
| Snapidc5a | |
| G4pb32jy-In | 32-channel I/O Module Rack |
| Oac-24 | |
| Idc5 | Input Module |
| G4-Odc24 | |
| P120d4 | |
| Snap-Aictd-8 | |
| G4-A8l | |
| Model: Dc 200 Mp | |
| Snap-Scm-485-422 | |
| Ic817cd | |
| G4-A8r | |
| Snap-Oac5-I | |
| Snap-Aipm-3v | |
| Snap-Pac-Sb1 | |
| Idc5p | |
| G4-Pb16h | |
| G4ad19 | |
| Cjc | |
| 575d15-12 | |
| Pci-Ac51 | |
| 240a25 | |
| 240d30-Hs | |
| Z120d10 | |
| Snap-Pac-R1 | PROGRAMMABLE CONTROLLER, FOR USE WITH:SNAP PAC SYSTEM, ACCESSORY TYPE:PROGRAMMABLE AUTOMATION COMMUNICATION, LEADED PROCESS COMPATIBLE:NO, PEAK REFLOW |
| Ac-7a | |
| G4pb16j | |
| G4pb24 | |
| G4-Lc32int | COMM BOARD |
| Pb32p2wo | |

| | |
|----------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| Da-3t | |
| B3000-B | |
| Fuse.125b | |
| G4lc32isalt | |
| Snap-Ps5 | |
| 590-0513-00 | |
| Snap-Aiv-32-Fm | ANALOG INPUT MODULE, 5VDC, 150MA, FOR USE WITH:OPTO22 SNAP PAC SYSTEMS, VOLTAGE RATING:5VDC, CURRENT RATING:150MA, LENGTH:83.13MM, EXTERNAL WIDTH:82.5 |
| G70 | |
| Snap-Pac-Rok | SNAP-PAC REDUNDANCY OPTION KIT, 32VDC, VOLTAGE RATING:32VDC, LENGTH:93.98MM, EXTERNAL WIDTH:83.82MM, EXTERNAL DEPTH:46.36MM, ACCESSORY TYPE:SNAP-PAC R |
| Snap-It-Rm-Uads | CONTROLLERS, PEAK REFLOW COMPATIBLE (260 C):NO, LEADED PROCESS COMPATIBLE:NO, ROHS COMPLIANT: NO |
| G4-Exl | |
| Groov-Snap-Upg | SNAP UPGRADE TO |
| 001848e | |
| Da-4t | |
| Pcie-Ac51 | |
| Iac24a | |
| Opto 22 Odc5q Quad Pak 4-Channel Dc Output 5-60 Vdc, 5 Vdc Logic | |
| 70odc5 | |
| G4-Ad10 | |
| G4ad6hs | |
| 240di25 | |
| 240a10 | |
| Ad-6hs | |
| 240d25 | |
| Ich11c1 | |
| Odc5q | |
| G40dc24 | I/O Module |
| Lc32sxf | |
| Ic4n35ssm | |
| G4oac5fm | |
| Ac42at | |
| Snap-Fuse1ab | |

| | |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| Pb16 | |
| G4-Base | |
| 716tx | ETHERNET SWITCH |
| Pbsc | |
| Ac40a | COMPUTERS, INTERFACE CARDS, PEAK REFLOW COMPATIBLE (260 C):NO, LEADED PROCESS COMPATIBLE:NO, FEATURES:FIBER OPTIC REPEATER, 120VAC, ROHS COMPLIANT: NO |
| 001717a | |
| Snap-Aima2-I | |
| Snap-It-Pm12 | SNAP PAC SYSTEM 12-MODULE ENCLOSURE, NEMA 3R, META |
| Snap-B3000-Modbus | SNAP Modbus I/O unit B3000 BRAIN |
| Snap-Odc5a-I | |
| Idc5a | |
| B11 | |
| Snap-Idc5-Fast | |
| Snap-Scm-Mch16 | |
| Snap-It-Rm-Pac-R1 | SNAP IT RM RACK WITH A PAC-R1 |
| G4da8 | |
| Pb16k | |
| G4ad20 | |
| Snap-Pac-Rck12 | |
| G4d16ls-Cover | |
| Lc2 | |
| G4odc24 | |
| Optoemu-Snr-3v | CURRENT SENSOR, 8 CHANNELS, 0.2%, ACCURACY %:0.2%, ACCURACY:0.2 %, EXTERNAL DEPTH:11.4CM, EXTERNAL HEIGHT:34.3CM, EXTERNAL WIDTH:15.2CM, INPUT VOLTAGE |
| 005078a | |
| Ad-10t2 | |
| Snap-Aitm-4i | |
| Snap-Pac-R1-Fm | SNAP PAC R-SERIES PROGRAMMABLE AUTOMATION CONTROLLER-FM APPROVED |
| Ic2502 | |
| Snap-B16mc | |
| G4-Ad17 | |
| Snap-Airate-Hfi | |
| G4d16r-Cover | |
| Da-5 | |

| | |
|--------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| G4-Lc4 | |
| Snap-Aiv-72 | |
| Snap-B6 | |
| 005746b | |
| 240d2s | |
| Snap-It-Rm16 | SNAP PAC SYSTEM 16-MODULE ENCLOSURE, METAL, RACK-M |
| G4fuseclip | |
| Pci-Ac28 | |
| Softpac | |
| G4odcs | |
| 006876b | |
| Snap-Lcsx | |
| Snap-B16mc-P | |
| Oac5a/120 | |
| Dc60s5 | |
| 001842e | |
| Odcq-5 | |
| Ad7 Non Rohs Analog Input Module | |
| 005326b | |
| 22 | |
| Oac-5a | |
| 001842f | |
| Smidc5 | |
| Snap-Label-4b | |
| Pbmd | |
| 001744b | |
| N-Tron904fx-Sc | SLIDE IN MODULE FOR 900 SERIES CHASSIS, 4 FIBER, MULTIMODE, SC CONNECTORS |
| G4b100 | |
| 001788l | |
| G4mservo | PC SERVO BOARD ASSEMBLY |
| Ac-28 | |
| B3000-B-Omux | |
| G4lc4b | |
| G4-Idc5 | |
| N-Tron708fx2-St | INDUSRTIAL ETHERNET SWITCH, NO. OF PORTS:8, NETWORK SPEEDS:10 / 100 GIGABIT, NO. OF PORTS 10/100TX:8, SUPPLY VOLTAGE MAX:30VDC, SUPPLY VOLTAGE MIN:10V |

| | |
|-------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| Snap-It-Pm-Ads-Plus | CONTROLLERS, PEAK REFLOW COMPATIBLE (260 C):NO, LEADED PROCESS COMPATIBLE:NO, ROHS COMPLIANT: NO |
| Snapidc32 | |
| Pb-4ah | |
| Snapphorp | |
| Optotermcable | |
| 240d25-17 | |
| Snap-Modlatchb | |
| Snap-Iac5a | |
| Snap-D4m | |
| Smapaoa3 | |
| N-Tron702-W | INDUSRTIAL ETHERNET SWITCH, NO. OF PORTS:8, NETWORK SPEEDS:10 / 100 GIGABIT, NO. OF PORTS 10/100TX:6, NO. OF PORTS 100FX:2, SUPPLY VOLTAGE MAX:30VDC |
| Pb16j | |
| 001784d | |
| 5196b | |
| Snap-Aima-32 | I/O MODULE, VOLTAGE RATING:5V, CURRENT RATING:150MA, LENGTH:83.13MM, EXTERNAL WIDTH:82.55MM, EXTERNAL DEPTH:18.29MM, FOR USE WITH:OPTO22 SNAP PAC SYST |
| Pb-24 | |
| Snap-Strap | |
| Pb32hqwo | |
| Ocb-003 | |
| Fuse02 | |
| Ac-5 | |
| 1848 | |
| 480d45-12 | |
| Ad11t | |
| Iac24/120 | |
| Pb16h | |
| Snap-Fuse7.5ab | |
| Iac-15 | |
| Snap-Idc5-Fast-A | |
| Term-2 | |
| N-Tron702-W-Pm | |
| Optoemu-Snr-Dr2 | ENERGY MONITORING UNIT WITH DEMAND RESPONSE CAPABI |
| B4pamux | |

| | |
|-----------------------------------|---------------------------------------------------------------------|
| N-Tron709fx-St | ETHERNET SWITCH, MANAGED, 8 COPPER 1 FIBRE, MULTIMODE, ST CONNECTOR |
| Snap-Pac-Eb2 | |
| Iac15n | |
| Snap-Pac-R1-B | SNAP PAC R-SERIES PROGRAMMABLE AUTOMATION CONTROLL |
| G4-Pb32dec | |
| Ac30b | |
| Ieee488 | |
| Output-Switch | |
| Optoopcserver | |
| G4d32eb2-Upg | |
| G4-Reg | |
| M4dualarc | |
| E1 | |
| 240d45sp | |
| Hh10 | |
| Snap-Ps24 | |
| Snapodc32s | |
| Ac31a | |
| Snap-Pac-Rck16-Fm | |
| Snap-Pac-Rck4-Fm | |
| Snap-TeX-Mr10-4 | |
| G4-Odc24afc | |
| 120d5 | |
| Snap-TeX-Rckcap | |
| 007214d | |
| Ac38b | |
| Optotermcable-G75 | |
| Input-Switch | |
| Snap-Aima | Analog Current Input Module |
| Snapaov5 | |
| Snap-Odc-Hdb | |
| G4da9 | |
| M4rtux | |
| Snap-Wirestrapb | |
| Pb-24q | |

| | |
|------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| Snap-B3000-Enet | |
| Snap-Idc5k | |
| N-Tron712fx4-St | ETHERNET SWITCH, MANAGED, 12 PORT 8 COPPER, 4 FIBER ST CONN |
| G4-Pb8 | |
| Ac422-001734a | |
| 001828g | |
| Snap-Aitm-I | |
| Snap-Mr10 | |
| 001662a | |
| Pb16s1 | |
| Snap-Pac-S1-Fm | SNAP PAC REDUNDANCY OPTION KIT, NO. OF DIGITAL INPUTS:-, NO. OF DIGITAL OUTPUTS:-, ACCESSORY TYPE:I/O MODULE, EXTERNAL DEPTH:44.4MM, EXTERNAL WIDTH:10 |
| Snap-Odc-32-Snk-Fm | |
| Snap-Pac-Rck16 | |
| 001788j | |
| Ac47 | |
| Snapenetd6 Snap-Enet-D64 | |
| Snap-Idc5 | Digital Input Module |
| N-Tron708tx | |
| G4ps245b | |
| Snappacrc8 | |
| G4-0ac5a | |
| Snap-Aitm2-I | |
| Zxr0pt022b1 | |
| Lcm4 | |
| 240d45-17 | |
| Snap-Modfusehldrb | |
| Snap0dc32src | |
| Snap-Aipm-3 | |
| 001836cwo | |
| Anapaitm | |
| Pacprojectpro | SOFTWARE, KIT CONTENTS:PAC PROJECT PROFESSIONAL COMPLETE SOFTWARE SUITE, DOCUMENTATION ON CD, PLUS PRINTED DOCUMENTATION, ACCESSORY TYPE:PROJECT PROFE |
| Snap-Aiarms-I-Fm | |
| Snap-Fuse4ab | |

| | |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| Odc-5r | |
| Zxropto22b1 | |
| Snap-B16m | |
| G4-Lc32sx | |
| G4-Pb4r | |
| Snap-B8mc-P | |
| Ad12t | |
| N-Tron306fx2-N-Sc | |
| Snap-Idc5fast | |
| G4ld-Card | |
| Snap-Scm-Bb4 | I/O RACK, ACCESSORY TYPE:BREAKOUT BOARD, FOR USE WITH:OPTO22 SNAP PAC SYSTEMS, LEADED PROCESS COMPATIBLE:NO, PEAK REFLOW COMPATIBLE (260 C):NO, ROHS C |
| Snap-Odc5-I | 4 Channel Isolated DC Output Module SNAP-0DC5-i |
| Snap-TeX-Fb16-L | |
| Led-Spcv-Lv100w | |
| G4-Lax | |
| Jumpers | |
| Snap-Aova-8 | |
| G4fusesockets | |
| Snap-Idc-Hdb-Fm | |
| G4-Odc5r | |
| Mp120d2-00 | |
| G4-Pb24 | |
| Snappacr16 | |
| Factoryfloor | |
| Pbma | |
| 001792j | |
| Pacdisplaypro | |
| Pb24wo | |
| G4rpanel | |
| Snap-B3000 | |
| 120d25 | |
| Snap-Aitm-2 | |
| Snap-M16 | |
| Iac5 | |
| Icpc846 | |

| | |
|--------------------------------------|------------------------------------------|
| 001788m | |
| Ic80n | |
| Snap-Psdin | |
| 001792k | |
| 001836jw | |
| Snap-It-Pm-R1ads | SNAP IT PANEL MOUNT PAC-R1 ADS BOX |
| Snapodc5sr | |
| Bds4opt23a01 | |
| Snap-Idc-32dn | |
| Snap_B3000 | SNAP Ethernet Brain Module |
| N-Tron308tx-N | |
| Snap-Idc5-Sw | |
| Opto22idc5 | |
| Snap-Odc5r5 | |
| Ac31b | |
| G4ps245a | Opto 22 Mystic Brick Power Supply Module |
| 001792h | |
| Ga0dc5 | |
| Snap-Aictd | |
| Optoemu-Act-0750-250 | |
| G4-Odc15 | |
| G4-Oac5 | |
| G4-Ps24xa | |
| 240d45 | |
| G4a8rcover | |
| Snap-Iac-16 | |
| G4-D16p | |
| Odc5a | Output Module |
| Ich11a550 | |
| N-Tron900-Pm | |
| Snap-Lcsx-Plus | |
| Snap-Airtd | |
| Ca4 | |
| M4rtuf1m | |
| G4-D32rs | |

[G4-Rax](#)

[Od-4](#)

[G4-Ad8](#)

[Snap-Ps5u](#)

[006352a](#)