

Opto 22

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Opto 22 Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Opto 22 T¼rkiye Distrib¼t¼r¼ veya temsilcisi deęildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.





rn	Aıklama
Opto 22, G4ODC5R , 139-2292000	
Opto 22, G4OAC5A5, 139N-2085938	
MP240D4	ELECTRONIC LOAD RELAY 24-280 VAC 4 A
000777555-81	Manufacturer: OPTO 22 # Manufacturer part number: SNAP-AIMA # Order number: 3405273
AIMA-4	OPTO 22# Manufacturer Part Number:SNAP-AIMA-4# Order number:4472123
MP240D4-17	Solid State Role
G4 ODC24	OUTPUT 60VDC 3A 24V LOGIC
IDC5B I/O MODULE	
007376B	
DC60S524	
G4-Pb4	
Snap-Rackdinb-Each	
Snap-Aima-32-Fm	SNAP 32-CH -20MA TO +20MA ANALOG CURRENT INPUT MODULE-FM APPROVED
G4-Odc5a	
Odc-24	
G4 Idc5	Input Module
Snap-B4m	B-Series 4 Module Rack
Snap-Aod-29	
G4d16r	Opto 22 Mystic Brick Controller Kit
G4a8l-Cover	
Oac-5q	
Iac5p	
Snap-Odc5r5fm	
G4-Ad4	
G4lc32f1m	
Snap-D8mc-P	
Iac-5a	
Snap-Idc-32-Fm	

Snap-B3000ha	
G4-Batt32	
Ad-18t	
Oac24a	
G4ls	
G4oac24ama	
Snap-Pac-Rck12-Fm	
Snap-Psudin	
Strap8	
240d45-18	
Snap-Rackdin	
Ad-4	
Pb32h	
Odc-5	
Groov-Svr-Win-Snap	GROOV SERVER FOR WINDOWS FOR SNAP PAC ONLY
Pb16mds	
Snap-It-Wm4	
Snap-Aoa-23	
N-Tron700-Pm	
005157d	
G4-Odc24-1.5a	
Snap-Odc5rfm	
Fuseg4	
Pb-16p1	
Ca2	
Snap-Idc5q	
Snap-Aitm-C	
001818b	
Optoemu-Snr-Dr1	ENERGY MONITORING UNIT WITH DEMAND RESPONSE CAPABI
Ex-2	
001836cw	
Brickstrap	
Fuse01g4	
G4-Mod-Sockets	
005246c	
Pb-32p2	

R0430	
001828d	
N-Tron7506gx2	
Groov-Ar1	GROOV BOX
380d25	
B1	
Ac38a	
Snap-Pac-R2-W	PROGRAMMABLE CONTROLLER, WIRELESS, ACCESSORY TYPE:PROGRAMMABLE AUTOMATION COMMUNICATION, FOR USE WITH:SNAP PAC SYSTEM, SIGNAL INPUT TYPE:ETHERNET, RS-
Iac-5aq	
Ad2t	
Pb-16s	
4860000-7617	CLASSIC CONTROLLER
240a45	
Snap-It-Pm-Ads	CONTROLLERS, PEAK REFLOW COMPATIBLE (260 C):NO, LEADED PROCESS COMPATIBLE:NO, ROHS COMPLIANT: NO
Ad17t	
Snap-Aiv-32	I/O MODULE, VOLTAGE RATING:5V, CURRENT RATING:150MA, LENGTH:83.13MM, EXTERNAL WIDTH:82.55MM, EXTERNAL DEPTH:18.29MM, FOR USE WITH:OPTO22 SNAP PAC SYST
Snap-Enet-D64	
Ad14t	
Snap-Idc-16	
005157c	
G4d16l-Cover	
240d50	
M4sarc	
G4brickbase	
Til114	
Da-6	
G4iac24	I/O Module
Snap-Aitm-8-Fm	
Snap-Idc5ma	
Snap-Hd-Acf6	
Ioprojectpro	IOPROJECT PROFESSIONAL SOFTWARE SUITE, FOR USE WITH:OPTO22 SNAP PAC LEGACY SYSTEM CONTROLLERS AND I/O UNITS, KIT CONTENTS:IOPROJECT PROFESSIONAL COMPL

Iac15a	
G41dc5-Input10-32vdc	
Ac40b	
Snap-Odc5snkfm	
G4-Pb16hc	
G4ad24	
Dc60s-3	
Snappacr2	
001788b	
Snap-Aov-25	Dual Channel Output Module SNAP-A0V-25
G4 Oac5afm	
139	
Snap-Idc5-Ht	
Snap-Brs	
Dc60s-5	
Z240d10-17	
Oac15c	
Ad-3	
Ac-8a	
G4d16r-Brain-Board	
Fuse05	
Oac5	OAC5 AC Output Relay Module OAC5 OPTO 22
Odc5p	
G4abrick	
G4-Ad16	
G4lc325x	CONTROLLER 200 MYSTIC
Pci-Ac5	
Snap-Scm-Profi	
Ssr-Hs	
Snap-TeX-Fb16-H	
Snap-Fieldconb	
Optoterminal-G75	CONTROLLERS, DISPLAY, METER DISPLAY TYPE:TFT-LCD COLOUR, DISPLAY RESOLUTION:640 X 480 PIXELS, SUPPLY VOLTAGE RANGE:10VDC TO 26VDC, OPERATING TEMPERATU
Snap-Hd-Cbf6	
Od6	
Optoemu-Cts-2000-600	

G4-Ad18	
Snap-Pac-S1-W	PROGRAMMABLE CONTROLLER, WIRELESS, NO. OF DIGITAL INPUTS:-, NO. OF DIGITAL OUTPUTS:-, ACCESSORY TYPE:PROGRAMMABLE AUTOMATION COMMUNICATION, FOR USE W1
120d3	
Snap-Rokdin	
Snap-Pac-Eb1-W	I/O PROCESSOR WIRELESS, CURRENT RATING:750MA, LENGTH:93.98MM, EXTERNAL WIDTH:83.82MM, EXTERNAL DEPTH:46.36MM, FOR USE WITH:OPTO22 SNAP PAC SYSTEMS, AC
Cac15	
G4odc5afm	
Ad-10t	
Od2	
Circuitcard	
Snap-Odc5src	
8	
G4-Oac5a5	
Snap-Scm-W2	
Fuseg4b	
G4-Swin	
007308d	
Oac-5	
Snap-Pac-S2	PROGRAMMABLE CONTROLLER, WIRELESS, ACCESSORY TYPE:PROGRAMMABLE AUTOMATION COMMUNICATION, FOR USE WITH:SNAP PAC SYSTEM, LEADED PROCESS COMPATIBLE:NO, P
Icmoc3012	
B3000	
Snap-Aitm	
N-Tron702m12-Pk	
N-Tron516tx-A	
120a10	
Ca10	
G4-Lc32sxf1m	
001830f	
005158g1	
Snap-Fuse10ab	
Da8 Power Module	
Optotermcable-G70	
Snap-Odc-32-Src	

Snap-D4mc	
Ad15t	
Ad-16t	
Snap-Odc5r	4-Ch Reed Relay Digital Output Module SNAP-0DC5R
Snap-Oac5ma	
Oac5-10pack	10PK AC Output Relay Module OAC5 OPTO 22
G4rcommkit	
G4oac15a	
Iac-5	
G4-Idc5k	
Snap-Tex-32	
Snap-B4	
001772a	
Snap-Iac-K-16	
M4-Ethernet	
Snap-Enet-S64	
N-Tron517fx-A-St-S	INDUSRTIAL WIRELESS RADIO, NETWORK SPEEDS:10 / 100 GIGABIT, NO. OF PORTS:1, SUPPLY VOLTAGE MAX:49VDC, SUPPLY VOLTAGE MIN:20VDC
G4-D16r	
G4-Ad11	
Pb24-Hq	
Model : Mp 240 D4	
Pb-16md	
4187	
Snap-Aod-29-Hfi	
Snap-Aoa-23-Isrc-Fm	
240di45	
G4strip	
G4-Aitm	
N-Tron716tx	INDUSRTIAL ETHERNET SWITCH, NO. OF PORTS:8, NETWORK SPEEDS:10 / 100 GIGABIT, NO. OF PORTS 10/100TX:6, NO. OF PORTS 100FX:2, SUPPLY VOLTAGE MAX:30VDC
Hh6	
575di45-12	
G4idc5d	
006015b	

480d15-12	
100023	
Odc24	
G4-Idc-5ma	
Strap2q	
E2	
G4-Lc32isa	
Snap-Airtd-1k	
22lc4a	
Snap-B12-Mc	
G4-Idc5g	
B5	
Oac5ah	
Pb4h-6771	
G4-Iac24	
G4p2245a	
B6	
Snap-B12m	SNAP B-Series 12-module Rack
32n107e	
Fuse02b	
N-Tronntsfp-Tx	
Od8	
005081aw	
001234b	
Snap-Aoa-23-Isrc	
Snap-Pac-Eb1-Fm	
Snap-Aima-Isrc	
G4lc32sx	Opto 22 Mystic 200SX Processor Module 200SX
Snap-Hd-G4f6	
Snap-Aoa-23-Ih	
Pactermssd	PAC TERMINAL SECURE STRATEGY DISTRIBUTION (SSD) (DOWNLOAD)
Pb16l	
185175a01	PC BOARD G4HDM
Ic545j	
B3000-B-Gt	
Strap4q	

001830a	
Snap-It-Rm-D64	CONTROLLERS, PEAK REFLOW COMPATIBLE (260 C):NO, LEADED PROCESS COMPATIBLE:NO, ROHS COMPLIANT: NO
001774b	
57456	
G4-Idc24	
Snap-Rck-B2m	
P240d4-17	
Idc-5d	
Snap-TeX-Drc10	
Snap-Idc-32d	
Hh8	
G4aiva	CIRCUIT BOARD ANALOG I/O
Snap-TeX-Cbe6	
Snap-Brs-Ha	
Ac-24at	
P120d2	
G4-Odc5r5	
G4-Ps245a	
G4b200	
Ac-42	
Pb-16t	
001848g	
200sx	
B2	
G4-Ad7	
Pb-Sa	
G4-Ior	
Ac36	
Snap-Rpsw	
001842d	
Snap-Aiv-Hdb-Fm	
Pbmoa	
Snap-M64	
Snap-Idc5fm	
Ac422	

8883	
G4-Oac5a	
84113310	
Mp380d4	
Da-3	
Snap-Up1-M64	PROGRAMMABLE LOGIC CONTROLLER, METER DISPLAY TYPE:LED, PEAK REFLOW COMPATIBLE (260 C):NO, LEADED PROCESS COMPATIBLE:NO, FEATURES:MULTIFUNCTION 64-POIN
Oac-27	
G4-A8p	
Snap-Odc5snk	
Snap-Hd-Bf6	
Ac-34	
Snap-Pac-Eb1	
001836fwo	
M4lcsx	
G4-Odc5	
G4-Oac24a	
308tx-N	
Snap-Aima-Ih	
G4-Ad12	
G4rax	Opto 22 Mystic Brick Controller Kit
Snap-TeX-Mr10-16c	
Oac5	
Ac-37	
Smiac5	
Icmoc3040	
G4oac5ama	
G4-Oac5ma	
Snap-Aiv-72h	
G4-Odc24a	
G4ps24xb	
Optointmb	
G4idc5	
Optoterminal-G70	CONTROLLER OPERATOR INTERFACE, DISPLAY RESOLUTION:320X240, OPERATING TEMPERATURE RANGE:-10C TO +60C, PEAK REFLOW COMPATIBLE (260 C):NO, FOR USE WITH:S
Odc-5a	

G4lc32sxser	
M4ps48d	
Snap-Fuse1ac	
Snap	
G4-Idc5b	
G4odc5r	
G4lc32arc	Opto 22 Mystic Brick 485 Interface Module
Snap-Airt-d-10	
Idc-5q	
Snap-Rck-M2b	
Snap-Oac5-Ifm	
Icilq55	
G4-Pem-Nuts	
6017c	
G4odc5r5fm	
G4-Iac5a	
Ad-6t	
Snap-Aivrms-I-Fm	
Aml21fba2aa	
G4-Ad25	
480d25-12	
Snap-Hd-Bf1	
G4lc32ram	
Pb-16a	
Snap-Scm-232	
G4lc4c	
Snap-Aima-Hdb-Fm	
Snap-Air400k-8	
G4 0ac5	Output Module
001792d	
Pb16he	
M4ps125d2	
889	
Dc60p	
001830j	

G4da10	
Snap-Odc5-Ifm	
Snap-Lcm-4	
240d3	
Snap-Aivrms-I	
Ic4n27	
Da4t0	
Ad-5t	
Snap-Omr6-A	
001836kwo	
Snap-Modtool	
Groov-Ar1-Snap	GROOV BOX FOR SNAP PAC ONLY
G4pb32dec	32-channel I/O Module Rack for DEC Computers 5292
G4-Da4	
G4hdm	
Pb-4r	
G4da6	
Ps115-1.5a	
G4strapb	
Odc-24a	
Odc22	
N-Tron306fx2-N-St	
Mp240d2	
G4-Lc32isaser	
Snap-Pac-S2-W	PROGRAMMABLE CONTROLLER, WIRELESS, NO. OF DIGITAL INPUTS:-, NO. OF DIGITAL OUTPUTS:-, ACCESSORY TYPE:PROGRAMMABLE AUTOMATION COMMUNICATION, FOR USE WI
N-Tron702m12-W	WIRELESS RADIO WITH 3 MIMO ANTENNAS
Pb-16h	
Oac24h	
001784a	
Snap-Pac-Rck8	
Snapaima4	
G4iac15a	
Snap-Iac-A-16	
Safetycover	
Mp240d4	

575d4521	
Snap-It-Emu1	OPTO 22 ENERGY MONITORING UNIT
Lcm4proc	PC BOARD
Ictd	
Snap-Idc5g	
Mp240d4-17	
Optoemu-Cts-0750-150	
240d107	
Ac-8	
Oac-5adc	
Pb-16hc	
1662	
Pb-4h	
Snap-Rackdinb	
M4-Ps120a	
240d10-17	
G4-Lc32mb	
Pb32p2w	
Snap-Aiv-4	
Snap-Pac-Rck4	
Snap-B8m	
007308e	
Icmoc2a4010	
Snap-Pid-V	
Da-4	
Term1	
Pb4md	
G4fuse4a	
Fuse125	
380d45	
Snap-Airate	
000201uwo	
G4-Idc5d	
Snap-Pac-Eb2-Fm	
Odc-15	
001848d	

G4-Ad3	
Sb1-Rs485	
N-Tron304tx-N	
Dc200p	
Z240d10	
G4-D16l	
G4b2	
G4oac5a	
5300-0003	
Ich11av2	
575d30-Hs	
Groov-At1	GROOV BOX
G4 Iac5	Input 120 VAC 5Volt Logic 591
Snapscm232	
Ad-13t	
Ad-7	
M4-Rtu	MODULAR CONTROLLER, FOR USE WITH:FACTORYFLOOR SOFTWARE, LEADED PROCESS COMPATIBLE:NO, PEAK REFLOW COMPATIBLE (260 C):NO, ROHS COMPLIANT: NO
Snap-Iac5fm	
Oac5a	Opto 22 OAC5A Output Relay Module
Snap-B3000-Brain	
Snap-Aima-I	
Snap-D12mc	
Groov-At1-Snap	GROOV BOX FOR SNAP PAC ONLY
G4ad26	
G4-Iol	
001828h	
G4 Odc5	ODC5 Output Module
Ac24t	
Snap-Aoa-3	
001838d	
Pb4a	
G4-Oac-5afm	
G4 Oac5	Opto 120V Fuse 890
Da7t	

Snap-Pac-R2	
Strap2	
Snap-Fuse2ab	
Optoemu-Cts-1250-400	
Idc5f	
Icmct273	
Snap-Pdprs64	
G4-Idc5g	
Snap-Omr6-C	
G4-Pb32r	
Iac-5g	
001784b	
Pb16ma	I/O BOARD
Optoterminal-G20	
Idc-24	
G4dbrick	
Odc5r	ODCR5 Dry Contact Output
P240d4	
Snap-Rck-M2pb	
Snap-Ailc-2	
Lc2dc	
M4senet-100	COMPUTERS, NETWORK INTERFACE CARDS, LEADED PROCESS COMPATIBLE:NO, PEAK REFLOW COMPATIBLE (260 C):NO, ROHS COMPLIANT: NO
G4-Ra	
G4d32eb2	ETHERNET I/O MODULE, 32 CH, LENGTH:266.7MM, EXTERNAL WIDTH:177.8MM, EXTERNAL DEPTH:100.3MM, FOR USE WITH:G4D32RS MISTIC DIGITAL RACK, ACCESSORY TYPE:E
G4hdmr	
Snap-Idc5d	4 Channel DC Input Module IDC5D
Fuse05b	
Snap-Scm-Ssi	
Snapodc5r Snap-Odc5r	
Snap-Pac-R1-W	PROGRAMMABLE CONTROLLER, WIRELESS, ACCESSORY TYPE:PROGRAMMABLE AUTOMATION COMMUNICATION, FOR USE WITH:SNAP PAC SYSTEM, SIGNAL INPUT TYPE:ETHERNET, RS-
Oac-15	
005158f	
G4-Ram4m	

Opto22odc5	
120d10	
001788k	
G4-Odc5fm	
Snap-Idc-32n	
G4-Pb8h	
Iac5e/24	
G4odc5	
Snap-Paclc	LEARNING CENTER, KIT CONTENTS:SNAP PAC LEARNING CENTER GUIDE, PAC PROJECT 8.0 SOFTWARE WITH PAC PROJECT DOCUMENT, FOR USE WITH:ETHERNET-BASED SYSTEMS
Snap-S2din	
Snap-Up1-D64	CONTROLLERS, FOR USE WITH:SNAP ULTIMATE I/O ETHERNET BRAIN 64 POINT DIGITAL, LEADED PROCESS COMPATIBLE:NO, PEAK REFLOW COMPATIBLE (260 C):NO ROHS COMP
Snap-A0a-23-Isrc	
Pb4moa	
Snap-Aov-27	
Snap-It-Rm-Ads	MONITORING UNIT RACK-MOUNTED
Pb-32hq	
G4-Da5	
Idc-5b	
G4lc4a	
Opto-22-B6	
Snap-Odc5srcfm	
Ad1	
N-Tron7026tx	ETHERNET SWITCH, MANAGED, 24 COPPER PORTS, 2 MINI-GBIC PORTS, RACKMOUNT
Snap-Pac-R2-Fm	SNAP PAC R-SERIES PROGRAMMABLE AUTOMATION CONTROLLER ON-THE-RACK-FM APPROVED
Ac-6	
Optodriver	
Odc-5q	
G4-Ad5	
G4 Idc5d	Input Module
Snap-Odc-Hdb-Fm	
Snap-Aiv-I	
G4idc5-Swnc	
Dc60s3	

240d10	
Plc-Manual-Cd	
Snap-Up1-Ads	
Snap-Iac5ma	
E-31a	
G4pb16l	
Snap-Aiarms	
Snap-D12mc-P	
Fuse01g4b	
Snap-Pac-Sb2	
Odc15a	
G4-Odc-5ma	
Oac-15a	
Snap-TeX-Mr10-16	
Snappacr1	
M4-Sser	
G4-Rs	
Snap-D12m	
N-Tron508fx2-A-St-S	ETHERNET SWITCH, MANAGED, 6 COPPER, 2 FIBER, MULTIMODE, ST, PLUG-AND-PLAY, STD. TEMPERATURE
Lcm4-Serial	
Snap-Aiv2-I	
Ac40c	
Iac5	AC Input Module IAC5 OPTO 22
Oac5a-11	
G4-Ad13	
Snap-Scm-St2	
Snap-Aov-5	
Snap-Aivrms	
Fuse01g4	
Snap-TeX-Cbs6	
141	
25904	
Snap-Aiv	2 Channel Analog Input Module AIV
Snap-Odc-32-Src-Fm	
Snap-D6mc	

416105	
Snap-Pac-Rck8-Fm	
Snap-Odc5asnk	
Snap-Aiarms-I	
G4-Hdal	
32n106e	
Til111	
Snap-Pac-Eb2-W	I/O PROCESSOR WIRELESS, CURRENT RATING:750MA, LENGTH:93.98MM, EXTERNAL WIDTH:83.82MM, EXTERNAL DEPTH:46.36MM, FOR USE WITH:OPTO22 SNAP PAC SYSTEMS, AC
G4-Hdar	
G4-D16I-Base	
Idc-15	
Oac-5a5	
Snap-Aictd-4	
Snap-Io4ab-Lc	LEARNING CENTER, KIT CONTENTS:LEARNING CENTRE USERS GUIDE, ETHERNET/IP PROTOCOL GUIDE, ETHERNET/IP CONFIGURATOR, FOR USE WITH:OPTO22 SNAP INPUT / OUTP
Optoemu-Pt600	
007308f	
G4ac5	
Snap-D4mc-P	
M4ps240a	
Optoemu-Act-0750-100	
Snap-Aiv-8	
G4-Lc32arc	
G4-Idc15	
G4-Pb32h	
Ac-30a	
G4-Strap	
Snap-Odc-32-Snk	
24oa45	
Snap-Enet-Rtc	
N-Tron900b-N	
Snap-Ailc	
G4ram1m	
Snap-D8mc	

G40ac24a	
G4ra-Card	
Mp-120d2	
Odc5	ODC5 Output Module
Ca8	
G4-A8I-Base	
P240d2	
120d45	
Snap-Odc5a-Ifm	
Optoemu-Cts-0750-70	
22-Iac5	
Snap-Aima-4	
Snap-Ps5-24dc	24 VDC Logic Power Supply OPTO 22
Snap-TeX-Cbo6	
Ad8	
8882	
Masarcf	
G4-Ad22	
Snap-Aimv2-4	
G4-Rd	
Oac-5p	
Da-8	
Dc60mp	
551ps5014	
Dc 60 Mp	
Optointab	
Snap-Scm-Can2b	
240di10	
N-Tron716fx2-St	INDUSRTIAL ETHERNET SWITCH, NO. OF PORTS:8, NETWORK SPEEDS:10 / 100 GIGABIT, NO. OF PORTS 10/100TX:8, SUPPLY VOLTAGE MAX:30VDC, SUPPLY VOLTAGE MIN:10V
Idc-5bq	
Fuse01b	
Idc5q	
Pb-8ah	
Hh4	
G4a8r	Opto 22 Mystic Brick Controller Kit

M4-Enclosure	
005247b	
Groov-Svr-Win	GROOV SERVER FOR WINDOWS
B200	
Snapidc5a	
G4pb32jy-In	32-channel I/O Module Rack
Oac-24	
Idc5	Input Module
G4-Odc24	
P120d4	
Snap-Aictd-8	
G4-A8l	
Model: Dc 200 Mp	
Snap-Scm-485-422	
Ic817cd	
G4-A8r	
Snap-Oac5-I	
Snap-Aipm-3v	
Snap-Pac-Sb1	
Idc5p	
G4-Pb16h	
G4ad19	
Cjc	
575d15-12	
Pci-Ac51	
240a25	
240d30-Hs	
Z120d10	
Snap-Pac-R1	PROGRAMMABLE CONTROLLER, FOR USE WITH:SNAP PAC SYSTEM, ACCESSORY TYPE:PROGRAMMABLE AUTOMATION COMMUNICATION, LEADED PROCESS COMPATIBLE:NO, PEAK REFLOW
Ac-7a	
G4pb16j	
G4pb24	
G4-Lc32int	COMM BOARD
Pb32p2wo	

Da-3t	
B3000-B	
Fuse.125b	
G4lc32isalt	
Snap-Ps5	
590-0513-00	
Snap-Aiv-32-Fm	ANALOG INPUT MODULE, 5VDC, 150MA, FOR USE WITH:OPTO22 SNAP PAC SYSTEMS, VOLTAGE RATING:5VDC, CURRENT RATING:150MA, LENGTH:83.13MM, EXTERNAL WIDTH:82.5
G70	
Snap-Pac-Rok	SNAP-PAC REDUNDANCY OPTION KIT, 32VDC, VOLTAGE RATING:32VDC, LENGTH:93.98MM, EXTERNAL WIDTH:83.82MM, EXTERNAL DEPTH:46.36MM, ACCESSORY TYPE:SNAP-PAC R
Snap-It-Rm-Uads	CONTROLLERS, PEAK REFLOW COMPATIBLE (260 C):NO, LEADED PROCESS COMPATIBLE:NO, ROHS COMPLIANT: NO
G4-Exl	
Groov-Snap-Upg	SNAP UPGRADE TO
001848e	
Da-4t	
Pcie-Ac51	
Iac24a	
Opto 22 Odc5q Quad Pak 4-Channel Dc Output 5-60 Vdc, 5 Vdc Logic	
70odc5	
G4-Ad10	
G4ad6hs	
240di25	
240a10	
Ad-6hs	
240d25	
Ich11c1	
Odc5q	
G40dc24	I/O Module
Lc32sxf	
Ic4n35ssm	
G4oac5fm	
Ac42at	
Snap-Fuse1ab	

Pb16	
G4-Base	
716tx	ETHERNET SWITCH
Pbsc	
Ac40a	COMPUTERS, INTERFACE CARDS, PEAK REFLOW COMPATIBLE (260 C):NO, LEADED PROCESS COMPATIBLE:NO, FEATURES:FIBER OPTIC REPEATER, 120VAC, ROHS COMPLIANT: NO
001717a	
Snap-Aima2-I	
Snap-It-Pm12	SNAP PAC SYSTEM 12-MODULE ENCLOSURE, NEMA 3R, META
Snap-B3000-Modbus	SNAP Modbus I/O unit B3000 BRAIN
Snap-Odc5a-I	
Idc5a	
B11	
Snap-Idc5-Fast	
Snap-Scm-Mch16	
Snap-It-Rm-Pac-R1	SNAP IT RM RACK WITH A PAC-R1
G4da8	
Pb16k	
G4ad20	
Snap-Pac-Rck12	
G4d16ls-Cover	
Lc2	
G4odc24	
Optoemu-Snr-3v	CURRENT SENSOR, 8 CHANNELS, 0.2%, ACCURACY %:0.2%, ACCURACY:0.2 %, EXTERNAL DEPTH:11.4CM, EXTERNAL HEIGHT:34.3CM, EXTERNAL WIDTH:15.2CM, INPUT VOLTAGE
005078a	
Ad-10t2	
Snap-Aitm-4i	
Snap-Pac-R1-Fm	SNAP PAC R-SERIES PROGRAMMABLE AUTOMATION CONTROLLER-FM APPROVED
Ic2502	
Snap-B16mc	
G4-Ad17	
Snap-Airate-Hfi	
G4d16r-Cover	
Da-5	

G4-Lc4	
Snap-Aiv-72	
Snap-B6	
005746b	
240d2s	
Snap-It-Rm16	SNAP PAC SYSTEM 16-MODULE ENCLOSURE, METAL, RACK-M
G4fuseclip	
Pci-Ac28	
Softpac	
G4odcs	
006876b	
Snap-Lcsx	
Snap-B16mc-P	
Oac5a/120	
Dc60s5	
001842e	
Odcq-5	
Ad7 Non Rohs Analog Input Module	
005326b	
22	
Oac-5a	
001842f	
Smidc5	
Snap-Label-4b	
Pbmd	
001744b	
N-Tron904fx-Sc	SLIDE IN MODULE FOR 900 SERIES CHASSIS, 4 FIBER, MULTIMODE, SC CONNECTORS
G4b100	
001788l	
G4mservo	PC SERVO BOARD ASSEMBLY
Ac-28	
B3000-B-Omux	
G4lc4b	
G4-Idc5	
N-Tron708fx2-St	INDUSRTIAL ETHERNET SWITCH, NO. OF PORTS:8, NETWORK SPEEDS:10 / 100 GIGABIT, NO. OF PORTS 10/100TX:8, SUPPLY VOLTAGE MAX:30VDC, SUPPLY VOLTAGE MIN:10V

Snap-It-Pm-Ads-Plus	CONTROLLERS, PEAK REFLOW COMPATIBLE (260 C):NO, LEADED PROCESS COMPATIBLE:NO, ROHS COMPLIANT: NO
Snapidc32	
Pb-4ah	
Snapphorp	
Optotermcable	
240d25-17	
Snap-Modlatchb	
Snap-Iac5a	
Snap-D4m	
Smapaoa3	
N-Tron702-W	INDUSRTIAL ETHERNET SWITCH, NO. OF PORTS:8, NETWORK SPEEDS:10 / 100 GIGABIT, NO. OF PORTS 10/100TX:6, NO. OF PORTS 100FX:2, SUPPLY VOLTAGE MAX:30VDC
Pb16j	
001784d	
5196b	
Snap-Aima-32	I/O MODULE, VOLTAGE RATING:5V, CURRENT RATING:150MA, LENGTH:83.13MM, EXTERNAL WIDTH:82.55MM, EXTERNAL DEPTH:18.29MM, FOR USE WITH:OPTO22 SNAP PAC SYST
Pb-24	
Snap-Strap	
Pb32hqwo	
Ocb-003	
Fuse02	
Ac-5	
1848	
480d45-12	
Ad11t	
Iac24/120	
Pb16h	
Snap-Fuse7.5ab	
Iac-15	
Snap-Idc5-Fast-A	
Term-2	
N-Tron702-W-Pm	
Optoemu-Snr-Dr2	ENERGY MONITORING UNIT WITH DEMAND RESPONSE CAPABI
B4pamux	

N-Tron709fx-St	ETHERNET SWITCH, MANAGED, 8 COPPER 1 FIBRE, MULTIMODE, ST CONNECTOR
Snap-Pac-Eb2	
Iac15n	
Snap-Pac-R1-B	SNAP PAC R-SERIES PROGRAMMABLE AUTOMATION CONTROLL
G4-Pb32dec	
Ac30b	
Ieee488	
Output-Switch	
Optoopcserver	
G4d32eb2-Upg	
G4-Reg	
M4dualarc	
E1	
240d45sp	
Hh10	
Snap-Ps24	
Snapodc32s	
Ac31a	
Snap-Pac-Rck16-Fm	
Snap-Pac-Rck4-Fm	
Snap-TeX-Mr10-4	
G4-Odc24afc	
120d5	
Snap-TeX-Rckcap	
007214d	
Ac38b	
Optotermcable-G75	
Input-Switch	
Snap-Aima	Analog Current Input Module
Snapaov5	
Snap-Odc-Hdb	
G4da9	
M4rtux	
Snap-Wirestrapb	
Pb-24q	

Snap-B3000-Enet	
Snap-Idc5k	
N-Tron712fx4-St	ETHERNET SWITCH, MANAGED, 12 PORT 8 COPPER, 4 FIBER ST CONN
G4-Pb8	
Ac422-001734a	
001828g	
Snap-Aitm-I	
Snap-Mr10	
001662a	
Pb16s1	
Snap-Pac-S1-Fm	SNAP PAC REDUNDANCY OPTION KIT, NO. OF DIGITAL INPUTS:-, NO. OF DIGITAL OUTPUTS:-, ACCESSORY TYPE:I/O MODULE, EXTERNAL DEPTH:44.4MM, EXTERNAL WIDTH:10
Snap-Odc-32-Snk-Fm	
Snap-Pac-Rck16	
001788j	
Ac47	
Snapenetd6 Snap-Enet-D64	
Snap-Idc5	Digital Input Module
N-Tron708tx	
G4ps245b	
Snappacrc8	
G4-0ac5a	
Snap-Aitm2-I	
Zxr0pt022b1	
Lcm4	
240d45-17	
Snap-Modfusehldrb	
Snap0dc32src	
Snap-Aipm-3	
001836cwo	
Anapaitm	
Pacprojectpro	SOFTWARE, KIT CONTENTS:PAC PROJECT PROFESSIONAL COMPLETE SOFTWARE SUITE, DOCUMENTATION ON CD, PLUS PRINTED DOCUMENTATION, ACCESSORY TYPE:PROJECT PROFE
Snap-Aiarms-I-Fm	
Snap-Fuse4ab	

Odc-5r	
Zxropto22b1	
Snap-B16m	
G4-Lc32sx	
G4-Pb4r	
Snap-B8mc-P	
Ad12t	
N-Tron306fx2-N-Sc	
Snap-Idc5fast	
G4ld-Card	
Snap-Scm-Bb4	I/O RACK, ACCESSORY TYPE:BREAKOUT BOARD, FOR USE WITH:OPTO22 SNAP PAC SYSTEMS, LEADED PROCESS COMPATIBLE:NO, PEAK REFLOW COMPATIBLE (260 C):NO, ROHS C
Snap-Odc5-I	4 Channel Isolated DC Output Module SNAP-0DC5-i
Snap-Tex-Fb16-L	
Led-Spcv-Lv100w	
G4-Lax	
Jumpers	
Snap-Aova-8	
G4fusesockets	
Snap-Idc-Hdb-Fm	
G4-Odc5r	
Mp120d2-00	
G4-Pb24	
Snappacr16	
Factoryfloor	
Pbma	
001792j	
Pacdisplaypro	
Pb24wo	
G4rpanel	
Snap-B3000	
120d25	
Snap-Aitm-2	
Snap-M16	
Iac5	
Icpc846	

001788m	
Ic80n	
Snap-Psdin	
001792k	
001836jw	
Snap-It-Pm-R1ads	SNAP IT PANEL MOUNT PAC-R1 ADS BOX
Snapodc5sr	
Bds4opt23a01	
Snap-Idc-32dn	
Snap_B3000	SNAP Ethernet Brain Module
N-Tron308tx-N	
Snap-Idc5-Sw	
Opto22idc5	
Snap-Odc5r5	
Ac31b	
G4ps245a	Opto 22 Mystic Brick Power Supply Module
001792h	
Ga0dc5	
Snap-Aictd	
Optoemu-Act-0750-250	
G4-Odc15	
G4-Oac5	
G4-Ps24xa	
240d45	
G4a8rcover	
Snap-Iac-16	
G4-D16p	
Odc5a	Output Module
Ich11a550	
N-Tron900-Pm	
Snap-Lcsx-Plus	
Snap-Airtd	
Ca4	
M4rtuf1m	
G4-D32rs	

[G4-Rax](#)

[Od-4](#)

[G4-Ad8](#)

[Snap-Ps5u](#)

[006352a](#)