

Optris

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye ii kapı teslim fiyat ve teslim s¼resi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Optris** Markası, tedarik s¼resi iin l¼tfen bizimle iletiŐime geiniz.

Firmamız Optris T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	Aıklama
Accsmiac	IR App Connector / USB-Kit for optris® CSmicro, CS, CSLaser, CX - USB adapter cable with micro USB connector and Adapters for USB-C and USB-A - absolutely necessary for the parameterization of CSmicro sensors - to use the free "CompactConnect" software https://www.optris.de/downloads
ACCTCERT	Works test certificate for optris® CT LT Calibration (3 reference temperatures) at ambient temperature, 110 ° C, 510 ° C
OPTCTLT15CB3	Pyrometer
ACCTCERT	Works test certificate for optris® CT LT Calibration (3 reference temperatures) at ambient temperature, 110 ° C, 510 ° C
PIF BR E2015 02 A	24VDC IP65 -30-+85C
OPTCSLT15SFCB1	optris pirometre OPTCSLT15SFCB1 G¼mr¼k tarife numarası: 90251920 MenŐe ¼lke: DE
ACCTFB	optris mounting bracket adjustable
OPTCTLT (TEMPERATURE MEASUREMENT SENSOR)	
CB15	
CB3	
CTL3MH2CF4	

CTL3MH2SF	
CTLaser 3MH1CF	
CTLT15	
CTLT15CB3	
D03CTLT10CB3	
D21CTLT15	
OPTCT3MH2CF	
OPTCTLT02	
OPTCTLT15CB3--50-600 °C/ 8-14 µm/ 15:1/180°C	
OPTCTRF2MH1SFVFC3	
OPTMSPLI	
OPTCSLT15SF	optris Pyrometer OPTCSLT15SF
CTlaser P7	
optris Pyrometer OPTCSLT15SFCB1	
OPTCTLT20CB3	optris Pyrometer OPTCTLT20CB3
OPTCTLT	
ACCTAP	optris air purge attachment for CT measuring heads
OPTCSLT15SFCB1	optris Pyrometer OPTCSLT15SFCB1
OPTCSTCLT15	
OPTCSLT15SF	
OPTCSLT15	optris Pyrometer OPTCSLT15SFCB1
OPTCTLT15FSFCB3	Model (Temperature / Spectral range / Optics): optris CTfast (LT15F): - 50-975°C / 8-14 µm / 15:1 / 120°C / 9 ms Optics: SF optics Cable length: 3 m head cable
OPTCTLT15	SN3070022 8.36V DC 250MA
630-650nm	-It will be able to measure temperature between (0-500) °C with laser sensor. -It will have the necessary outputs to print the measured temperature value on the 4 digits 7-segment display screen. The Optris CT 3M model meets the required features. You can contact the company and confirm.
OPTPI40ILTO53T090	optris Infrarot-Kamera PI400i
Optctra1mbcf2cb3	
Optcslt10cb3 Obsolete/Replacement Optcstclt15cb3 Temperature Sensor	
Ct Lt02	
Optctltt15cb3	
Acctst20	
Ctlt02	
Infct12mhff Invalid/Check Optct12mhff	

Temperature Measurement Device	
Adaptor Usb	
Optct1mh1sf	
Optct12mhff	
D27ctlt15 Robuster Miniatur-Infrarot-Sensor Lt	
Optris Ms	
T15	
Infmerdcb8	
OPTCTLT15CB3	Infrared sensor optris® CT LT15 -50-600 ° C, 15: 1, SF, 3m cable Infrared thermometer for non-metallic surfaces Metrological parameters - Temperature range: -50 ... 600 ° C (scalable via programming buttons or software) Spectral range: 8-14 µm - Optical resolution (90% energy): 15: 1 (precision glass optics) - CF auxiliary lens (optional): 0.8 mm @ 10 mm - System accuracy: ± 1% or ± 1 ° C (at ambient temperature 23 ± 5 ° C) (Whichever is greater) (For object temperatures > 0 ° C, E: 1 - Reproducibility: ± 0.5% or ± 0.5 ° C (at ambient temperature 23 ± 5 ° C) (Whichever is greater)
Optct1mh5fcb3hc	optris CTlaser 1M, 650-1800 ° C, 300: 1, SF, 3m HT cable plug version
Messkopfkabel Cb3	
1mh1	
Acctrs485b	
Acctshlt20cb3	
Cb15 Messkopfkabel - 15m	
Optct12mhcf4	
Optris Tmus00	
Optct13mh2sf	
D7actlt10hcb8h	
Optcstclt15	Infrared sensor optris® CS LT15 1m cable Compact infrared thermometer for non-metallic surfaces Metrological parameters - Temperature measuring range: -40 to 1030 ° C - Spectral range: 8 - 14µm - Optical resolution (90% energy): 15: 1 - CF auxiliary lens (optional): 0.8 mm @ 10 mm - System accuracy: ± 1.5% or ± 1.5 ° C (at ambient temperature 23 ± 5 ° C and object temperature > 0 ° C; whichever is greater) - Reproducibility: ± 0.75% or ± 0.75 ° C (at ambient temperature 23 ± 5 ° C and object temperature > 0 ° C; whichever is greater)
Optcsl2mh5fcb8	
Optmspli	
Opt-Pi160	
Acctshlt20cb3 Electronic Sensor	
D27ctlt15 Sensor	
Acctri	
D27ctlt15	
D06acctmhs	

Optcsmlt15	
Optctra1mbsfcb10	
Acctapmh	
D03 Ct Lt10	
Optcsm2wlt15	
Optctl-2mlff	
Infctra1mbcf2cb3 Invalid/Check Optctra1mbcf2cb3 Temperature Measurement Device	
Optctlt15	
Ctlt15 Robuster Miniatur-Infrarot-Sensor Lt	
Ctlt15cb3 Infrarot-Sensor	
Optctl-Lt-Sf-Cb15	
Cb15 15 M Messkopfkabelcb15	
Acctlcjias	CoolingJacket Advanced Standard for CTlaser, CSLaser, CTvideo, CSvideo - Universal protective housing for ambient temperatures up to 315 ° C - Standard version
Optctlt15cb3	
Optct-Lt15-Cb8	
Pi 400i	
Optctlt20cb15	
Accjafpctl	Front attachment for opris® CTlaser, CSLaser, CTvideo, CSvideo - Front attachment for CoolingJacket Advanced
Ct Lt02 Kabel	
Optcsmlt15k	
Ct12mlcf4	
Opt-Pi200	
Acctlcb8fc	
Pmog-22kd-0i4gsn 2051052-6lt20	
Infmerdcb8 Cooling Device	
Acctusbk	
Infrarot Handthermometer Oprisã174; Mspro	
Opt-Pi230	
Ct2mhsfcb15	
Accusbk	
Optpi16o23t900	
Ctlt20	
D27ctlt15 Pyrometer	

Optcstclt15cb3	Infrared sensor optris® CS LT15 3m cable Compact infrared thermometer for nonmetal surfaces Measurement Specifications - Temperature range: -40 ° C ... 1030 ° C (scalable via software) - Spectral range: 8 - 14 µm - Optical resolution (90% energy): 15: 1 - CF-lens (optional) 0.8 mm @ 10 mm - System accuracy: ± 1.5% or ± 1.5 ° C (at ambient temp. 23 ± 5 ° C) (Object temperature > 0 ° C, whichever is greater) - Repeatability: ± 0.75% or ± 0.75 ° C (at ambient temp. 23 ± 5 ° C) (Object temperature > 0 ° C, whichever is greater) - Temperature coefficient: ± 0.05 K / K or ± 0.05% / K (For ambient temperatures <18 ° C and > 28 ° C; whichever is greater)
Infctra1mbcf2cb3 Invalid/Check Optctra1mbcf2cb3	
Optctlt20cb8	
Opt-Pi400	
Infraapt	
Optcslltsf	
Acpi4xxcjas	
Opt-Pi640	
3ml-Sf-Cb3	
Optcsml T15	
Optctlt2mlff	
Infraapt Crtatio Protection Storage Apparatus	
Optcslt10cb3 Obsolete/Replacement Optcstclt15cb3	
D03ctlt10	
Pyrometer Ctlt15	
Pyrometer 50-975,[ctlaser Lt/Optris],4/20,36 V Dc	
Opt-Pi450	
For Ctlt15cb3 Optical Head On Pyrometer	
Pyrometer Opt-Cl-Lt15-Cb3	
Optctlt3mh2sf Sensor	
Optctlt20	
1mbsfcb10	
Acctlab	
Acctmb	
Cb3 3 M Messkopfkabel	
Acctlw	
Infctlt2mhff Invalid/Check Optctlt2mhff	
Ctlaser 3mh1 Sensor	
Acctlap	

[781708zcsr4z40015af](#)

[Infrarot Handthermometer @ Mspro](#)