

Owis

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Owis Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Owis T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunulmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
16.362.0320	KT 65-STA 6 mm (± 3 mm) travel (X, Y) and clamping device for securing the spindle - Low-reflection aluminum, black anodized - SYS 65 compatible - Fine thread spindles with 0.25 mm pitch - Load capacity max. 200 N, axial load 90 N, Reset force 6.5 - 22 N - Load torque 4 Nm - Scale division 5 μ m - Free aperture \emptyset 32 mm - M6 thread for mounting on pins - Slider with 4 M4 threads in a 34 x 34 mm grid for horizontal mounting on slide RT 65-59-R
14.014.0500	S 40-4-500 4-sided profile SYS 40, 500 mm long - suitable for use in magnetic fields - low-reflection aluminum, black anodized - for all installation positions - front thread M4 x 12 in 32 x 32 mm grid - straightness 0.40 mm/m - torsion 0.25°/m
14.014.0300	S 40-4-300 4-sided profile SYS 40, 300 mm long - suitable for use in magnetic fields - low-reflection aluminum, black anodized - for all installation positions - front thread M4 x 12 in 32 x 32 mm grid - straightness 0.40 mm/m - torsion 0.25°/m
	DF-S65-4 Swivel base for 4-sided profiles S 40-4 and S 65-4

16.094.0800	165 x 105 x 25 mm, rotatable by 90° - low-reflection aluminum, black anodized - for rotation with defined pivot point - incl. 4 cylinder screws M4 x 16 4 cylinder screws M6 x 16 4 cylinder screws M6 x 25
14.024.0065	RT 40-4-65-M4 SYS 40 rider, 65 mm wide, with M4 hexagon socket screws - without M3 threaded hole on the side - low-reflection aluminum, black anodized - for front-side fastening with maximum stability of 4-sided profiles S 40-4 - for mounting SYS 65 components (if SYS 40 system height does not have to be achieved) - incl. 4 cylinder screws M4 x 6
Ps35	
Ps30-90-Joy-3	