

Padovan Valerio

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Padovan Valerio Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Padovan Valerio T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
Tw1-8,8 Bar	
7525.11.0	Safety valve TA11AX Pressure: 11.0 bar / individual certificate Connection: G1/2"-M Material: brass Gasket: Viton Temperature: -10°+200°C Nominal width: DN 11 Approval: CE with tamper-proof ventilation Medium: air
7526.11.0	Safety valve TA15AX Pressure: 11.0 bar / individual certificate Connection: G 3/4" -M Material: brass Gasket: Viton Temperature: -10+200°C Nominal width: DN14 Approval: CE tamper-proof ventilation medium air
safety valve	Opening Pressure 10 bar Operating Ambient Temperature -20 ... +45 °C Fluid Type Air Fluid Temperature -10 ... +80 °C Connection Thread 1/4" - 3/8" - 1/2" Flow rate 250 L/min
7524.04.5	Safety valve TA6AX pressure: 4.5 bar / Individual certificate connection: G1/4"MMaterial: BrassSeal: Viton temperature: -10+200°C nominal size: DN 6mmApproval: CETamper-proof lifting device - new TA6Medium: air / nitrogen
	Safety valve TW1 Pressure: 12.0 bar / individual certificate Connection: G1/2"-M Material: brass Gasket: Viton

3160.12.0	Temperature: -20+200°C Nominal diameter: DN7 Approval: CE ISO 4126 Medium: air
see list	Safety valves are certified according to ASME SEC VIII Div.1
Safety valve TA11 Padovan	Brass Viton seal Pressure: 11+16bar Connection: G1/2-M
0086 2014/68/EU D:10.8	CW614N 11,00 BAR TA11 157322 -104200C2022 IT PATENT END
036 TUV 16. 4 bar	