

## Padovan Valerio

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Padovan Valerio** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Padovan Valerio T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*



¼r¼n	A¼ıklama
<a href="#">Tw1-8,8 Bar</a>	
<a href="#">7525.11.0</a>	Safety valve TA11AX Pressure: 11.0 bar / individual certificate Connection: G1/2"-M Material: brass Gasket: Viton Temperature: -10°+200°C Nominal width: DN 11 Approval: CE with tamper-proof ventilation Medium: air
<a href="#">7526.11.0</a>	Safety valve TA15AX Pressure: 11.0 bar / individual certificate Connection: G 3/4" -M Material: brass Gasket: Viton Temperature: -10+200°C Nominal width: DN14 Approval: CE tamper-proof ventilation medium air
<a href="#">safety valve</a>	Opening Pressure 10 bar Operating Ambient Temperature -20 ... +45 °C Fluid Type Air Fluid Temperature -10 ... +80 °C Connection Thread 1/4" - 3/8" - 1/2" Flow rate 250 L/min
<a href="#">7524.04.5</a>	Safety valve TA6AX pressure: 4.5 bar / Individual certificate connection: G1/4"MMaterial: BrassSeal: Viton temperature: -10+200°C nominal size: DN 6mmApproval: CETamper-proof lifting device - new TA6Medium: air / nitrogen
	Safety valve TW1 Pressure: 12.0 bar / individual certificate Connection: G1/2"-M Material: brass Gasket: Viton

<a href="#">3160.12.0</a>	Temperature: -20+200°C Nominal diameter: DN7 Approval: CE ISO 4126 Medium: air
<a href="#">see list</a>	Safety valves are certified according to ASME SEC VIII Div.1
<a href="#">Safety valve TA11 Padovan</a>	Brass Viton seal Pressure: 11+16bar Connection: G1/2-M
<a href="#">0086 2014/68/EU D:10.8</a>	CW614N 11,00 BAR TA11 157322 -104200C2022 IT PATENT END
<a href="#">036 TUV 16. 4 bar</a>	
<a href="#">safety valve TW1</a>	Pressure: 7.5 bar / Individual certificate Connection: G 1/4" - M (please check if correct) Material: Brass Seal: FKM Temperature: -20+200°C Nominal diameter: DN7 Approval: CE ISO 4126 Medium: Air