

## Palazzoli

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Palazzoli** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Palazzoli T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*



¼r¼n	A¼ıklama
<a href="#">P477417</a>	Art.-Nr.: 0370000000000P477417 CEE STRAIGHT PLUG 63A 3P+E 380-415V 50-60HZ 6H IP67 Frequency 50-60Hz - Protection degree IP67 Poles 3P+ // Clock Position 6 Standard plug-socket EN60309-2 Nominal Operating Voltage 400V Insulating Voltage 500V Manufacturing Material Thermoplastic Nominal current 63A // Execution MOBILE Shape Straight (t8536 6990 IT)
<a href="#">MIGNON-EX Selector Switch Teile-Nr. P202275EX</a>	
<a href="#">RED 800061</a>	24VDC
<a href="#">GREEN 800062</a>	24vdc
<a href="#">TRASPARENT 800063</a>	24VDC
<a href="#">YELLOW 800064</a>	24VDC
<a href="#">TRASPARENT 831072</a>	24VDC
	P202275EX MIGNON-EX SELECTOR SWITCH 1X16A 3D 3G Technical data Dimensions 136X62X51 mm Hole type M20

<a href="#">03700000000P202275EX</a>	Number of entries in enclosure 1 Rated current/voltage 16A 250V~10A 400V~ Frequency 50/60Hz Protection degree IP66 Poles 1P Rated operating voltage 250V~/400V~ Manufacturing material RESIN THERMOSETTING ANTISTAT DEVICE FUNCTION Selector switches Width 62 mm Rated current 16/10A Execution WALL MOUNTING Atex ATEX application zone Zona/Zone 2 and 22 Atex Dust Nominal Current - Atex Gas Nominal Current - Atex Dust Marking Ex tc IIIC T70°C Dc Atex Gas Marking Ex nR IIC T6 Gc GAS Dissipable Power - DUST Dissipable Power - Min. Amb. Temp. -20°C Max. Amb. Temp. +40°C Group & Cat. ATEX GAS II 3G Group & Cat. ATEX DUST II 3D
<a href="#">P831072</a>	RINO OVAL LIGHTING FIXTURE IN ALUMINIUM 60W 1 LAMPHOLDER E27 INLET M20 CAGE
<a href="#">272178</a>	
<a href="#">532005</a>	
<a href="#">Distribution Box Al Ip55</a>	
<a href="#">538610</a>	
<a href="#">Ip 44 - , No</a>	
<a href="#">630051</a>	
<a href="#">292102</a>	
<a href="#">476416</a>	
<a href="#">14.12.0491</a>	
<a href="#">P151881</a>	
<a href="#">511512</a>	
<a href="#">472446</a>	
<a href="#">Alternator</a>	
<a href="#">Pala531440</a>	
<a href="#">477516</a>	
<a href="#">710236</a>	
<a href="#">356338</a>	
<a href="#">Pala538210</a>	
<a href="#">202282</a>	
<a href="#">Tais Series With 5 Socket-Outlets 16a 2p + E 220v Ac</a>	
<a href="#">472518</a>	
<a href="#">630011</a>	

<a href="#">4701204</a>	
<a href="#">515512</a>	
<a href="#">464330ex</a>	
<a href="#">515111</a>	
<a href="#">511217</a>	
<a href="#">P532242ex</a>	TAIS-EX BOXES IN THERMOSETTING (GRP) FOR COMPOSITION OF SOCKET BOARDS 250X185X125 Dimensions 250X185 mm Cover height 50 mm Protection degree IP66 Manufacturing Material Thermosetting halogen free Height Box 75mm Execution WALL MOUNTING Cover Type Blind Outfit WITHOUT PLATE Insulation Class II Atex ATEX application zone Zona/Zone 2, 21 and 22 Notified body (CE) 0051 Atex Dust Marking Ex tb IIIC Db Atex Gas Marking Ex nR IIC Gc Certificate Number ATEX TÜV IT 13 ATEX 050 U GAS Dissipable Power 8 DUST Dissipable Power 22 Min. Amb. Temp. -40°C
<a href="#">471204</a>	
<a href="#">346350</a>	
<a href="#">491233.</a>	
<a href="#">Tais Series With 5 Socket-Outlets 32a 3p + E 380v Ac</a>	
<a href="#">3p+e 63a 440-460v 11h Ip67</a>	
<a href="#">14.18.0057</a>	
<a href="#">477302</a>	
<a href="#">819056</a>	
<a href="#">D001051620</a>	
<a href="#">473103</a>	
<a href="#">D1830700301</a>	
<a href="#">477303ex</a>	
<a href="#">477105</a>	
<a href="#">900463</a>	
<a href="#">472233</a>	
<a href="#">477602</a>	
<a href="#">Equipment, Including Equipment Connection By Fg7(O)m1 0,6/1 Kv Cable</a>	
<a href="#">511210</a>	

<a href="#">07.37.0012</a>
<a href="#">201151</a>
<a href="#">400247</a>
<a href="#">433052</a>
<a href="#">477002</a>
<a href="#">Krio.Lx.Sa.250 Ip657</a>
<a href="#">P/N:431 237,Poles:2p+e</a>
<a href="#">800061ex</a>
<a href="#">710336</a>
<a href="#">511212</a>
<a href="#">D192036</a>
<a href="#">D001054142</a>
<a href="#">532117ex</a>
<a href="#">472731</a>
<a href="#">472731ex</a>
<a href="#">08.31.0009</a>
<a href="#">477303</a>
<a href="#">477423ex</a>
<a href="#">476426</a>
<a href="#">18663</a>
<a href="#">831072</a>
<a href="#">P472453</a>
<a href="#">477206</a>
<a href="#">Tais Series With 5 Socket-Outlets 16a 3p + E 380v Ac</a>
<a href="#">467126ex Protection 2p+t 16a 230v 50- 60hz Ip66/Ip67 For Atex Zones 2d 3g</a>
<a href="#">671532716</a>
<a href="#">249550</a>
<a href="#">464430ex</a>
<a href="#">D7380710201</a>

<a href="#">471-304-D220-250v-16a-6k-2p+t</a>
<a href="#">347001</a>
<a href="#">471105</a>
<a href="#">515323</a>
<a href="#">19.02.0027</a>
<a href="#">511632</a>
<a href="#">477103</a>
<a href="#">463136ex</a>
<a href="#">472732</a>
<a href="#">532035ex</a>
<a href="#">630002</a>
<a href="#">01.01.0384</a>
<a href="#">Motor Starter</a>
<a href="#">101031</a>
<a href="#">08.37.0009</a>
<a href="#">511324</a>
<a href="#">740 001</a>
<a href="#">477677</a>
<a href="#">D1110403004</a>
<a href="#">800062ex</a>
<a href="#">473413</a>
<a href="#">472768</a>
<a href="#">S10r819</a>
<a href="#">720244</a>
<a href="#">151880 Socket With Stop Switch 63a</a> <a href="#">3p+e 690v</a>
<a href="#">14.02.0028</a>
<a href="#">D1110403103</a>
<a href="#">730346</a>
<a href="#">151891</a>
<a href="#">900643</a>

<a href="#">Ter Series With 3 Outlets 16 A-2p 150va</a>	
<a href="#">472333</a>	
<a href="#">710246</a>	
<a href="#">D005452335</a>	
<a href="#">471812</a>	
<a href="#">D1110402902</a>	
<a href="#">477305</a>	
<a href="#">P900473</a>	P900473 Sirens in aluminium alloy, with vibrating membrane 50-60Hz IP66 Hole type M20 Sound level at 1 mt. 107/105dB Frequency 50/60Hz Protection level IP66 Poles 2P+ Acustic Signal Type D Operational working temp -40 T 40 Nominal Operating Voltage 230V Manufacturing Material Aluminium alloy Nominal current 0.3A Zolltarif-Nr.: 8536 6990 Ursprungsland: Italien
<a href="#">272303</a>	
<a href="#">14.12.0215</a>	
<a href="#">D002053599ring</a>	
<a href="#">477203</a>	
<a href="#">D19jm00100</a>	
<a href="#">270323</a>	
<a href="#">540033</a>	
<a href="#">472844</a>	
<a href="#">472447</a>	
<a href="#">540091</a>	
<a href="#">471304d</a>	
<a href="#">P101221</a>	
<a href="#">511452</a>	
<a href="#">800062</a>	
<a href="#">400126</a>	
<a href="#">540090</a>	
<a href="#">151881 Socket With Stop Switch 125a</a>	
<a href="#">3p+e 690v</a>	
<a href="#">477416</a>	
<a href="#">472781</a>	

<a href="#">315.6346</a>
<a href="#">Moil Point For Hydro Hammer</a>
<a href="#">477456</a>
<a href="#">D11107001601</a>
<a href="#">05.41.0009</a>
<a href="#">549550</a>
<a href="#">511110</a>
<a href="#">D1110701503</a>
<a href="#">400336</a>
<a href="#">159030</a>
<a href="#">472547</a>
<a href="#">Fm90z1 450/750v</a>
<a href="#">D1120761102</a>
<a href="#">479463</a>
<a href="#">471362</a>
<a href="#">37-1304daufschnappbar 35 Mm</a>
<a href="#">472466</a>
<a href="#">540035</a>
<a href="#">579400</a>
<a href="#">471254</a>
<a href="#">473203</a>
<a href="#">515453</a>
<a href="#">700126</a>
<a href="#">473105</a>
<a href="#">272142ex</a>
<a href="#">PaI900473</a>
<a href="#">477417</a>
<a href="#">P471414</a>
<a href="#">472428</a>
<a href="#">800061</a>
<a href="#">473605</a>

<a href="#">511320</a>
<a href="#">276702</a>
<a href="#">472456</a>
<a href="#">D7380710401</a>
<a href="#">2p 16a 24v Tais Ip44</a>
<a href="#">08.37.0010</a>
<a href="#">464732ex</a>
<a href="#">D13011241</a>
<a href="#">463146ex</a>
<a href="#">Pal 515632</a>
<a href="#">472730</a>
<a href="#">Sp231391</a>
<a href="#">579500</a>
<a href="#">720224ul</a>
<a href="#">14.14.0080</a>
<a href="#">346338</a>
<a href="#">Nt-Rtd-393 T/R Pt100ohm-Classe B- Ambiente</a>
<a href="#">2.5 Mm2 ,4.8 X 0.8 Mm</a>
<a href="#">650426 , Raplacement 630002 And 630051</a>
<a href="#">471354</a>
<a href="#">900473</a>
<a href="#">16a 2p 24v 50/60 Hz Ip44</a>
<a href="#">249538</a>
<a href="#">Pala531021</a>
<a href="#">477 426</a>
<a href="#">720126</a>
<a href="#">D001050807</a>
<a href="#">437152</a>
<a href="#">261431</a>



<a href="#">D001050691</a>
<a href="#">831095</a>
<a href="#">477716</a>
<a href="#">511 632</a>
<a href="#">472443</a>
<a href="#">464731ex</a>
<a href="#">473317</a>
<a href="#">540034</a>
<a href="#">471-354+101221-220-250v-16a-6k-2p+t</a>
<a href="#">431237 (Ex.431027)</a>
<a href="#">532006</a>
<a href="#">W11: Industrial Dust Proof Integral Controlgear, Wellglass Luminaire, Suitable For 70w Hpsv Lamp</a>
<a href="#">471873</a>
<a href="#">431237</a>
<a href="#">515200</a>
<a href="#">472732ex</a>
<a href="#">831172</a>
<a href="#">477412</a>
<a href="#">630050</a>
<a href="#">477676</a>
<a href="#">08.33.0014</a>
<a href="#">32a-500v-3f+t-İp65</a>
<a href="#">14.14.0081</a>
<a href="#">Pal 515637</a>
<a href="#">26420469</a>
<a href="#">473303</a>
<a href="#">19.01.0385</a>