



## Pepperl Fuchs

Garanti: 12 ay  
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Pepperl Fuchs** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

*Firmamız Pepperl Fuchs Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.*

rn	Aıklama
<a href="#">Nbn4 - 12gm40 - 20 - V1</a>	
<a href="#">Kfd2-Cd-Ex1.32</a>	P&F isolating converter 1-channel. 0-20mA / 0-20mA special item 104204
<a href="#">Kfd2-Stc4-Ex1-Y1</a>	P&F transmitter feed 283680
<a href="#">Kfd2-Stc4-Ex1-Y ## Successor Type ##</a>	
<a href="#">Nx360d-F99-U2e2-V15</a>	Tilt sensor INX360D-F99-U2E2-V15 Measuring range: 0 ... 360 °, operating voltage: 10 ... 30 V DC, output type: 2 switching outputs pnp, normally open, reverse polarity protected, short-circuit proof, output type: 1 voltage output 0 ... 5 V, connection type: connector M12 x 1, 5-pin
<a href="#">P&amp;F Reflexionsli OBT350-R100-2EP-IO-V31</a>	267075-0058
<a href="#">NJ5-18GM-N-V1</a>	PTB00 ATEX 2048X
<a href="#">NBN4-12GM40-Z0-V1</a>	Induktiver Sensor
<a href="#">KFD2-STC4-EX1</a>	
<a href="#">KFD2-STC4-EX2</a>	
<a href="#">KFD2-STV4-EX1-2</a>	

<a href="#">KFD2-SH-EX1</a>	Voltage repeater - 1-channel isolated barrier - 24 V DC supply (Power Rail) - Voltage input 0 V ... -20 V - Vibration sensor input - Field supply with voltage / current - Voltage output 0 V ... -20 V - Up to SIL 2 according to IEC 61508
<a href="#">KFD2-VR4-EX1.26</a>	
<a href="#">UB2000-F42S-E5-V15</a>	133994
<a href="#">NCB1,5-8GM40-N0-V1-Y97264</a>	180206
<a href="#">KFU8-UFC-EX1.D</a>	231197 P&F Frequency converter KFU8-UFC-EX1.D
<a href="#">NCN8-18GM40-N0-V1</a>	Proximity initiator Switching distance: 8 mm, installation: non-flush, switching function: break contact (NC), output type: NAMUR, nominal voltage: 8.2 V (Ri approx. 1 k?)
<a href="#">NBN3-F69-E2-V1</a>	
<a href="#">RLK28-55-Z/31/116</a>	
<a href="#">OBT500-18GM60-E5</a>	Photoelectric proximity switch Scanning distance: 500mm, adjustable, IRED 880nm Cylindrical design M18, 80mm long, brass housing vern. Operating voltage: 10 ... 30VDC Output: 1 pnp, light / dark switching electronically switchable Connection: fixed cable 2 m
<a href="#">NJ5-18GK-N-150</a>	Inductive sensor cylindrical, switching distance: 5mm, flush Temperature range: -40 ... 150 ° C Electrical version: NAMUR with 2m AIHF cable
<a href="#">KFD2-SCD2-EX2.LK</a>	Smart output driver - 2-channel isolated barrier - 24 V DC supply (Power Rail) - Current output up to 650 Ü burden - HART I / P and positioner - Line fault monitoring - accuracy 0.1% - SIL 2 (SC 3) according to IEC / EN 61508
<a href="#">KFD0-TR-Ex1</a>	- 1-channel isolated barrier - 24 V DC supply (loop powered) - 2- or 3-wire Pt100 RTD input - Output 4 mA ... 20 mA, temperature linearization selectable - Setting of the ranges via DIP switches - Sensor break monitoring
<a href="#">SL3010-X1/GS130-133</a>	
<a href="#">KFD0-CS-EX1-5IP</a>	
<a href="#">KCD2-E2L</a>	
<a href="#">UB300-18GM40A-U-V1</a>	
<a href="#">NBB15-30GM50-A2-V1</a>	326161-0148 Induktiver Sensor
<a href="#">PROXİMİTY SWITCH NBN10-F10-E2-V1</a>	
<a href="#">3SMT PT1000 MB</a>	
<a href="#">3S WDI</a>	4-20mA
<a href="#">MODEL:A250 PSP-5/</a>	TİPİ:NBB3-V3-Z4 \ BRAKET TİP:MB1
<a href="#">MODEL:A250 PSP-5/</a>	TİPİ:NBB3-V3-Z4 \ BRAKET TİP:MB2
<a href="#">MODEL:A250 PSXP1</a>	SENSOR TİPİ:NBB3-V3-Z4 \ BRAKET TİP:MB1
<a href="#">MODEL:A250 PSXP1</a>	SENSOR TİPİ:NBB3-V3-Z4 \ BRAKET TİP:MB2
<a href="#">KFU8-UFC-EX1.D</a>	Frequency converter KFU8-UFC-EX1.D
<a href="#">KFU8-UFC-1.D</a>	
<a href="#">Z728.F</a>	
<a href="#">Nj3 0 U1 E2</a>	

<a href="#">552354</a> <a href="#">3005300110 Visolux Sensor</a>	
<a href="#">Nbb20-L2-E2-V1</a>	PART NO: 187481
<a href="#">3rg7057-3cc00-Pf</a>	
<a href="#">06.00712</a>	
<a href="#">87764</a>	
<a href="#">Nj5-18gm-N</a>	
<a href="#">Kfd2-Stc4-Ex1</a>	BARRIER
<a href="#">Nj-2-11ng</a>	
<a href="#">254606</a>	
<a href="#">Klr-C02-2,2-2,0-K70</a>	
<a href="#">Rlk28-8-H-2000-Ir</a>	
<a href="#">Kfu8-Ufc-Ex1.D</a>	P + F item no .: 231197 Series KF ... Construction housing 40mm Input frequency 0.001Hz ... 5kHz Analog output 0/4 ... 20 mA Measuring range freely parameterizable 2 relay outputs 1 electronic outputs, potential-free each output individually parameterizable up suppression Reclosing lockout Line break and Short circuit monitoring bounce filter Parameterization via control panel 1-channel SIL2 acc.to IEC 61508
<a href="#">11.02340</a>	
<a href="#">85567</a>	
<a href="#">541996</a>	
<a href="#">Nj5-18gk-Sn</a>	
<a href="#">087764</a>	
<a href="#">Nmb15-30gm65-E2-V1</a>	
<a href="#">Kfu8- Ufc- Ex1d Frequency Current Converter</a>	
<a href="#">If5826</a>	
<a href="#">Nj5-18gk-N-150</a>	
<a href="#">01.00778</a>	
<a href="#">104093</a>	
<a href="#">If-0/66</a>	
<a href="#">Dk10-Las/9s20</a>	
<a href="#">106437</a>	
<a href="#">481197</a>	
<a href="#">3rg4013-0kb00-Pf</a>	Art nr. 552300 Induktiver Sensor
<a href="#">Kfd2-Ut2-Ex2</a>	
<a href="#">256494</a>	
<a href="#">254631</a>	
<a href="#">Mlv12-8-H-350-Rt/47/65b/124</a>	

[Nbb2-12gm50-E2-V1](#)