



Pepperl Fuchs

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Pepperl Fuchs Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Pepperl Fuchs Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
Nbn4 - 12gm40 - 20 - V1	
Kfd2-Cd-Ex1.32	P&F isolating converter 1-channel. 0-20mA / 0-20mA special item 104204
Kfd2-Stc4-Ex1-Y1	P&F transmitter feed 283680
Kfd2-Stc4-Ex1-Y ## Successor Type ##	
Nx360d-F99-U2e2-V15	Tilt sensor INX360D-F99-U2E2-V15 Measuring range: 0 ... 360 °, operating voltage: 10 ... 30 V DC, output type: 2 switching outputs pnp, normally open, reverse polarity protected, short-circuit proof, output type: 1 voltage output 0 ... 5 V, connection type: connector M12 x 1, 5-pin
P&F Reflexionsli OBT350-R100-2EP-IO-V31	267075-0058
NJ5-18GM-N-V1	PTB00 ATEX 2048X
NBN4-12GM40-Z0-V1	Induktiver Sensor
KFD2-STC4-EX1	
KFD2-STC4-EX2	
KFD2-STV4-EX1-2	

KFD2-SH-EX1	Voltage repeater - 1-channel isolated barrier - 24 V DC supply (Power Rail) - Voltage input 0 V ... -20 V - Vibration sensor input - Field supply with voltage / current - Voltage output 0 V ... -20 V - Up to SIL 2 according to IEC 61508
KFD2-VR4-EX1.26	
UB2000-F42S-E5-V15	133994
NCB1,5-8GM40-N0-V1-Y97264	180206
KFU8-UFC-EX1.D	231197 P&F Frequency converter KFU8-UFC-EX1.D
NCN8-18GM40-N0-V1	Proximity initiator Switching distance: 8 mm, installation: non-flush, switching function: break contact (NC), output type: NAMUR, nominal voltage: 8.2 V (Ri approx. 1 k?)
NBN3-F69-E2-V1	
RLK28-55-Z/31/116	
OBT500-18GM60-E5	Photoelectric proximity switch Scanning distance: 500mm, adjustable, IRED 880nm Cylindrical design M18, 80mm long, brass housing vern. Operating voltage: 10 ... 30VDC Output: 1 pnp, light / dark switching electronically switchable Connection: fixed cable 2 m
NJ5-18GK-N-150	Inductive sensor cylindrical, switching distance: 5mm, flush Temperature range: -40 ... 150 ° C Electrical version: NAMUR with 2m AIHF cable
KFD2-SCD2-EX2.LK	Smart output driver - 2-channel isolated barrier - 24 V DC supply (Power Rail) - Current output up to 650 Ü burden - HART I / P and positioner - Line fault monitoring - accuracy 0.1% - SIL 2 (SC 3) according to IEC / EN 61508
KFD0-TR-Ex1	- 1-channel isolated barrier - 24 V DC supply (loop powered) - 2- or 3-wire Pt100 RTD input - Output 4 mA ... 20 mA, temperature linearization selectable - Setting of the ranges via DIP switches - Sensor break monitoring
SL3010-X1/GS130-133	
KFD0-CS-EX1-5IP	
KCD2-E2L	
UB300-18GM40A-U-V1	
NBB15-30GM50-A2-V1	326161-0148 Induktiver Sensor
PROXİMİTY SWITCH NBN10-F10-E2-V1	
3SMT PT1000 MB	
3S WDI	4-20mA
MODEL:A250 PSP-5/	TİPİ:NBB3-V3-Z4 \ BRAKET TİP:MB1
MODEL:A250 PSP-5/	TİPİ:NBB3-V3-Z4 \ BRAKET TİP:MB2
MODEL:A250 PSXP1	SENSOR TİPİ:NBB3-V3-Z4 \ BRAKET TİP:MB1
MODEL:A250 PSXP1	SENSOR TİPİ:NBB3-V3-Z4 \ BRAKET TİP:MB2
KFU8-UFC-EX1.D	Frequency converter KFU8-UFC-EX1.D
KFU8-UFC-1.D	
Z728.F	
Nj3 0 U1 E2	

552354 3005300110 Visolux Sensor	
Nbb20-L2-E2-V1	PART NO: 187481
3rg7057-3cc00-Pf	
06.00712	
87764	
Nj5-18gm-N	
Kfd2-Stc4-Ex1	BARRIER
Nj-2-11ng	
254606	
Klr-C02-2,2-2,0-K70	
Rlk28-8-H-2000-Ir	
Kfu8-Ufc-Ex1.D	P + F item no .: 231197 Series KF ... Construction housing 40mm Input frequency 0.001Hz ... 5kHz Analog output 0/4 ... 20 mA Measuring range freely parameterizable 2 relay outputs 1 electronic outputs, potential-free each output individually parameterizable up suppression Reclosing lockout Line break and Short circuit monitoring bounce filter Parameterization via control panel 1-channel SIL2 acc.to IEC 61508
11.02340	
85567	
541996	
Nj5-18gk-Sn	
087764	
Nmb15-30gm65-E2-V1	
Kfu8- Ufc- Ex1d Frequency Current Converter	
If5826	
Nj5-18gk-N-150	
01.00778	
104093	
If-0/66	
Dk10-Las/9s20	
106437	
481197	
3rg4013-0kb00-Pf	Art nr. 552300 Induktiver Sensor
Kfd2-Ut2-Ex2	
256494	
254631	
Mlv12-8-H-350-Rt/47/65b/124	

[Nbb2-12gm50-E2-V1](#)