



## Peristaltic Pump

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Peristaltic Pump** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Peristaltic Pump T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*

¼r¼n	A¼ıklama
<a href="#">SR25.6 0,8 NI/h, 115/230 V</a>	01P1350 Peristaltic pump type SR25.6 for front panel mounting, sheet thickness: min. 3.5 mm, speed: 10 rpm, delivery rate: 0.80 NI / h liquid, pressure range: 200 mbar to 2.2 bar abs., Material: Novoprene, PVDF, connections: PVDF hose connection DN 4/6, mains: 115/230 V, 50/60 Hz, cable length: 700 mm Stat. Item no. 84136080 Origin of goods: DE Pref .: EU
<a href="#">SR25.2.W, 115/230 V</a>	Peristaltic pump type SR25.2. W for wall or surface mounting, rotational speed: 5 rpm, capacity: 0.3 NI / h liquid, pressure range: 200 mbar to 2.2 bar abs., material: Novoprene, PVDF, PVDF hose connection DN 4/6, power: 115/230 V, 50/60 Hz with connection terminal Attention: Successor to 01P1000 - SR25.1 ** Harmonized code: 84136080 CoO comm .: DE pref .: EU
<a href="#">Sr25.2 0,3 NI/H, 115/230 V, Ecm</a>	Peristaltic pump type SR25.2 for front panel mounting, sheet thickness: min. 3.5 mm, speed: 5 rpm, flow rate: 0.30 NI / h liquid, pressure range: 200 mbar up to 2.2 bar abs., material: Novoprene, PVDF, PVDF hose connection DN 4/6, mains: 115/230 V, 50/60 Hz, cable length: 700 mm Stat. Lot no. 84136080 Origin of goods: DE Pref .: EU

[Sr25.2-G In Housing, 0.3 NI / H,  
115/230 V](#)

Peristaltic pump SR25.2-G in the housing, speed: 5 rpm, delivery rate: 0.3 NI / h liquid, pressure range: 200 mbar to 2.2 bar abs., Material: Novoprene, PVDF, connections: PVDF hose connection DN 4/6, housing made of Polycarbonate, dimensions (H x W x D): 105 x 105 x 107 mm, Cable entry M20, mains: 230/115 V, 50/60 Hz Stat. Lot no. 84136080  
Origin of goods: DE Pref .: EU

[Sr25.2.W 0,3 NI/H, 115/230 V](#)

Peristaltic pump type SR25.2.W for wall or surface mounting, speed: 5 rpm, delivery rate: 0.3 NI / h liquid, pressure range: 200 mbar to 2.2 bar abs., material: Novoprene, PVDF, connections: PVDF hose connection DN 4/6, mains: 115/230 V, 50/60 Hz with connection terminal \*\* Attention: successor to 01P1000 - SR25.1 \*\*