

## Pfeifer

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Pfeifer** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Pfeifer T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*



¼r¼n	A¼ıklama
<a href="#">Ø27mm / S460n</a>	
<a href="#">Ø36mm / S460n</a>	
<a href="#">G10 Pro-0,7t-M12-Lack-Gwlg.18mm</a>	Screw-on swivel G10 Pro – 0.7t –M12 – lacquer – GwLg.18mm Screw-on swivel G10 Pro Grade 10 - Significantly higher load capacity (up to 25%) than comparable quality class 8 swivel - Flexible use - 360 ° rotatable under load and Can be swiveled 180 ° - Additionally tested safety: DGUV test seal (H stamp) - Optimal planning during construction thanks 3D data Can be rotated 360 ° (under load), swiveled 180 ° Safety factor 4: 1 Operating temperature range: - 40 ° C to + 200 ° C - outside this range, reduced rates apply Load capacities according to the operating instructions M12 x 18 thread Load capacity at 90 °: 0.7 t Customs tariff number: 73269098
	Screw-on swivel G10 Pro – 1.4t –M16 – lacquer – GwLg.20mm Screw-on swivel G10 Pro Grade 10 - Significantly higher load capacity (up to 25%) than comparable quality class 8 swivel - Flexible use - 360 ° rotatable under load and 180 ° pivotable - Additionally tested safety: DGUV test seal

<a href="#">G10 Pro-1,4t-M16-Lack-Gwlg.20mm</a>	(H stamp) - Optimal planning during construction thanks to 3D data Can be rotated 360 ° (under load), swiveled 180 ° Safety factor 4: 1 Operating temperature range: - 40 ° C to + 200 ° C - outside this range, reduced rates apply Load capacities according to the operating instructions Thread M16 x 20 load capacity at 90 °: 1.4 t Customs tariff number: 73269098 EU
<a href="#">Type PKR251 (Compact Full Range Gauge)</a>	
<a href="#">283665</a>	RHINO hydraulic jack - Lifting force 10.0t - Optimally suitable for the horizontal and vertical commitment - Safe working thanks to the pressure relief valve - Flexible rotation thanks to the 360 ° rotatable housing - easy handling with removable hand lever - Exact lowering through the drain valve - Large and stable base plate for perfect Stability - Weight 35 kg - Lifting range with lifting foot 30 - 260 mm
<a href="#">21611704</a>	
<a href="#">D24 BUCHSE L=78 mm</a>	
<a href="#">M24 x 200 mm.</a>	
<a href="#">M24 x 78 mm. TRANSPORTANKER</a>	
<a href="#">Rope 15.00 P106 1960 U currently TK2</a>	Special rope conforming to EN 12385-4 . Twisted ends wound on a reel Length 233,000 (m)
<a href="#">262488 ASW AR1-C800X-1.4T-M16X2-EL20MM</a>	Screw-on swivel / Type: G10 PRO (AW) Screw-on swivel G10 Pro Grade 10 - Significantly higher load capacity (up to 25%) than comparable grade 8 screw-on swivel - Flexible use - Rotates 360° under load and pivots 180° - Additional safety testing: DGUV test seal (H stamp) - Optimal planning during construction thanks to 3D data Rotates 360° (under load), pivots 180° Safety factor 4:1 Operating temperature range: - 40 °C to + 200 °C - outside this range, reduced load capacities apply according to the operating instructions Thread M16 x 20 Load capacity at 90°: 1.4 t
<a href="#">Pf110 125-T</a>	
<a href="#">12.501.710.010</a>	
<a href="#">Pf127 232-X</a>	
<a href="#">2110900001</a>	
<a href="#">123115</a>	
<a href="#">135871klh(12.501.710 Alte Bez.)</a>	
<a href="#">Pf146 037</a>	
<a href="#">Pf110 116-T</a>	
<a href="#">48 03 1000.002</a>	
<a href="#">110932</a>	

<a href="#">Pf100 325-T</a>
<a href="#">110937</a>
<a href="#">122541+123115</a>
<a href="#">119665</a>
<a href="#">110922</a>
<a href="#">110935</a>
<a href="#">P103414</a>
<a href="#">135631</a>
<a href="#">119667</a>
<a href="#">Pf124 016</a>
<a href="#">110928</a>
<a href="#">110920</a>
<a href="#">A037385</a>
<a href="#">255596</a>
<a href="#">05.051.241</a>
<a href="#">Pf 100 316-T</a>
<a href="#">110926</a>