

Pfeiffer

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Pfeiffer Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Pfeiffer T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunulmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
	<p>001 Swivel fitting B29148 2pcs Origin Com. 205.2796 Designation data Design data Crowd Supply air 4.0 bar DeltaP 16.0 bar Test pressure passage standard 6 bar Medium Not specified Temperature ¼C No information How Fail Close works Drive position A1 (Pfeiffer standard) 001.001 k14b3061b63 2 pcs BR14b DN80 PN40 B1 R20 WTD Lug HSB7 Control or butterfly valve, double eccentric, end fitting Case: 1.4408 Slice: 1.4408 Shift shaft: 1.4542/H1150 Storage: 1.4571/HSB7 Seat ring: PTFE seal ring/spring loaded Housing seal: PTFE Shaft seal: disc spring-loaded PTFE roof boot packing Version: TA-Luft continuous sealing strip Flange sealing strip: EN 1092-1 Form B1 Length: EN 558 R20 (46mm) DIN / ISO 5211: F05 / SW 14 MD Max at 20¼C [Nm]: 592 PS(1) / TS(1) 40bar (-60C) PS(2) / TS(2) 40bar (50C) PT [bar]: 63 TS Min [¼C]: -60 TS Max [¼C]: 200 001.002 36000 2 pcs Strength and leak testing PED 2014/68/EU + AD2000-A4 Test basis: DIN EN 12266-1 Device design: DIN 3354 flaps + DIN 3230 part 3; Direction: on the rule side Strength test: DIN EN 12266-1 P10 (see test instructions) Leak test: DIN EN 12266-1 P11 (see test instructions) Seat tightness: DIN EN 12266-1 P12 (see test instructions) Leak rate: A 001.003 43643fc 2 pcs SRP00220-4.0 F10-VK22 BR31a Standard FC</p>

Valve system contains;

Pfeiffer double piston swivel drive Version: BR31a standard
Housing: aluminum; ALODUR Size: 220 DIN 5211 flange: F10
Shaft holder: VK22 - internal square 22mm diagonal Swivel
angle: 90° +5°/-15° in both end positions Mode of action:
single-acting Number of springs: 4+4 Spring rotation
direction: CW - clockwise Safety position: Closed Pneumatic
connection: NAMUR 24x32mm; G1/4" VDI/VDE3845 Level 1:
AA2 (80x30x30) Perm. Ambient temperature: -40°C...+80°C
Including blowout-proof end stops and integrated centering
ring 001.004 ms14b0008 2 pcs Mounting kit F10/F05-D22/H14
BR14b DN80/100; CS; 1.4305; A4-70 BR/CS-F10/F05-
D22/H14-C4-A1 BR/CS console 1.0038 hot-dip galvanized
F10/F05 Drive side F10 Fitting side F05 D22/H14 coupling
1.4305 Drive side 22mm diagonal external square Fitting side
14mm internal two-flat C4 - A1 Corrosivity category C4 /
requirement class A1 Screws A4-70 001.005 30600 2 pcs
Attachment of the swivel drive F10 001.006 408182 3730-3-
110010400001001001009997 e/p positioner TROVIS 3730
HART Ex approval and marking II 2 G Ex ia IIC T4/T6 Gb / II
2D Ex ia IIIC T85 °C Db, BVS 18 ATEX E 044 X; Slot A:
position indicator 4 to 20 mA; Slot C: 2 inductive Limit
contacts SJ2-SN, NC (NAMUR) and binary output (NAMUR);
Electrical Connection 2-fold M20 x 1.5, 1 cable gland; SIL;
Hardware version 1.00.00; Software version V2.00.15; Variant
ID: 100132249/100132248 001.007 46424 Heavy attachment
kit 3730 on drive, AA1-AA4 VDI/VDE 3845; 90°, for BR31a 15-
5000 Attachments to part-turn drives VDI/VDE 3845 (for all
dimensions of level 1 / 2009), heavy version Variant ID:
1400-9244 001.008 44198 Connection plate 3730/3766
aluminum G1/4"; for free piping Connection plate 3730/3766
Aluminum G1/4" Variant ID: 1400-7461 001.009 30581
Mounting positioner 001.010 b0001316 Piping 2 components
V4A 8mm Ermeto Complete piping of 2 components Material:
- Ermeto stainless steel screw connections - Tube Ø 8mm
stainless steel 001.011 34001 Inspection certificate 3.1
according to DIN EN 10204 accordingly Pressure Equipment
Directive 2014/68/EU and the AD-2000 leaflets Exams:
Dimensional testing, strength testing, Leak test, functional
test 001.012 34003 Material acceptance test certificate 3.1
according to DIN EN 10204 accordingly Pressure Equipment
Directive 2014/68/EU Materials in accordance with EN
standards and AD 2000 information sheets

[B4707283MA](#)

TPR 280, Active Pirani Transmitter DN 16 ISO-KF PT R26 950A

[Tpr 281 Ptr2195a](#)

[Fds361](#)

[Pk002952](#)

[Uno 120 A\(Pkd 16602\)](#)

[Pk 216507-R](#)

[Pm C01 720](#)

[Pk 213151-R](#)

Pt 448 250 -T	
Ptr26501	VACUUM COMPACT PROCESS ION GAUGE
2112700001	
Tcp015	ELECTRONIC DRIVE CONTROLLER FOR PUMP
Srp00060-4,0 F05-Y-D-14 43619fc	
Ptr26500	PROCESS ION GAUGE SS ELECTRON COLLECTOR 16W 30V
Part No:330 Ident No:58400245.14	
Cmr264, Tube Dia 1/2 Inch	
55000041.011 + 55000000.002	
Pt R33 130	
Pk004522	
Tpr265 Dn16 Iso-Kf	
Cmr264 Tube Dia 1/2 Inch	
55000041.001 (Ex.50000040.001)	
Tph-330	PUMP ASSEMBLY
50000040.001(Ex.2110900001)	
Pmc01-692a	VACUUM PUMP CONTROLLER TURBO TC100
120vkz016	
Survos Rapid D	
Pt G28 030	
Ptrb050-0,5x1,0 Al	
Pt 110 030-T	
Pt 110 040-T	
Pk E00 002 -T	
Ptrb050-0,5x1,0 Al/540591	
Okta4000a	
Pm-C01-473	POWER SUPPLY 100-240V 50/60HZ
P4004 314dx	
Pm-P01-203-H1123	TURBO PUMP
B5181214qz	
Fernbedienung Mit Spiralkabel	

Pp E20 008-T	
06126005001	
Tpu-180h	VACUUM TURBO PUMP
N4001 318ct	
Pt R26 950 A Tpr 280, Active Pirani Transmitter	
Duo 5 M Pk D61 712 C	
Cmr263, Tube Dia 1/2 Inch	
Pk D61 712 D Drehschieberpumpe	
Pk300044-X	
Pf 324 016	
Pk-D63-105-B	VACUUM PUMP
Pt R26 000	
21127000.001352385	
Pkd41702a	
Tcp-121	DRIVE UNIT
05.018.203	
Pt R24 621	
Rd30	
Okta500a	
Pk004524	
122876	
Tph170	TURBO PUMP VACUUM
Pt R24 601	
Pmp02290	
Tml261	PUMP
Lp 503, Schnuffelsonde Fur Smarttest Und Qualytest	
P 4150449a1	
Tpd011n	VACUUM PUMP W/POWER SUPPLY
Orf 004 , By Odk 005	

Tcp-035	ELECTRONIC DRIVE UNIT 28-36V TURBOMOLECULAR PUMP
Pm E01 000-T	
119568	
55000040.001	
Pp E11 013 -T	
Pk213140	
Duo-20m	VACUUM PUMP
Pk2133140	
55 00 0030.002 [ex. Ptrr50 11006]	
Pk Z40 145	
Tpg 300	
Tpr 280, Active Pirani Transmitter Dn 16 Iso-Kf, 80;C Catalog Å Pt R26 950 A	
Pk E62 026-T	
Tmh100 Ip	
Tph-190	VACUUM PUMP 190L/S
Duo 2.5	
210sdtlam	OIL PUMP 3PHASE MOTOR 170-254V 50HZ 170-300V 60HZ
Fernbedienung Rc 500 WI Fur Heliumlecksucher Asm 3xx Kabellos Bis 100 M	
Pf324010	
Tmh261-250-030-P-X	VACUUM PUMP 6000/MIN 1000HZ
Pm01320	VACCUM PUMP TURBO 230LITERS/SECOND TYPE TPH240
Tpr010	
Ppw21000	PUMP
Ptrb050-0,5x1,0 A	
Tmh261p	DRAG PUMP TURBOMOLECULAR
Pp E21 006-T	
Rd30*3.50	