



## Phymetrix

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Phymetrix** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Phymetrix T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunulmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*

¼r¼n	A¼ıklama
<a href="#">Hydrobaby (handheld device for mobile measurement)</a>	- 110°C to +20°C dew point measuring range, all gas-contacting parts made of 316 stainless steel and PTFE, 1/8" Swagelok cutting ring connection in the inlet and outlet, Housing protection class IP65, integrated temperature compensation, incl. Drying chamber for the sensor, USB interface (can be used for Recharging the batteries), including measured value storage Features: - easy-to-read graphic LCD display - Softkeys on the front for selecting the described menus. - Acoustic feedback when keys are pressed and alarm signals. - Graph/diagrams of moisture measurement with automatic scaling - Help texts for each context of the individual menus. - Protection of the batteries through customer-specific switch-off times. - USB port - Built-in pressure measurement & pressure-corrected humidity display (simultaneously displayed with uncorrected value) (at an additional charge) - Password use possible to prevent unauthorized use Danger: Aggressive gases such as ammonia, chlorine, HCL, SO2 are excluded
<a href="#">Pressure compensation 0-10 bar</a>	Pressure is automatically recognized and taken into account
<a href="#">Interface extension</a>	4-20mA output

<a href="#">PPMa a with NIST</a>	Cert <msnual teflon Tube Charger USB cable
<a href="#">Weatherproof carrying case</a>	
<a href="#">Ppma</a>	
<a href="#">Model Ppma</a>	
<a href="#">Model: Dd5 (Optionally)</a>	Panel Mount Moisture Display (5 digit),
<a href="#">Plma Dd5 Power</a>	Phymetrix PLMA DD5 Power Input: 90-260VAC47-440Hz,Range: 5 digits -19999 t o 99999 programmable decimal
<a href="#">Model Plma</a>	
<a href="#">Plmarange: -110°</a>	Phymetrix PLMARange: -110° C to +20°C dewpoint ( -166°F to +68°F dewpoint )5V DC to 28VDC two wire loop operation 4mA to 20mA Sensor, humidity - PHYMETRIX PLMA
<a href="#">Plma</a>	Phymetrix Loop powered Moisture Analyzer, Model: PLMa provided w/Certificate of Conf. to NIST, User's Manual &10' cable
<a href="#">Model: Sc-1 (Optionally)</a>	Sample Cell 3/4"-16 sensor well 1/8"NPTF in&out