

Pintsch Bamag



Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Pintsch Bamag Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Pintsch Bamag T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	A¼ıklama
000 798 300-214	
5-008725700734	
8-000601338214	
8-000798300214E	
8-001212700214	
8-902450012643	
8-902450035602	
8-902850042635	
GRP.SFB 25-H/ KFB 40	
002378957652	KLFSa 24V DC, yelow,
Model SFB 40/55, Moment 550 Nm	110 V DC, 2 A, 220W Serial : 902083145001, Year 2002, Maker/Pintsch Bamag Dins Laken
Brake Disk Type:KFB63	902451038128, Torque:630Nm, 207VDC, 212W
902 450 006 710	
Kfb16	
001186201214	

035 620 957-001	
1.3 Brake Flange	
031 411 126-000	
008 284 901-958	
8 001225313214	
Sfb 25-H/Kfb40	
035 075 772-000	
000 594 500 214	
902 451 047 880	
042 572 498-000	
1ms/Ns Kfb 40/47	
000 582 690 214	
031 411 803-000	
000 594 600 214	
000 594 500-214	
002375406653	
8-000594600214e Reibbelagtrã196;Ger-Grp:	
Kfb10	
Sfb 63 , A400, 110v	Electromagnetic two-surface spring pressure brake SFB 63 - braking torque 630 Nm - coil voltage 110 V DC - Flange A 400 according to IEC standard and DIN 42948 / DIN EN 50347 FF 350 - Degree of protection IP 67 according to DIN EN 60529 / VDE 0470-1 - Manual airscrews (standard version) - housing centered (interchangeable) - Painting with two-component epoxy primer Nomenclature number: 85052000
042 524 036 000	
Jad334	PB.NR-207284401000 WONDEL GOLTOMANN
4-008166101734	
001 041 900-214	
8-001046300214e	
000 594 900-214	
501799 7.5 Dc24v 1.37a A=9.5mm	
	8-TOTAL-MAB Driving hub SFB 63 completely drilled ØxxH7

8-Total-Mab	incl. keyway according to DIN6885 / 1; Tolerance zone P9, L = xxx mm, L1 = xxx mm, can be used for SFB 63
8-000595500214 Bolzen Sfb 25	
Bs5 R	
042 524 064-000	
8-000798300214e Sfb 25-H / Kfb 40	
Kfb40 8-001063500214	
Kfb30	
8-0000596	
000 594 600-214	
Sfb 25-H/ Kfb 40 (8-000798300214e)	
000 594 900 214	
4-008166100734	
047 010 012-009	
033 020 784-000	
8-000589300214 Bremsflansch	
000 595 800-214	
000 595 500 214	
042 524 036-000	
8 000798400214e	
8-001225313214	
042 572 498 000	
031 411 532-000	
4 008166100734	
000 595 300 214	
000 595 300-214	
000798300214e	
032 410 210-000	
001063500214	
065420110000	
1.4 Armature Plate	

[Kfb40 8-001063500214](#)

[000 595 500-214](#)

[001 041 900 214](#)

[Kfb40](#)

[Kfb160](#)