

Plymovent

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Plymovent Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Plymovent T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
Mobilegoplus/3m (215)	0000111473
Dualgoplus/3+4m (435)	0000111515
Monogoplus/4m (215)	0000111491
Kua-4	Metal tube arm
Monogo Plus	Stationary filter unit with METAL tube arm
MFD 435	7025100000
UltraFlex-3 / extraction arm	7925170090
UltraFlex-4 / extraction arm (alternative)	7925220090
MAGNETIC SAFETY KIT	(DISCONNECT THE CAR EXHAUST SYSTEM HOSE WHEN INSTALLING THE METER AWAY TO MOVE FREE AND EMPLOYEES, AT THE SAME TIME CERTAIN THICKNESS IN THE EXHAUST SYSTEM FROM THE INLET, WHERE THE HOUSING HOSE AND SYSTEM DAMAGE TO THE MAGNETIC DAMAGE TO THE REPLACEMENT)

MAGNETIC EXHAUST	VEHICLE HOSE CONNECTION KIT (MAGNETIC CONNECTION ON THE FIRE VEHICLE EXHAUST PIPE-TO THE SUCTION HOSE AGAINST MAGNETIC HOSE AGAINST MAGNETIC HOSE CONNECTION APPLICATION TO THE LEAKAGE EMPLOYMENT WHEN THE VEHICLE CONNECTION IS CONNECTED TO THE LEAKAGE SYSTEM.
VEHICLE RADIO FREQUENCY TRANSMITTER	(CONNECTED TO THE VEHICLE IGNITION, IT ENABLES THE FAN TO AUTOMATICALLY WHEN THE VEHICLE IGNITION IS TURNED ON. THE TRANSMITTER SENDS A WIRELESS SIGNAL TO THE NRC-24V/230V RECEIVER AND RUNS THE FAN TO RUNNING THE PRODUCT DEVICE -300 DEVICE DEVICE.
RADIO FREQUENCY RECEIVER	(RECEIVE THE OPERATION OF THE SYSTEM BY DETECTING THE SIGNAL FROM THE SIGNAL TRANSMITTER ON THE VEHIC BY OPERATION OF THE VEHICLE, THE RECEIVER SENSOR STOPPING THE SYSTEM AFTER THE VEHICLE LEADS FROM THE PARTICULAR DISTANCE STATION - WORKING RANGE 100-300 MT)
MANAGEMENT BOARD	(A SYSTEM PANEL WITH AUTOMATIC AND MANUAL OPERATION FEATURE AND WITH ITS INSIDE PROTECTION FUSE, WHEN THE SYSTEM IS ACTIVE, THE SYSTEM STARTS AND STOPS THE SYSTEM WITH THE INFORMATION RECEIVED FROM THE SIGNAL RECEIVERS AND THE SYSTEM FAN FREQUENCY CONTROL)
09820310110	
09850060050	
37756	
37993	
6387	
7274	
FCC-50/HE	
H10-610x610x292	
110877	SER-850 Spring operated hose reel for 125 mm-150 mm hose Hose capacity up to 10 m, 850 mm drum width Excl. hose connection-
111919	MAS-150 Hose connection kit Ø 150 mm, for SER reels-Hose Connection Kit Stoppers and Reductions
110200	ET 150 Exhaust hose Ø 150 mm, L = 10 m-Exhaust Suction Hose L:10m D:100 mm-650 C temperature
109627	HTA 150-200 Hose connection Ø 150 mm, nozzle Ø 150 mm- Alu. Exhaust Nozzle
100306	FUA-3000 (435) Extraction Fan-1,5 HP-380 V-50 Hz-3 ph
80FMS055	Fan Manual Starter 2,5-4 Fan Thermal Switch

DUCTS	Ventilation Channels/Suspension Consoles/Fittings/Jet Cap-Fan post front shot
Oc-1 Me-41/42	
6475-1011	
6900-1011	FILTER CARTRIDGE
Oc-2 Me-41/42	