

Procentec



Garanti: 12 ay

Bu ¼r¼ne ait T¼rkiye ii kapı teslim fiyat ve teslim s¼resi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

Procentec Markası, tedarik s¼resi iin l¼tfen bizimle iletiŐime geiniz.

Firmamız Procentec T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	Aıklama
Profihub A5	16010 RS485 5-fach Repeater IP65 f¼r PROFIBUS DP / MPI & PROFISAVE galvanically isolated output channels; EMC filter through BIT regeneration; Integrated switchable Terminating resistors; Bus status display per channel; Automatic baud rate detection 9.6 Kbps - 12Mbps; 31 devices per channel; Protection class IP65; UL listed
PA003135	CONNECTOR PROFIBUS DP DIAGNOSTIC FC PG (90°) RS485 IN IP 20 ENVIRONMENTS WITH DIAGNOSTIC INDICATORS
101-00211A	
1720R	
17210R	
17420	
37020	
37021 (PROFIBUS)	
B5-17010	
GC-PB-CB-1CH-SC	
ProfiBUS-Hub B5 5	
17030X	ProfiSwitch X5 RS485 5-channel repeater with variable baud rate per channel for PROFIBUS DP / MPI & PROFISAVE 5 galvanically isolated output channels; Multiple connection options (screw connections, SUB-D, universal clamps); Redundant power supply with 2x 24V connection; EMI filter by BIT regeneration and robust operation mode (optional); switchable redundancy mode; Integrated switchable terminating resistors; bus status display per channel;

	configurable baud rate per channel; 31 devices per channel; protection class IP20; UL (E365044-A1-UL), DNV (A-13659), FCC & CE certifications
ProfiHub B5+R	17020R RS485 5-channel repeater with diagnostic function for PROFIBUS DP / MPI & PROFISAVE 5 galvanically isolated output channels; Multiple connection options (screw connections, SUB-D, universal clamps); Redundant power supply with 2x 24V connection; EMI filter by BIT regeneration and robust operation mode (optional); switchable redundancy mode; Integrated switchable terminating resistors; bus status display per channel; Automatic baud rate detection 9.6 Kbps – 12Mbps; 31 devices per channel; Capable of diagnostics as a PROFIBUS slave via PLC connection or with Procentec COMBricks; protection class IP20; Certifications according to UL (E365044-A1-UL), DNV (A-13659), FCC & CE
101-2000127	ComBricks Fixed Backplane HS + 6 Sub
101-20011C	ComBricks Head Station Type 1C
SA3060	Anybus Premium Fee
101-201101	ComBricks 1 Channel Repeater
101-200qc4s	
101-201610	
110-00013a	
101-201102	
37021 Profitrace 2	
101-201101	
Profihub B5+rd	
Kompakter Repeater B1	
100-201610	
101-201530	
Profihub-A5	
101-20011b	
101-210210k	
16010	PROFIBUS HUB 5 CHANNEL DP REPEATER 10-32VDC 4.1W
38022	
14020	
L45467-G16-C355	
101-200qbs	

101-00201a	
Gc-Pb-Profihub-B	
101-20011c	
B5-17010 Obsolete/Replacement 17020r	
Pa003135.	
17020r	
17020rd	
39020	
17030x	
16011	
Profitrace 2	
101-200	
513-00011a	
101-00211a T1 Terminator	
101-20011ck	
Profihub-B5	
101-200012	
514-00011a	
Profihub A5 (16010)	
Dp Hub 16010	
Ab7000-C	
Profihub B5+r	17020R B5 + R is the successor product of the B5, which is not more we offered
37021	
17010	
Erdungsschiene Fuer Profihub A5 (16011)	
Gc-Detect-Pb-Kit2-Upro	
101-201210	ComBricks 1 Channel SCOPE Repeater