

## Profibus

Garanti: 12 ay  
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Profibus** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

*Firmamız Profibus Trkiye Distribtr veya temsilcisi deėildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.*



rn	Aıklama
<a href="#">Crevis_Na-9122</a>	
<a href="#">Profibus-Tester Pb-Q One</a>	Incl.case, CD, manual guide, adapter, USB cable * Assessment of physical and logical transmission quality * fully automatic detection of PROFIBUS topology under running Production conditions with indication of Repeaters and cable lengths * suitable for acceptance and Commissioning, maintenance and service as well Troubleshooting in PROFIBUS networks Stat.-commodity code: 90303370 Country of origin: Federal Republic of Germany Net weight: 1.50 kg
<a href="#">Pa Adapter Fr Pb-Q One</a>	Nomenclature number: 90303370 Country of origin: Federal Republic Germany
<a href="#">Pbmb Ii Profibus Assembly Module</a>	(blue housing) Input: 24 V DC (20 - 28V, reverse polarity protected) Output: 5V DC / 200mA short-circuit proof PIN 5 (GND) 6 (+ 5V) * Connection via screw terminal * Type of fastening: snap on DIN rail according to EN 50022 Net weight: 0.033 kg Static product no .: 85423190 UL No .: E218520 Country of origin: European Community (EEC Germany) No cumulation applied with preference
<a href="#">M12 Terminating Resistor Socket B-Coded Ip67</a>	Screw thread (M12 x 1 mm) recommended Tightening torque 0.6 Nm, self-locking Degree of protection: IP67 when plugged in and screwed on (EN 60529) Material (locking): zinc Die-cast, matt nickel-plated country of origin: Germany Stat. Product number: 85331000
<a href="#">Adapter Set For M12 Connection Technology</a>	with M12 connection technology, including terminating resistor Nomenclature number: 85075000
<a href="#">Anybus AB7000-C</a>	Device to Fieldbus Converter

<a href="#">110010050</a>	
<a href="#">17020R</a>	
<a href="#">226534</a>	
<a href="#">38022</a>	
<a href="#">DDL-NN-006012</a>	
<a href="#">PA003135</a>	
<a href="#">DDA-NN-006014</a>	PROFIBUS testers 5 sets To check the cabling, the bus physics and the Communication in PROFIBUS-DP networks. Including PROFIBUS Tester 5 main unit (DDA-NN-006015), portable oscilloscope, PC software PROFIBUS diagnostic suite, manuals, power pack (100..240V/50..60Hz), mains cable (EU+USA) and adapter cable in carrying case. -- For deliveries within the EU: -- According to EU regulation 1907/2006 (REACH) Article 33 we hereby inform you that this product has the following Substance(s) from ECHA's extended candidate list for special contains Substances of Very High Concern (SVHC) above the Limit of 0.1 percent by weight is/is: - 1,2-dimethoxyethane,ethylene glycol dimethyl ether (EGDME) (CAS No. 110-71-4 1)
<a href="#">DDA-NN-006014</a>	PROFIBUS testers 5 sets To check the cabling, the bus physics and the Communication in PROFIBUS-DP networks. Including PROFIBUS Tester 5 main unit (DDA-NN-006015), portable oscilloscope, power supply (100..240V/50..60Hz), mains cable (EU+USA) and adapter cable in carrying case.
<a href="#">DUCKER/ELK/10168487/PROFIBUS GATEWAY/BIHL WIEDEMAN</a>	BWU2545
<a href="#">CNC/PLC SST PCU3L-A</a>	
<a href="#">PROFIBUS Troubleshooting Toolkit Ultra PRO</a>	38022
<a href="#">VCI 1P CA</a>	DP INTERFACE
<a href="#">NL 51N-DPL</a>	PROFINET / PROFIBUS Proxy connector Upgrading a PROFIBUS Slave to PROFINET Quick and easy transformaton from a PROFIBUS DP Slave to a PROFINET IO-Device Direct mounting to the PROFIBUS interface Full support of PROFIBUS alarms, diagnosis, and DPV1 Automatic generation of the PROFINET GSDML file Certified device renders PROFINET certification by the customer unnecessary
<a href="#">2862398</a>	
<a href="#">Pbif1ms</a>	PC BOARD
<a href="#">Bluambas® Pb Comfort - Funkmaster</a>	Protection class IP 65 PROFIBUS over radio " - Connection of up to 4 PROFIBUS nodes at max. 1.5 Mbps - Connection of 1 radio master with max. 4 radio slaves - Bluetooth wireless technology 2.4 GHz, 100 mW - Range: up to 100 m (Antenna-dependent) - Power supply: 24 V DC Stat. Lot number: 85176200 Net weight: ..... country of origin: Germany
<a href="#">700-972-6aa02</a>	
<a href="#">Encoder.Crd58-8192 R 4096 C2z01 Profibus</a>	
<a href="#">Fast Corner Pg 6es7972-0ba50-0xa0</a>	
<a href="#">Mlc9002-Bm240pb Bus Control Module</a>	
<a href="#">6137591</a>	
<a href="#">Profibus Diagnostic Case Iii</a>	for service and commissioning Diagnostic tools for continuous and temporary network analysis in PROFIBUS for commissioning and service * PB-Q One - PROFIBUS Tester * PROFtest II XL without DP master function - Line tester * PB INSpektor® NT - Distributed Data Collector *

	APKA II - Active programming cable * Plug-in power supply 24V / 1.25A * EMCheck LSMZ I - Leakage measuring clamp * Transport case Customs tariff number: 90308930 Country of origin: Federal Republic of Germany
<a href="#">Kpi1000</a>	
<a href="#">Rpba-01</a>	
<a href="#">9350-9 Diag Conn 90</a>	
<a href="#">2170212 Unitronik Bus Fdp L2/Fip 1x2x0,64 Laap</a>	
<a href="#">Bc-Pbmb-Pb-S</a>	
<a href="#">Bc-600-Pb-Cb-M12</a>	
<a href="#">Profibus-Dp</a>	
<a href="#">Awg22s</a>	
<a href="#">2718688 Pho01720</a>	
<a href="#">Pb-B V3.3</a>	
<a href="#">I-7550-B Cr</a>	
<a href="#">Mms6350/Dp</a>	
<a href="#">Tra-Pb-Ts</a>	
<a href="#">Bc-M12dp-Pb</a>	
<a href="#">Bwu1703</a>	
<a href="#">700-972-6aa00</a>	
<a href="#">Ocd-Dpc1b-1212-C100-H3p</a>	
<a href="#">Cev-65m-01460</a>	
<a href="#">Ab7821-F(Bwu1703)</a>	
<a href="#">Patest</a>	* Segment check with "OK / BAD" display * Recording the number of devices in the segment * Live List Display * Registration and cancellation of participants * Telegram errors and repetitions * Segment voltage display * Display of signal levels of all devices * Short-circuit detection between signal wires and cable shield * Measurement of interference mean and - peak value Goods tariff number: 90303310 Equipment: * PAtest with MBP and USB interface * Connection cable with measuring adapter * USB cable
<a href="#">Dp / V1</a>	
<a href="#">700-972-0bb12 Profibus-Stecker, 90;</a>	
<a href="#">Bm4-O-Pro-01-00-00</a>	
<a href="#">Bluambas® Pb Comfort - Radio Slave</a>	Protection class IP 65 PROFIBUS over radio " - Connection of up to 4 PROFIBUS nodes at max. 1.5 Mbps - Connection of 1 radio master with max. 4 radio slaves - Bluetooth wireless technology 2.4 GHz, 100 mW - Range: up to 100 m (depending on antenna) - Power supply: 24 V DC Stat. Lot number: 85176200 Net weight: ..... country of origin: Germany - Power supply: 24 V DC Stat. Lot number: 85176200 Net weight: ..... country of origin: Germany
<a href="#">4.071</a>	
<a href="#">S202-F4/06/0r-001/0b-K0</a>	

<a href="#">Bk3120-0.050</a>	
<a href="#">Bc-502-Pb</a>	
<a href="#">Gcdetectpbkit2pl</a>	ANALYZER
<a href="#">Pb-Lsz-Chb3</a>	
<a href="#">Bidp-170</a>	
<a href="#">Gcdetectpbtr2hws</a>	ANALYZER
<a href="#">Dp-Encoder</a>	
<a href="#">Gccif104pb</a>	MODULE
<a href="#">Rif 1769?Dpm</a>	
<a href="#">700-972-0ba12 Profibus-Stecker, 90;</a>	
<a href="#">Gcdetectpbkit2up</a>	ANALYZER
<a href="#">Mlc9002-An11100 Mlcsoftware, User Manual And Cabel</a>	
<a href="#">Bc-600-Pb-Cb-Dsub1</a>	
<a href="#">700-884-Mpi21</a>	NETLink® PRO Compact, PROFIBUS Ethernet gateway - PROFIBUS - ETHERNET/IP