



## Raoul Lenoir

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Raoul Lenoir** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Raoul Lenoir T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*

¼r¼n	A¼ıklama
<a href="#">CIRCULAR LIFTING MAGNET</a>	ITEM 1 CIRCULAR LIFTING MAGNET Diameter : 1 500 mm Weight : 2 500 mm Protection : IP 55 Power : 10 000 Watts at 15 C Voltage : 220 VDC Duty cycle 60 % (10 Mn Cycle) Ribbed foundry frame made of high magnetic permeability cast steel Wear plate non magnetic manganese steel Winding out of aluminium wire conducting material A fill in resin blocking and insulating the coil in the frame with dielectric property External reinforced connecting box Chain with three common suspension ring Lifting capacity kg Slab : 19000 Turning Density 0.2 1T/M3 : 330 Light scrap : Density 1 3 T/M3 :630 Cast iron Density 3 4.5 T/M3 : 1100 Ball : 6500
<a href="#">ALSCH/CC1000</a>	1 FEEDING, COMMAND & CONTROL DEVICES FROM OUR MODEL General features : Cabinet dimension : L1200 x H1200 x D400 mm Painting : RAL 7035 Tension 3 x 400 VAC , 50 Hz Working rate 100 % One main fuse switch Transformer with separate winding (supplied with box) with primary tension variation + 5% Rectifier with diode bridge, inverted voltage 1200 V with RC circuit One socle with fuses HPC type protector <input type="checkbox"/> Inverted supply unit magnetization and unmagnetization including : One magnetization ion relay

	Discharging resistance box (provide for external use with roof and lateral side) Protection devices : fuses, diode...protection are used to avoid short cut, overload, fuses in the DC output Relays supplied are wired on terminal blocks and with identified cores.
<a href="#">1 BACKUP SECURITY SYSTEM BB/CC1000</a>	Included : - 1 Electronic charger included in our control box TRL 12 - Automatic released when the charging cycle is completed - Protection class IP65 - Casing acidproof - Lighting and audio alarm when the batteries power is required Please note that the battery box has to be ventilated or air cooled Nota : These equipments will be supplied by us : 1) Industrial and Maintenance free battery elements for 20 minutes autonomy for 220 VDC operation voltage 2) Battery box Mounting, adapting, setting up and other accessories at your expenses or supplied with extra cost.
<a href="#">1 SET HEAVY DUTY CONNECTORS</a>	- Spring mark LEGRAND - Female and male - Capacity : 16 000 W - Voltage : 220 VDC
<a href="#">CABLE REELS</a>	- Spring mark LEGRAND (Mechanical motorisation) - Trade mark DELACHAUX - Active cable length 25 m
<a href="#">Belt For Ov 630/100p</a>	
<a href="#">Ovap 1000/35</a>	
<a href="#">Adi/90m</a>	
<a href="#">10903001</a>	
<a href="#">05163f 17736</a>	We need the Magnetic Sticks (1100mm length 250mm diameter) PLEASE SEE ATTACHED PHOTO
<a href="#">A0903099</a>	
<a href="#">Belt For Ovh790/80p</a>	