

## Raritan

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Raritan** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Raritan T¼rkiye Distrib¼t¼r¼ veya temsilcisi deėildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*



¼r¼n	A¼ıklama
<a href="#">DKX4-101</a>	Manufacturer item number: DUMMYCC
<a href="#">Three-phase Total Measurement ipPDU</a>	(VERTICAL) 3 phase input, 3 1 phase output 32A-IEC 60309, 3P + N + E, 24 pieces C13 6 pieces C19
<a href="#">Single phase Total Measurement ipPDU</a>	(HORIZONTAL) 1 phase input, 1 phase output 32A-IEC 60309, 2P + E, 6 pieces C13
<a href="#">Single phase Total Measurement non ipPDU</a>	(HORIZONTAL) 1 phase input, 1 phase output 32A-IEC 60309, 2P + E, 6 pieces C13
<a href="#">Three-phase Port Based Measurement</a>	(Outlet) PDU (VERTICAL) 3 phase input, 3 1 phase output 32A-IEC 60309, 3P + N + E, 18 pieces C13 6 pieces C20
<a href="#">Three Phase Metering IN-LINE METER PDU</a>	(19 "HORIZONTAL), 2 x 3-phase input 2 x 3-phase output 32A, IEC 60309-3P + N + E, with american socket
<a href="#">Monophase Metering IN-LINE METER PDU</a>	(19 "HORIZONTAL), 2 1 phase input 2 1 phase output 32A, IEC 60309-2P + E american socket
<a href="#">3PH - 32A Non-IP PDU</a>	(VERTICAL) with analyzer 3 phase input, 3 x 1 phase output 32A-IEC 60309, 3P + N + E, 18 pcs C13 6 pcs C19
<a href="#">C13-C14 power cable - 1 meter</a>	
<a href="#">C13-C14 power cable - 2 meter</a>	
<a href="#">C19-C20 power cable - 1.5 meters</a>	

<a href="#">C19-C20 power cable - 2,5 meters</a>	
<a href="#">C14 - European female adapter - 25 cm</a>	
<a href="#">3x32Trifaz input</a>	3 Pieces 32 Mono output Octopus American socket cable
<a href="#">KVM Switch (Single Port KX II-101)</a>	
<a href="#">PX3-5528V-V2</a>	3PH Wye, 400V AC, 32A, 18 x C-13, 6 x C-19 3PH Wye, 400V AC, 32A, 24 outlets: 18 x IEC C-13, 6 x IEC C-19, plug: IEC 60309 32A 3P + N + PE, 22.2kVA, Zero U vertical PDU, Ethernet, serial, USB-A, USB-B and sensor connections, sequential phase assignment
<a href="#">DX2-T2H2</a>	Temperature (2) and Humidity (2) Sensor Temperature (2) & Humidity (2) Sensor with Replaceable Sensor Head for PX3 PDU
<a href="#">DSX2-48</a>	48-port serial console server with dual-power AC and dual gigabi 48-port serial console server with dual-power AC and dual gigabit LAN. Serial, USB and KVM local console ports. 19" rack mount kit.
<a href="#">PX3-4260R</a>	Outlet Metered iPDU (Single Phase): 1PH, 230V AC, 16A, 12 Outlet Outlet Metered iPDU (Single Phase): 1PH, 230V AC, 16A, 12 Outlets:12x IEC C13, Input Type: IEC60309 16A, 3.8kVA, 1U Horizontal, Ethernet, Serial, USB-A, USB-B, Environmental Rack Sensor Port
<a href="#">PX2-418012R</a>	
<a href="#">SRC-0100</a>	100-240V, 1U Smart rack controller with dual power input, 1 x RJ 100-240V, 1U Smart rack controller with dual power input, 1 x RJ- 45 sensor port, 1 x RJ-45 feature port for AMS, 1 x RJ-45 RS-485 port, 2 x USB-A port, 1 x USB-B port, 1 x RJ-45 10/100/1000 Mbps Ethernet port, 1 x RJ-45 10/100 Mbps Ethernet port, High res
<a href="#">DX2-T1H1</a>	Temperature (1) and Humidity (1) Sensor Temperature (1) and Humidity (1) Sensor with replaceable Sensor Head for PX3 PDU.
<a href="#">SRC-0100-KIT</a>	100-240V, 1U Smart rack controller with 1 x DX2-T3H1 sensor 100-240V, 1U Smart rack controller with dual power input, 1 xRJ- 45 sensor port, 1 xRJ-45 feature port for AMS, 1 xRJ-45 RS232 console port, 2 xUSB-A port, 1xUSB-B port, 2 xRJ-45 10/100/1000 Mbps Ethernet port, High res. LCD display und 1 x DX2-T3H1 sensor
<a href="#">electro scan; 24V Treatment System; 1,2 Ah</a>	Saltwater
<a href="#">PX3-3270</a>	Inline Meter: 3PH Wye, 190-415V AC, 32/30A (32A/PH Rated), 2 Lin Inline Meter: 3PH Wye, 190-415V AC, 32/30A (32A/PH Rated), 2 Lines, Input Type: 2x AC Terminal, Outlet Type: 2x AC Terminal, 1U, Ethernet, Serial, 2x USB-A, USB-B and Sensor Connections
<a href="#">PX3-5367CR-E2</a>	Monitored and switched rack PDU (2U Horizontal) 3.7kVA, 16 outlets). INPUT: 230v, 16a - IEC 60320 C20 plug (2P3W); OUTPUT: 14@ C13 Locking, 2@ C19
<a href="#">DSX2-48</a>	48-port serial console server with dualpower AC and dual gigabit LAN. Serial, USB and KVM local console ports. 19" rack mount kit.
<a href="#">In-Line Meter PX3-3270</a>	
<a href="#">POWER CORD 1 M C13/C14 LOCKING TYPE</a>	
<a href="#">POWER CORD 1.5 M C13/C14 LOCKING TYPE</a>	
<a href="#">POWER CORD 2 M C13/C14 LOCKING TYPE</a>	
<a href="#">POWER CORD 2.5 M C13/C14 LOCKING TYPE</a>	
<a href="#">POWER CORD 3 M C13/C14 LOCKING TYPE</a>	
<a href="#">POWER CORD 3.5 M C13/C14 LOCKING TYPE</a>	
<a href="#">POWER CORD C19/C18 LOCKING TYPE</a>	

[PDU HORIZONTAL \(Raritan - PX3-1843R-F12-M11\)](#)

[PDU STS \(Raritan PX3TS-1469R\)](#)

[PDU VERTICAL \(Raritan - PC1002V-F12-11\)](#)

[Px2-4134nr](#)

[Px3-3280](#)

[Px3-3420](#)

[Px2-4092r Pdu,](#)

Raritan PX2-4092R PDU, 230VAC, 32A, 1ph, IEC 60309 2P + E 6h, 3m connection cable, 7.36kVA, output: 4x IEC C-19, 16A, Measuring monitoring of outputs

[Px3-3220](#)

[Px3-3270](#)