



Raytech

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Raytech Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Raytech T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	A¼ıklama
33kv	
11kv	
Titel 3	
Titel 3-A	
Titel 3-B	
Titel 3-C	
Titel 4	
84044	OHM gel socket GCL OHM gel sleeve for 3x cables 1X 6mm ° or 3 insulated wires; use underwater IPX8; ready to use, pre-filled Gel; halogen-free UV resistant; operating temperature up to 90 °; dimensions 61x35x28 mm LxWxH; EN 50393 m. Terminals EN 61238-1 - PU 1 pc.
GEL FILLED CLIP ATTACHMENT BOX 41 MM	Unfortunately there is no article number, only these specifications from the customer. IT WILL BE PLASTIC HOUSING, READY GEL FILLED. THE PLASTIC BODY ON THE CABLE ENTRY OUTPUTS WILL BE FLEXIBLE. IT WILL BE EN 50393, UL 94-HB QUALITY CERTIFICATES. IT WILL ALLOW APPLICATION BETWEEN -40C°/+50C°. IT WILL BE IP68 PROTECTION CLASS. IT WILL BE AT LEAST 41 MM IN LENGTH.

GEL FILLED ATTACHMENT BOX WITH CLIP 45 MM	IT WILL BE PLASTIC HOUSING, READY GEL FILLED. THE PLASTIC BODY ON THE CABLE ENTRY OUTPUTS WILL BE FLEXIBLE. IT WILL BE EN 50393, UL 94-HB QUALITY CERTIFICATES. IT WILL ALLOW APPLICATION BETWEEN -40Cº/+50Cº. IT WILL BE IP68 PROTECTION CLASS. LENGTH WILL BE AT LEAST 45 MM.
GEL FILLED ATTACHMENT BOX WITH CLIP 53 MM	IT WILL BE PLASTIC HOUSING, READY GEL FILLED. THE PLASTIC BODY ON THE CABLE ENTRY OUTPUTS WILL BE FLEXIBLE. IT WILL BE EN 50393, UL 94-HB QUALITY CERTIFICATES. IT WILL ALLOW APPLICATION BETWEEN -40Cº/+50Cº. IT WILL BE IP68 PROTECTION CLASS. IT WILL BE AT LEAST 53 MM IN LENGTH.
GEL FILLED FLAT SPLIT MUF 3X2,5 MM2	IT WILL BE PLASTIC HOUSING, READY GEL FILLED. CABLE ENTRY OUTPUTS WILL HAVE SUITABLE FITTINGS. IT WILL BE THE NECESSARY TERMINAL GROUP FOR CABLE CONNECTION. IT WILL BE EN 50393, UL 94-HB QUALITY CERTIFICATES. IT WILL ALLOW APPLICATION BETWEEN -40Cº/+50Cº. IT WILL BE IP69 PROTECTION CLASS. IT WILL ALLOW CONNECTIONS UP TO 3x2.5 MM CABLE SECTION. IT WILL BE AT LEAST 80 MM LENGTH.
GEL FILLED FLAT SPLIT MUF 3X4 MM2	IT WILL BE PLASTIC HOUSING, READY GEL FILLED. CABLE ENTRY OUTPUTS WILL HAVE SUITABLE FITTINGS. IT WILL BE THE NECESSARY TERMINAL GROUP FOR CABLE CONNECTION. IT WILL BE EN 50393, UL 94-HB QUALITY CERTIFICATES. IT WILL ALLOW APPLICATION BETWEEN -40Cº/+50Cº. IT WILL BE IP69 PROTECTION CLASS. IT WILL ALLOW CONNECTION UP TO 3x4 MM CABLE SECTION. IT WILL BE AT LEAST 80 MM LENGTH.
Tr-1p (70032)	
Ls-88cb,10-107 Obsolete Repl By 89748537	
Wr50-12 / Digital- Wicklungswiderstandsmessgerät	
Wr50-12 (70035n)	
70049nv	
Tr-1p	
Micro Jr.2	
30-Chemt6u - Not Available	
Wr 50 Dc	
Item No.: 70049n	
90064-100	
Item No.: 70032	
Mwtm-160/50-1500/142	
Micro Junior 2 Micro Ohm Meter	
Item No.: 70025n	
2490189	
Tp-01	
Wr50-12 Dc	
Wr50-12	
89748537	
Cwt-3811	

168951	
Mj-04.	
Tr-1 (70031)	
Item No.: 70035n	
Ls-88cb,10-106 Obsolete Repl By 89748537	
Wr14	
Lps10	
Ip68	
Micro Centrium 2 (Mc2)	
70035n	
Wrz-512	
Tr-Mark Iii (70049nv)	
Tp-03	
Tr-Mark Iii 250v	For 3 phase Turns Ratio measurements
30198-100, Wr50 2ch-Mc	
My04	
Tr-Mark Iii	
T-Rex (70003)	