

Raytek



Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Raytek** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Raytek Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
RAYMI310LTS	MI310 sensor head with 1m cable Temperature range: -40 ... 600 ° C, spectral Sensitivity: 8 ... 14µm, optics: 10: 1, Response time: 130ms, 1m cable, Sensor head ambient temperature max. 120 ° C Customs tariff no .: 90251900 Country of origin: DE ECCN: EAR99 The designation XXXMIACAP2 is not known, that's why we offer you the following article.
XXXMIACAB	adjustable mounting bracket for MI sensors Customs tariff no .: 90259000 Country of origin: DE ECCN: EAR99 Optionally, we also offer you the Evaluation electronics for the sensor heads
RAYMI3COMM	Alternative position MI3 communication box Output signals: 0/4 ... 20mA, 0 ... 5 / 10V, J, K, R and S thermocouples; Emissivity: adjustable from 0.2 ... 1, graph. Display, USB 2.0 connection Customs tariff number: 84733020 Country of origin: DE ECCN: EAR99
Fluke 62 MAX+	Fluke Infrared Thermometer 62 MAX + -30 ... 650 ° C, accuracy + -1.0% or 1.0 ° C, Emissivity adjustable from 0.1 ... 1.0, Optics 12: 1, protection class IP54; Double
RAYMI310LTHCB3	MI310 high temperature sensor head with 3m electric wire Temperature range: -40 ... 600 ° C, spectral Sensitivity: 8 ... 14µm, optics: 10: 1, Response time: 130ms, 3m cable, Sensor head ambient temperature max. 180 ° C Customs tariff no .: 90251900 DE
XXXMIACAJI	Air bubble housing installed for MI sensors
RAYMI3COMM	MI3 communication box Output signals: 0/4 ... 20mA, 0 ... 5 / 10V, J, K, R and S thermocouples; Emissivity: adjustable from 0.2 ... 1, graph.

	Display, USB 2.0 connection
RAYR3IPLUS1MSCL	Raytek Raynger 3i Plus 700 ...3000°C, dual laser and Perspective visor, emissivity adjustable, Optics 250:1, spectral range 1µm, USB interface, Software DataTemp 3i Plus, tote bag Customs fee number. 90251900 Country of origin: CN ECCN: EAR99
RAYR3IPLUS1ML	alternative position Raytek Raynger 3i Plus 700 ...3000°C, dual laser sight, Adjustable emissivity, optics 250:1, spectral range 1µm, USB interface, DataTemp 3i Plus software, carrying case Customs fee number. 90251900 Country of origin: CN
RAYCMLTJ3M	Raytek Compact Series CMLTJ3M Measuring range: -20...+500°C, output: Type J thermocouple, emissivity 0.1...1.1 digitally adjustable, optics 13:1, 8...14µm, M18*1, 3m cable
RAYMI310LTHCB8	MI310 high temperature sensor head with 8m Cable Temperature range: -40...600°C, spectral Sensitivity: 8...14µm, optics: 10:1, Response time: 130ms, 8m cable, Sensor head ambient temperature max. 180°C
XXXMIACAJI	Air blow housing (no cooling) - installed, for MI3xxLTH only as installed option possible
RAYMI3COMM	alternative position MI3 communications box Output signals: 0/4...20mA, 0...5/10V, Type J,K,R and S thermocouples; Emissivity: adjustable from 0.2...1, graph. Display, USB 2.0 port
RAYR3IPLUS2ML	Raytek Raynger 3i Plus 400 ...2000°C, dual laser sight, Adjustable emissivity, optics 250:1, Spectral range 1.6µm, USB 2.0 and Bluetooth interface, Software DataTemp 3i Plus, tote bag
RAYGPC PANEL METRE 24 VDC -HTF	
RAYMI3COMM	MI3 communications box Output signals: 0/4...20mA, 0...5/10V, Type J,K,R and S thermocouples; Emissivity: adjustable from 0.2...1, graph. Display, USB 2.0 port
RAYTXCLTPCF1W	
RAYMI3COMM	Communication box (metal) in IP65 housing, for MI3 measuring head, with USB 2.0 interface and analog outputs including Data Temp Multidrop Software (Win 7)
RAYMI310LTH_CB8	RAYMI310LTHCB8 Miniature temperature sensor - High temperature sensor for Ambient temperatures up to 180°C - Temperature range -40 to 600°C - Wavelength 8 to 14 µm - Optics D:S 10:1 - Response time 130 ms - 8m cable
625737022306	
RAYMI320LTHCB8 L	
RAYMI3COMM	
PYROMETRE RAYXRTLTSFA	
RAYM13COMM	20C0923
S-CS-PI	CS SYSTEM POSITION SENSOR
RAYMI310LTSCB3	TEMPERATURE MEASURING SENSOR
Raygps-Sfl	GPS STANDARD FOCUS SENSING HD W/8-14 MICRON 50:1
Raytxfltpsfw	TEMPERATURE SENSOR INFRARED THERMALERT
Koruma Cami/Raymid02ltcd3	
Raymi320lthcb8	

Rayfr1bcf2 (10m Cable)	
Spec/Raytxchtsfw	
Raytxtj3	HOUSING
Cs210 System Verbindungsbox (Xxxcs210conbox)	
Mi310ltscb3	
4489412	Raynger Portable IR Thermometer 752 to 3632F
Rayci-3-A	IR Temperature Sensor 10 mV/C Linear Voltage, 0-350C
(Wja) M-5 Wja	
Raytmp50lt	THERMAL PROCESS IMAGER MP50 20-300DEG C
Miacfb	Mounting Bracket
Raycmltv3	
Raymr1sbsf + Raymt	
Rayrhltcf	INFRARED SENSOR
Cs 210	
M13	
Autopro St25 - By 42509 (Marke Extech Instruments)	
Infrarot-Thermometer Raytek Typ Cmltk3m	
3781034	Modular 4TE DIN mountable 4-channel IR thermometer system
Raynger Sg2	
Raygprsf	TEMPERATURE SENSOR 110/220VAC 4-20MA 1/8IN DIN
Rat3p	THERMALERT 3PLUS MONITOR TEMPERATURE MEASUREMENT
Mmactv	
DI2txcltsfw	PYROMETER
(Software) For Raymid02ltcd3	
3781052	Modular 6TE DIN mountable 4-channel IR thermometer system
562	THERMOMETER
Txsltcf2w	
Raygprcf	TEMPERATURE SENSOR INFRARED
4221848	Modular 6TE DIN mountable 4-channel IR thermometer system
2474951	Air cooling and purging system with .8m insulated air hose.
Rayxrltssfs	
Raymi310ltscb3 1.00 0.00 341.00 0.00 341.00 341.00	
Rayxrcltsfs	
Rayxrtlctf1	

Raymm2mlvfil	INFRARED THERM
Raymic10ltcb3 Disabled	
Fluke68(Exraynger St 80)	
Xxxmi3acpwp	
Cs 100 - , Follow Up Model Cs 210	
Dx6mid10lt (353402) Referenz Ist Nicht Bekannt	
E1rl-F2-L-0-0	
Raymi310lts	
Raytxchtsf Sensor Tx C Ht Sf	
4489401	Raynger Portable IR Thermometer 1292 to 5432F
Rayt4balt-A71	INFRARED TEMPERATURE SENSOR
Raytxshtsfis5	
C 13 A	
Xxx2ccb8	
Xxxmiacab	
Rayr3iltld12u	THERMOMETER
Dr6txsmtsfw	
Mid10lt	
Raygpscfl	INFARED SENSING HEAD SIGHTED CLOSED 1MW 630-670NM
Mi3 Messkopf	
Raygpc2469926	
Rayc13b10ld	
St20 Pro ? Xb , By 42509	
Rayci3a10 Ld Ir	
Ray Txs Ht Sf Is5	
Ray3i2ml2	
Xxxtxactwhs	
St20	
Raymr1sarf	
Xxxysecp	
Mj-04	
V17111-130	
Micaj	
Raymid10lt	
Raytek Raynger Mx4 Plus Td Messbereich: -30 ..	

900 ;C Optik: 60:1,Koffer 2 1 Batterie Und Bedienungs	
Rayxrtltsfa	TEMPERATURE SENSOR INFARED
Rayst6lse	PORTABLE INFARED THERMOMETER
Cmltkm	
Raymx4ptdu	THERMOMETER INFRARED -25-1600F
Raymmltsf1v	INFRARED SENSOR MARATHON MM SERIES
Raytxcltspf	TEMPERATURE SENSOR INFRARED 4-20MA LOW TEMP
Mi3-Comm-Lt-G5	
Raynger-St80	
Xxxcmacpwm	
4489435	Raynger Portable IR Thermometer with Scope, 752 to 3632F
Xxtxxar	
Rayxxmiacab	
Raygprcfw	INFRARED SENSING HEAD AIR/WATER 0-1000DEG F
Txs Ht Sf	
Rs232-485	
Raymi3mcomm	
Kommunikationsbox Fur Mi3	
Raytek Raymi3comm Pyrometer	
Raytxsltsfw	
St-80 Obsolete Replaced By Rayst81	
Raytxshtsf	
Mi3 Heads	
Rayr3iplus1ml	
Raymr1sbsf+raymtak	
Raymid10lt 5c5146 -	
A71t3p	DISPLAY
Raytek Raynger Mx2 Td Messbereich: -30 .. 900 ;C Optik: 60:1, Zehntelgradauflosung 1 1 Mit Koffer, B	
Rayxxsysecpi	
3781041	Modular 6TE DIN mountable 4-channel IR thermometer system
Raytek-Ursprungserzeugnis-F3;R-Raymr1sarf-Istanbul-Turkiye	
4363355	MI3 series IR thermometer I/O box with USB 2.0
Et2ltsfjwc	SENSOR
Raytes150 Lt	

Ch ,0-5 Volt	
Raymr1sbsfw	
67874	
Rayst60xb	
Raynger St 60	
St60xxeu	
Xxxmiacaj	
1911882	
Raytxfltsfw	TEMPERATURE DETECTOR 4-20MA
Rayci-2-A	IR Temperature Sensor K T/C, 0-350C
Raymtake	
Raymid10ltcb3 , Raymi310ltscb3	
Rayfr1bcf2 (22m Cable)	
Raytxcltsf	
Txfltsf	
Cb3	
Raynger-St60	
Raytes150 P31	
Raymi310ltscb8	
Rayxxx2ccb8	
Txxtj1	
Typ Cmltj	
1911881	
Rayxrcmtsfa	TEMPERATURE INFRARED SENSOR
Rayxrtltsf	TEMP SENSOR
122836	LASER TEMPERATURE SENSOR
Lt	
Scl01pute1	
Xxxcmapm	
Rayst6lxcg Bu Urun Artik Uretilmemekte.	
1201shaffer	
305000140788	
Ray Mi3 10 Ltf Cb3	
Raymm2sbsfl	INFRARED THERM
Ray Cmltjm	
Et3ltsfwc	CONTROL

Raytxsltsf	INFRARED SENSOR LOW TEMPERATURE W/33:1OPTIC
St61	
Xxxracwcs	
Mid10ltsb3	Infrared Sensor
Rayxacrck	
Raymi310lth_Cb8	
Spec/Raytxsltsfs	
2cltcb4	
Rayfa2bsf3	
Mi3	
Xxtxxmb	
Mmltsvf1l	
Rayxcltsfw	
Raycmltv	
Et2ltsfk	SENSOR
Raymi3comm	
Raynger St61	
F9jmih20ltsb5	
Txxacpa	
2470039	GPS Sensing Head, Std.Focus 8-14 U
Rayr31lrl2	
Mc 12a	
Xxxhsfic2	
Raymi-D-02-Lt-Cb3	IR Temperature Sensor, 2:1 Optics, -40 to 600C
Mi3 Ir	
Rayt3b	MONITOR TEMPERATURE MEASUREMENT THERMALERT III
Ry-Mi3-02ltscb8	
Xxx2cltcb15	
Rayci2a	
Raymt6u	
Raymid02ltcd3 Yeni (Digital)	
Xxxsyscct	
XxxmiacrajÁ;	
Raymm1mlvf1l	
4093306	MI3 series IR thermometer I/O box with USB 2.0

Raymi310ltscb1	
Raymi310g5s	IR Sensor, 10:1 Optics, 1m, 250 to 1650C (382 to 3002F)
42509	
Raymid20ltcb3	CABLE
Rayxrt7	
Xxx2ccb4	
Rayst81	
Raycmltj3m	
Raytxsmtsf	
Raytxcltcf1	
Mx2	INFRARED DETR
Raymico2 Ltcb3	
Tpt80hr+ls	
Vt240s-5p Hb01	
Rayr312ml3u	
D54txsf2sf	
St-60 Obsolete Replaced By Rayst61	
Raygprsfw	TEMPERATURE SENSOR INFRARED
Xxxtxmst	
Raymic10ltcb3 , No	
Raynger St	
Rayrpm40l3e	PORTABLE INFARED THERMOMETER W/LEATHER CASE
4489420	Raynger Portable IR Thermometer w/Scope, 1292 to 5432F
Mi3comm	
Raymi310lth Cb3	
Raymr1scf-Ben	SENSOR INFRARED TEMPERATURE 1000-3000DEG C 24VDC
Et3ltsf	SENSOR
Raytes150 P30	
Scr01pute1	
Rayt30b	MONITOR TEMPERATURE MEASUREMENT
Rayst61	
Xxxtstc12	
Rayr3i2ml2g	
Raymi310lth (Not Offered)	
Raymi302ltscb3	
303b3.1	

It2sf	
3966024	SENSOR
Txxacap	
56-0415-0-0-0-6a	
Rayet3ltsfc	
4093298	MI3 series IR thermometer I/O box with USB 2.0
Raytek Ray-Mi3-10ltscb3	
Raynger-St20	
Rayci-1-B	IR Temperature Sensor J T/C, 30-500C
Raymr1sbsf S/N: 19790008 Power: 24vdc - 32035	
Raymx2tdu	SENSOR
Xxx 2c Cb8	
Raynger 3i 1m	
Lrl2u	INFARED LASER THERMOMETER RAYNGER-3I
Handheld Pyrometer :2m Temp. Range: 200ã186; To 1800;C (400ã186; To 3275;F),Spectral Response: 1.0 M	
Raygpm2	
Raycmltkm	
Raygpm10cb3	
Xxxtxactwm	
Raymid10ltsb3	
Raymi320lthcb3	
Thermalert Tx	
4363370	Modular 6TE DIN mountable 4-channel IR thermometer system
Mi310lts	
Raymi320lth	IR Sensor, 22:1 Optics, 1m, 0 to 1000C (32 to 1832F)
Raycmltvm	
Ci-3b	IR Temperature Sensor 10 mV/C Voltage, 30-500C
Pm30l2n1u	TEMP PROBE
Raygprsf	INFRARED SNSR
2474960	Air cooling and purging system with 2.8m insulated air hose.
Raymr1sbsf	
Rayr3ilrscl2u	
3781065	Modular 6TE DIN mountable 4-channel IR thermometer system
Raytxchtsf	

Raymmg5lvf1lw	TRANSMITTER
5g-1007-0-0-0-2a	
Raymi310lth	IR Sensor, 10:1 Optics, 1m, -40 to 600C (-40 to 1112F)
Xxxtxactwl	
Rayci-1-A	IR Temperature Sensor Type J T/C, 0-115C
Raygpc	Panel mount meter & PS 110/220 VAC for Ceiling Mount Sensors
Raytxfltpsf	INFRARED THERMOMETER PYROMETER
E1rl-F2-V-O-O	
Mmltssf1	
Rayfr1bcf2 (3m Cable)	
Xxxcmacram	
Txcltpsf	INFRA RED THERMOMETER THERMALERT TX SERIES 3C155
Mi3 Box	
Raymi310ltscb3	
St2	
Xxxtjacft	
Xxxtxactwh	
Raytxfltsf	TEMPERATURE DETECTOR
Rayrhp3sfwc	INFRARED SENSOR
95 0144	
Xxxmiaccj1á;Á;	
Raymih10ltcb3	INFRARED SENSOR 10:1OPTICS W/3M CABLE
Xxxciadjb	
Mt4	
Raymx2u	
Rayfr1bcf2 (6m Cable)	
Raytek Minitemp Mt6u	
Xxxysecpi	
Raymi-C-10-Lt	Modular Infrared Thermometer -40C to 600C
Raymi310ltfcb3	
Raymr1scsf	
Rayxxxmi3100ap	
Rayxxxmi3100adjb	
305000139962	
Raytmp150lt	
D6txcltsf	INFRARED TEMPERATURE SENSOR OUTPUT 4-20MA

Rayxrtltsfs	SENSOR
Xxx2cltcb4	
Raytek Cm	
Raymi310ltscb15	
Rayfr1bcf2 (1m Cable)	
Raymi3mcomme	
Raytxfltp7	SENSOR
Mi3 Display Usb 2.0	
Xxx485cv2	