

Raziol

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Raziol Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Raziol T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunulmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
1012100150	RB F 0150 Roller lubricator standard felt ø 60 mm Low-wear felt rollers ø60 mm. The felt rollers are supplied with oil from the inside out through fixed hollow axles, Roll adjustment by tension springs, Min.recommended belt width: approx. 80 mm max.greasing width: 150 mm, Permissible oil viscosity (40 ° C): approx. 150 mm² / s With oil connection hoses and optical Feed control (dropper chambers), Model TK 2.
1080040004	D 040 ST SSO 2.5 bar upright "NC contact" 40 l container upright completely assembled with: ----- - "NC" float switch with device socket - Compressed air fitting up to 2.5 bar
1044111300	Oil distributor block VBMV-2 with two magnetic valves (but without throttles) on mounting plate for separate pressure reservoir. Complete with 2 solenoid coils 24V DC, oil connection for hose 10x3.5 and screw connections for hose PU-8/6, incl. hose NBR / PVC 10x3.5 (Aø17 / Iø10), assembled to 5 m

3009532111	THROTTLE COMPLETE FOR OIL DISTRIBUTION BLOCKS VBMV AND VBMV-02 Thread 1/8 "
1042110012	
4043000047	
4043000050	Cable 05.0 m for valve 5/2-1/4 to EBAD4000 KL appliance socket incl. LED quenching diode
1012180300	RB 300 FK-P SW Roller oiler Kipp Pneumatic felt ø 60 with the following properties: - Oil mist-free lubricant application through low-wear felt rollers - The oil supply to the felt rollers is done from the inside by fixed hollow axles. - The adjustment of the upper roller to the material is done by Pneumatic cylinder, stroke height approx. 10 mm, with swivel device - Roller set change without tools - Oil connection on both sides of the upper and lower roller Technical data: - greasing rollers ø 60 mm - Maximum recommended material thickness: approx. 5.0 mm - Maximum recommended oil viscosity (40°C): approx. 150 mm ² /s - The oil must not be resinous and must not contain any solids. Dimensions: - Length in DLR: approx. 100 mm - Width across the DLR: approx. 555 mm (incl. space for oil connection) - Passline: 80 mm The scope of delivery of the roller oiler includes oil connection hoses with optical inflow control (dropper chambers TK4) including four quick-connector sockets. With built-in roller change kit:
1045911111	HST hand lever up to 2.5 bar LIFT CONTROL HAND OPERATED For starting and stopping the upper greasing roller (e.g. when threading the tape) With pressure reducer and pressure gauge up to 2.5 bar and connections for hose PU-LUFT 4/2.3
1045911112	HST HOSE, ø 4/2.5 mm 2 x 2 m - 4 x 1 m Pneumatic hose for connecting the stroke control with the pneumatic cylinders the roller oiler.
3073141320	
3073141326	
3073141321	
09539254	
80720005	
3073141324	
1080720017	
3073141317	
3073141325	
Ebad3000	
Rb Pf-Sw 1200	981133 Rollendurchmesser: 40 mm Wellenlänge: 1200 mm

3009165500	
Kit-2-11/13-16	
1080720005	
3073141318	
3073141327	
Lubricate Machine	800mm long 6mm thick
3001080400	
3073141323	
1080720017(Ex, 80720005)	