

RECO

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
RECO Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız RECO T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunulmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
RECO Membrane MB-DN 25	RECO diaphragm MB-DN 25 CleaningLine membrane Material TPE-E Purge / raw gas temperature -20 ... + 100 ° C Medium quality class 2 compressed air (ISO 8573) Country of origin: Germany Manufacturer: RECO GmbH
RM-216 C.10.01	RECO filter control RM-216C.10.01 Loop-Bus System EasyLine IN 110/ 230V~, 26-28 V= OUT 24V= NormLine 28.08, 250x160x90 mm Protection IP-66, NEMA 5 Gland 1x M16, 3x M25 Plug 1x M16, 1x M20, 1x M25 dp- Connector N6/4 Range OUT 4-20mA=0-5000Pa RM-216C.10.01
017410615002	
10502741	
10600001	
10600013	
10600075	
10600258	

10600717
10600750
10601330
10602301
10602304
10602400
10603055
10603060
10603206
10603227
10603228
10603271
10603291
10603292 RM-BV 12 DP 10V ATEX
10603944
10697145
16000014
16000300
16000300 (RM-216 C.10.01)
16000302
16000310
16000340
16000351
16000380
16000395
16000500
16000532
2/2 N4,5-8P-24VDC
2/2 NG4,0-6P-24VD
2/2 NG4,0-6P-24VDC
2/2 NG4,5-8P-24VDC

21115936
53010001
60250293
61700000
61700002
61700004
61700096
61700099
61700123
70100002
70100026
70100046
70100049
70100056
70100057
70100074
70500279
DHL
H07RN-F 5x1,5mm? 0,2m
H07RN-F 5x1,5mm? 10m
H07RN-F 5x1,5mm? 2m
MB-DN 25
P/N 353119-01
PCB
pn10600001
RM-200C
RM-208 CB 13 UL 0V
RM-216 CB.10
RM-216 CB.10 ATEX
RM-216C

RM-300_C	
RM-BV_12_DP	
RM-BV_12_DP_3V_ATEX	
RM-BV4	
RM-BV8	
RM-BV8.10.04 (10600329)	
RM-DPC	
RM-LV_6 / 5V	
RM-N_4,5	
VD-DN25;E343908_SET	
VPE5_10600013	
RM-BV4_Micro_DP_2V_ATEX	RECO filter control RM-BV4 Micro DP 2V ATEX Basic Line IN 230V~ OUT 24V= BluLine S 321/2.02 IP-66, NEMA 4 Certificate ATEX Zone 22 Cat 3 D 2 mounted RM-Valve NG 4P6R-90° 1xM16+BP, 1x M20+BP DP-Connector 6/4
NG_4	
2/2_NG4,0-6P-24VDC	RECO Magnetventil, solenoid valve Components 2/2 magnetic valve input supply voltage 24V DC power 22 W ED 10% with seal and gland M25 - black RECO
RM-200C	RECO filter control RM-200C Plug and Play ATEX with connection cable RECO filter control RM-200C plug and play ATEX EasyLine loop bus 10m IN 100-240VAC OUT loop bus DP sensor 0-5000 Pa +/-1% Certificates CE, ATEX 3D housing PC; IP 66, NEMA 4 NormLine 057Z-001; 250x160x90mm B,H,T Connections 1xM25, 2xM20, 1xM16 DP connector TPC push-4/6mm 1x connector M25-5 pole 1.5 mm² Hardware RM-200C xx.xx 1x connection cable_H07RN-F 5x1.5mm²- Male-socket-M25-10m(6025 0261)
RM-LV_6 / 5V	RECO valve module RM-LV 6 / 5V RECO valve module RM-LV 6 / 5V EasyLine loop bus IN loop bus OUT loop bus Valve outputs 5, 24V= Solenoid valve RM-N 4.5 Certificates CE, ATEX 3GD housing Al; IP-66 Al box ST_Al valve box 5V anod.; L 299, W 156, H 91mm Connections 2x plug connector M25-5 pin 1.5mm²
Connection_cable_H07RN-F_5x1.5mm²	10m Connection cable_H07RN-F 5x1.5mm²- Male-female M25
RM-216_C.10	Loop-Bus System EasyLine IN 110/ 230V~, 26-28 V= OUT 24V= NormLine 28.08, 250x160x90 mm Protection IP-66, NEMA 5 Gland 1x M16, 3x M25 Plug 1x M16, 1x M20, 1x M25 dp- Connector N6/4 Range OUT 4-20mA=0-5000Pa RM-216C.10.01
RM-LV_4/2V	

MB-DN 40-50 VS	p/n 61700099
Filter control RM-BV 12 DP 3V ATEX	RECO filter control RM-BV 12 DP 3V ATEX Stand Alone System IN 110/230 V~ OUT 24V= BlueLine 150/3.01, 250x160x90mm Protection IP-66, NEMA 4 Certificate ATEX Zone 22 Cat 3D 3 mounted RM-Valve NG 4P6R-90° Gland 1xM16+BP, 1xM25+BP DP-Sensor 0-5000Pa=4-20mA DP-Connector 6/4 RM- BV12.01.01
310602GLY	Gauge 760mmHg/0/10.5Bar/C2.5 1/4 LAWER