

Red Lion



Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Red Lion Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Red Lion Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn

Aıklama

[Paxi0030](#)

Industrial speedometer / preset counter Measuring input: NPN, PNP sensors, CMOS, TTL, HTL, Namur Number of digits: 6 digits Digits: LED 7-segment red Digit height: 14 mm Case size: 92 x 45 mm Supply voltage: 11-36 VDC Degree of protection: IP65 on the front Housing dimensions: W 97 x H 50 x D 105 mm Operation: push button Connection: fixed terminal block

[Px2chz00 \(Px2c8h00 In Muadil Modeli\)](#)

horizontal PID control with reduced Overshoot - universal input for process, - temperature, voltage, current and resistance - Programmable two-line display with units and bar chart - Four programmable universal detectors - Three color display with 7 programmable Color zones - Optionally installable option cards for Setpoints, - Communication and retransmitted Analog output - Support for FlexCards, including second analog input, - Remote setpoint, heating current monitoring or a 2nd PID controller - Ramp / Soak Capability, up to 16 profiles with 20 steps each - Up to 16 alarms with Boolean Logic functionality - Built-in USB programming port - Allows device configuration with the Crimson® programming software - NEMA 4X / IP65 Sealed front panel Dimensions:

	96.52x 49.53 x105.16mm Weight: 226.8 g Customs tariff number: 8504409580 Country of manufacture: USA
Paxcds20	Plug-in relay output card 4x changer for PAX digital display and large digital display LPAX Weight: 100g Customs tariff number: 9032.90.6080 Country of origin: US
Paxcdl10	Plug-in analog output card for PAX digital display and large digital display LPAX 0 to 20 mA, 4 to 20 mA or 0 to 10 VDC Country of manufacture: USA Weight: approx.10g Customs tariff number: 9032.90.6080
PAXP0000	Industrial digital display / process signal display Measuring input: standard signals 0/4 ... 20 mA, 0 ... 10VDC Measuring rate: 20 measurements / sec., A / D converter with 16 bit resolution User inputs: 3, programmable Number of digits: 5 digits Digits: LED 7-segment red Digit height: 14 mm Case size: 96 x 48 mm Supply voltage: 85-250 VAC Protection class: IP65 on the front Housing dimensions: 96 x 48 x 104 mm Operation: push button Connection: fixed terminal strip Country of manufacture: USA Weight: 227g Customs tariff number: 9029.10.8000
IFMR0036	Speed monitor
110542-336	
110591-336	
110708-336	
110821-336	
110FXE2-SC-15	
111750-336	
111850-336	
112190-336	
112297-336	
112320-336	
112771-336	
716TX	
CUB4CL20	
CUB4LP/CL	
CUB4V000	
CUB7CCR0	
DSPLE000	
DSPSX000	
DT800010	
GEM20060	
IAMS0010	
LD2006P0	
M4048X	
Model: PAXD	

NSY-1000 APSIS010	
PAX_S	
PAXCDS10	
PAX-I-0010	
PAXI0020	
PAXLCR00	
PAXS0010	
PAXT0000	
PSDR0100/AC	
ST-IPM-6350	
SL-5ES-1	691500000059 5 port unmanaged switch 10/100 Mbit/s 10/100BaseTX: 5 ports, RJ45 10/100/1000Mbps SFP: 10/100BaseTX PoE: 10/100/1000BaseTX PoE: Operating temperature range: -10 - +60 °C Housing Material: UL94V0 Lexan
CUB4LP/CL CURRENT LOOP INDICATOR 4-20mA-M2248D	EXTERNAL BACKLIGHT POWER
6915CDL10106	PAXS/CDL10 20 Set
302PAXP0010D	PAXP0010 Industry standard display Display: LED, 5 digits Colours: red Dimensions (W x H x D): 97 x 50 x 105 mm Panel cutout (W x H): 92 x 45 mm
320000000050	PAXCDS20 PAX® Setpoint plug-in cards Quad relay version For use with PAX units only
691500001004	PAXI0030 Industrial counter/tachometer/slave display Display: LED, 6 digits Colours: red Dimensions (W x H x D): 97 x 50 x 105 mm Panel cutout (W x H): 92 x 45 mm
INDICATOR 4-20mA-M2248D	CUB4LP/CL
SIXNET ET-8MG-MIL-1	
PAX CDL	PAXCDL10 CARD, ANALOG OUTPUT
PAXP0010	PROCESS INPUT METER, RED DISPLAY, DC POWERED, 4-20 MA,11-36 V DC INPUT
PAXCDS20	RELAY OUTPUT CARD, QUAD SETPOINT,3 AMP CONTACTS @ 120/240 VAC OR 28 VDC
PAXI0030	COUNTER/RATE METER, DUAL, RED DISPLAY, DC POWERED
PAXD0000	Universal DC Input Meter, Red Display, AC Powered
PAXT0000	
CUB4V	
MP62TAC1	110508-336 Permanent magnet sensor Diameter: 16mm - 5/8" thread with M12 connector Switching distance: 0.8mm Limit frequency: 20 kHz Output impedance: 1200 Ohm/400 mH Protection class: IP65 Operating temperature: -40°C ... +107°C Housing: stainless steel - no external energy source required - encapsulated, insensitive to dirt, oil, moisture & humidity Installation: via 2 nuts, flush Connection: cable 200mm
6915N0000820	116TX 16 Port Unmanaged Switch 10/100 Mbit/s
Paxs0000 Analoganzeige Moment Zinken	

Paxlvd00
Ifmr0036
Cub2l800
Pgmmod00
Paxi0020
Csmstrzr
Cub7tvso
Paxusb00
Pmk10000
Paxcdc20
SI-6es-4sc Sixnet SI-6es-4sc Multimode, Sc Style Unmanaged Ethernet Switch, 4km
We-Cub4cl20
Cub5rly0
Ps24v03aa
Vt-Mipm-245-D
Cub5pb00
1279066
SI-5es-1
Paxlc800 Modem No:Paxlc8_230vac
Iama3535
Cub4lp00
Pax10010 , By Paxi0020 And Paxi0030
SI-8es-1 Sixnet SI-8es-1 8 Port Unmanaged Ethernet Switch
Et-Gt-9es By Slx-8es-1
Vcm20000 (50-270v)
Lmpc0000
C48ts10449074
106fx2-St
Tips Mds
112193-336
04913497
IFMR0066
Speed monitor
Zfh0500d
Paxcdc40

Iama3535 Module
Model: Ifmr0036
Cub4lp40
112191-336
Cub4v
Pax-I-0010 Replaced By Paxi0030
Nsy-1000 Apsis010
Paxs0000
P4810115
Sl-8es-1
Paxi0130
Dsple000 Konverter Rs-232/Rs485 Ethernet
Model Pax 1
Slx-8es-1
Paxp0010 11-36vdc/24vac
M2248c
T4811000
Paxcdc50
691500001070 Paxs0000
Aplit405 - , By Paxlit00
Paxp0010
691500000521 Drrj45t8
110396-336
Mp62ta00
Cub4cl20 Digitalanzeige24v 4-20ma
Icm50000
Cub4lp/Cl Anzeigepatine
Cub4cl10
Paxcds20 Quad Setpoint Relay Output Card
Iams0011
Paxcdl Replaced By 302paxcdl10d Paxcdl10
302paxcdl10d Paxcdl10
112016-336
112fx4-Sc N-Tron 112fx4-Sc Multimode, Sc Style Ethernet Switch, 2km
6915dsple000

Pax_S
Pmkcc100
Nsy-1000 Apsis000
Cub4v000 5000b4
Imp23167 Alternativ: Paxd0000, Paxcds10
Cub3t300
T16 Series M4048x Nh003 / T164111u
Cub5b000
Oo10 Pgm
Drrj45t8
G310s210
Dt800000
Imp20162 Nsy-1000
Voltmeter Cub4v-000
C48cd012
Tsw1a400
Paxp0000 A
Dt3do5000
Cub4v-000 Voltmeter
Xchspa00
Paxt0000 Industrial Temperature Indicator
Paxlit00
G310s210 Systemsteuerung
Eb-Pse-24v-1b
Paxcdl10 Ein Optionaler Dual Analog Output Card