

## Reflex Ag

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Reflex Ag** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Reflex Ag T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*



¼r¼n	A¼ıklama
<a href="#">RGR2518PKS0B</a>	RGS solenoid valve type R2518PKS0B - NAMUR 3/2 5/2 spring return - MC 30 Plug & Socket 24VDC - Screw Driver Override - Black anod. aluminum 848120900 Origin: UK Weight: about 0.44kg CURRENT ITEM NO.: Please note that the item no. (R1518PKS0B, old) has been changed. The new Article no. is: R2518PKS0B. #####
<a href="#">RGR2518PKS0U</a>	Solenoid Voltage: 240V AC Coil Wire Pneumatrol Part-N° R2518PKS0U Mounting: Namur mount Reflex valve Port Size: BSP 1/4 inch ported Function: 5 Port 2 position, internally piloted, solenoid operator, spring return Operation: Pilot operated spool valve with interchangeable 3/2 and 5/2 Namur interface plates. Operating Pressure: 3 to 10 barg Flow rate:Cv = 1.1 (1,050 norm. l/min) Operating Temp: min.: - 20°C / max.: +80°C Materials: Aluminium valve body with hard anodised, PTFE impregnated spool Specification: Moulded solenoid, with plug and socket electrical connection Manual Override: Screwdriver latching manual override Solenoid Voltage: 240V AC Coil Wire Rating Class H, 180° C max. Duty Cycle: 100% Power Cons. 2W IP Rating: IP65 SIL Rating: SIL2 on energising, SIL3 on deenergising. ##### old item number: R1518PKS0U new Article number:

R2518PKSOU #####

[R2518pksou](#)

[Bs 5385-3](#)

[Ple80-12/M2/082](#)