



Regeltechnik Kornwestheim

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Regeltechnik Kornwestheim Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Regeltechnik Kornwestheim Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
Level Transmitter	<p>Brine transfer: 01HPB30BL110 Reenjeksiyon : 01HPD30BL004 Level sensor type NI 1341 Measuring range (L1) 600 mm Chain length (L2) 192 mm (PN100) Nominal pressure PN100 Temp. max. +280°C (Medium-Geothermal brine) PN100 Pressure maximum 63bar at +280°C (PN100) 100bar at +20°C (PN100) Temperature range -60°C...+280°C (Medium: Geothermal brine) for NI 1341 Vessel with connection flanges, without monitoring glass DN 50 for PN 100 Electrical details Output: 4-20 mA, 3 wire Supply voltage: 24 VDC/100mA Type of protection: IP 65 Ambient temperature: -20°C to 70°C Application 1. Level measuring with LED display per 10% steps and remote transmission with 4-20 mA output Electrical connection Figure 1. Standard connection 4-20 mA Calibration -Medium: Geothermal brine -Temperature: 200°C -Density: 980 kg/m3 -Measuring range: 600 mm Adaptation of effective range L1 Should be avoided Dimensions NI 1341 Standard</p>