

Regloplas

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Regloplas Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Regloplas T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
163-100016a	RT61 controller, complete unit 400V, 50 / 60Hz.m. main switch and safety-overhauled- (Version with 3 option slots) (Replaces RT60 - 163-100010A)
P140S/6/B501/1K/RT45	
REGLOPLAS 300LD/20/FM65/1K/RT100PCS	
NO: 101714430016	
150/18/TS15/RT45	
150-100001	
150-100023	
150S/4/TP20/1K-LWB-400-SPS	
154-100071	
154-100089	

228989	
300L/20/FM65/1K-RT100+MP2050	
300L/20KW/FM65/1K/RT100	
300S/6KW/FM25/1K/RT100	
311-100035	
340-070077	
340-100080	
350-100012	
350-100016	
350-100022	
400-100051	
490-100055	
90smart	
90XL/20/CR5-8/DK - RT100	
FABRIK NO :541345 BAUJHAR :1991 INHALT :9,6 LT ,2BAR,300 C,24KW,25 L/MIN	
G-90SMART-0001	
P100M/18/SM72/D K/RT100.	
P160M/18/SM75/SK/RT100	
RT50	
TOE/CY-4091.02	
350-100197	Valve block complete for 90smart12 & 90S12 230VAC
350-100198	Nipple return M12x0.5 AC 2W Nipple return compl. 90smart 12 & 90S12 , 230V A
G-90SMART-0001	90smart/9/TP20/1K-RT70 Temperature control unit 1-circuit device open system Flow temperature max. 90°C heat carrier water Capacity 7.0 l Expansion space 2.5 l Heating power 9 kW Cooling capacity 51 kW Cooling method indirect cooling at a flow temperature of 80 °C at a cooling water temperature of 20 °C with a flow rate per circuit of 20 l/min Pump type TP20 - Leak-free submersible pump Flow rate max. 60 l/min Pressure max. 3.8 bar Power consumption 0.5 kW Control RT70 Measurement type Pt100 connections Flow/return G ½" Cooling water network G ½" Total current consumption 13.7 A (at 400V/50Hz) Mains water pressure min. 2-6 bar Degree of protection IP40 Ambient temperature max. 40 °C Dimensions W/H/D 202/560/661 mm Weight

	approx. 44 kg Color grey, RAL 9006/7016 Continuous sound pressure level <70 dB(A) standard equipment - Automatic water refill - suction - Leak stop operation - PID controller with high accuracy - SSR for wear-free switching of the heating - Dirt filter in the water mains connection - Water circuits made of stainless materials - lockable transport rollers - internal bypass for pump protection - Dry running protection / level monitoring - Connection cable 4m, without plug
150-100001	Safety thermostat set. 95°C 90smart-04
90smart/9/Tp20/1k-Rt70	
324-100087	
340-070339	
Einschraubkonus 3/8quot;A-A Zu Eintauchfuhler, Mat. 1.4305	
340-100033	
350-100022 Magnetsteuerteil Mit O-Ring, 24v Dc/3w Zu 90smart/Rt60, 150smart = Ventileinsatz Fur Y6-	
Ag / 176-100001 /Rt100 Main Unit V3.0 Obsolete Repl By 176-100047	
90smart/9/Tp20/1k-Rt34	
350-100012 Membraneinheit M. O-Ringen U. Druckfeder Zu Kuhlventil, Ventilblock, 90smart/150smart = M	
P100m/18/Sm72/Dk/Rt100	
150-044142	
Rt50 171-100005	
340-070474	
300I/20/Fm65/1k-Rt100	
176-100047	
P140smart/9/B501/1k/Rt60	
Type:Toe/Cy-4091.02 Nr:50hz 2kl	
154-100008	
Rem93	
90 Smart /9/Tp20/1 K/Rt61	
T-Max150smart9/Tp20/1krt60	

400-004035	
90smart/9/Tp20/1k/Rt34 Replaced By 90smart/9/Tp20/1k-Rt70	
P140s/8/Sm22/Sk-Rt100 Temperaturger¼;T	
Ch-4015 Basel 220v 8000w Type:Fh13 Nr:228989	
350-100050 Magnetsteuerteil Mit O-Ring, 24v Dc/ 7w 90smart/Rt60 = Ventileinsatz Fur Y2-Ventil	
Rt50 171-045800 Ser. No: 50605149	
171-045811	
Regloplas Model P140m/8/Sm72/Sk/Rt100 Single Zone Temperature Control Unit	
154-044401	
313100093	HEATER
300s/6/Fm25/1k/Rt100	
Rt61	TEMPERATURE CONTROLLER 400V 50HZ
Rk100	
90s/6/Tp20/1k/Rt45	TEMPERATURE CONTROLLER
150smart	
340-070083	
350-100016 Ventilblock O. Spulen 24v Dc, 90smart/Rt60 Inkl. Anschl. U. Rucklaufr. 1x1/2+1x3/8ms	
163-100017/90smart	
Fabrik No :541345 Baujhar :1991 Inhalt :9,6 Lt ,2bar,300 C,24kw,25 L/Min	
90smart/9/Tp20/1k/Rt60	
Rt40	TEMP CONTROL
Mp2003	CONTROL
311-047631	
Pt 100	