

## Regloplas

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Regloplas** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Regloplas T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*



¼r¼n	A¼ıklama
<a href="#">163-100016a</a>	RT61 controller, complete unit 400V, 50 / 60Hz.m. main switch and safety-overhauled- (Version with 3 option slots) (Replaces RT60 - 163-100010A)
<a href="#">P140S/6/B501/1K/RT45</a>	
<a href="#">REGLOPLAS 300LD/20/FM65/1K/RT100PCS</a>	
<a href="#">NO: 101714430016</a>	
<a href="#">150/18/TS15/RT45</a>	
<a href="#">150-100001</a>	
<a href="#">150-100023</a>	
<a href="#">150S/4/TP20/1K-LWB-400-SPS</a>	
<a href="#">154-100071</a>	
<a href="#">154-100089</a>	

<a href="#">228989</a>	
<a href="#">300L/20/FM65/1K-RT100+MP2050</a>	
<a href="#">300L/20KW/FM65/1K/RT100</a>	
<a href="#">300S/6KW/FM25/1K/RT100</a>	
<a href="#">311-100035</a>	
<a href="#">340-070077</a>	
<a href="#">340-100080</a>	
<a href="#">350-100012</a>	
<a href="#">350-100016</a>	
<a href="#">350-100022</a>	
<a href="#">400-100051</a>	
<a href="#">490-100055</a>	
<a href="#">90smart</a>	
<a href="#">90XL/20/CR5-8/DK - RT100</a>	
<a href="#">FABRIK NO :541345 BAUJHAR :1991</a> <a href="#">INHALT :9,6 LT ,2BAR,300 C,24KW,25</a> <a href="#">L/MIN</a>	
<a href="#">G-90SMART-0001</a>	
<a href="#">P100M/18/SM72/D K/RT100.</a>	
<a href="#">P160M/18/SM75/SK/RT100</a>	
<a href="#">RT50</a>	
<a href="#">TOE/CY-4091.02</a>	
<a href="#">350-100197</a>	Valve block complete for 90smart12 & 90S12 230VAC
<a href="#">350-100198</a>	Nipple return M12x0.5 AC 2W Nipple return compl. 90smart 12 & 90S12 , 230V A
<a href="#">G-90SMART-0001</a>	90smart/9/TP20/1K-RT70 Temperature control unit 1-circuit device open system Flow temperature max. 90°C heat carrier water Capacity 7.0 l Expansion space 2.5 l Heating power 9 kW Cooling capacity 51 kW Cooling method indirect cooling at a flow temperature of 80 °C at a cooling water temperature of 20 °C with a flow rate per circuit of 20 l/min Pump type TP20 - Leak-free submersible pump Flow rate max. 60 l/min Pressure max. 3.8 bar Power consumption 0.5 kW Control RT70 Measurement type Pt100 connections Flow/return G ½" Cooling water network G ½" Total current consumption 13.7 A (at 400V/50Hz) Mains water pressure min. 2-6 bar Degree of protection IP40 Ambient temperature max. 40 °C Dimensions W/H/D 202/560/661 mm Weight

	approx. 44 kg Color grey, RAL 9006/7016 Continuous sound pressure level <70 dB(A) standard equipment - Automatic water refill - suction - Leak stop operation - PID controller with high accuracy - SSR for wear-free switching of the heating - Dirt filter in the water mains connection - Water circuits made of stainless materials - lockable transport rollers - internal bypass for pump protection - Dry running protection / level monitoring - Connection cable 4m, without plug
<a href="#">150-100001</a>	Safety thermostat set. 95°C 90smart-04
<a href="#">90smart/9/Tp20/1k-Rt70</a>	
<a href="#">324-100087</a>	
<a href="#">340-070339</a>	
<a href="#">Einschraubkonus 3/8quot;A-A Zu Eintauchfuhler, Mat. 1.4305</a>	
<a href="#">340-100033</a>	
<a href="#">350-100022 Magnetsteuerteil Mit O-Ring, 24v Dc/3w Zu 90smart/Rt60, 150smart = Ventileinsatz Fur Y6-</a>	
<a href="#">Ag / 176-100001 /Rt100 Main Unit V3.0 Obsolete Repl By 176-100047</a>	
<a href="#">90smart/9/Tp20/1k-Rt34</a>	
<a href="#">350-100012 Membraneinheit M. O-Ringen U. Druckfeder Zu Kuhlventil, Ventilblock, 90smart/150smart = M</a>	
<a href="#">P100m/18/Sm72/Dk/Rt100</a>	
<a href="#">150-044142</a>	
<a href="#">Rt50 171-100005</a>	
<a href="#">340-070474</a>	
<a href="#">300I/20/Fm65/1k-Rt100</a>	
<a href="#">176-100047</a>	
<a href="#">P140smart/9/B501/1k/Rt60</a>	
<a href="#">Type:Toe/Cy-4091.02 Nr:50hz 2kl</a>	
<a href="#">154-100008</a>	
<a href="#">Rem93</a>	
<a href="#">90 Smart /9/Tp20/1 K/Rt61</a>	
<a href="#">T-Max150smart9/Tp20/1krt60</a>	

<a href="#">400-004035</a>	
<a href="#">90smart/9/Tp20/1k/Rt34 Replaced By 90smart/9/Tp20/1k-Rt70</a>	
<a href="#">P140s/8/Sm22/Sk-Rt100</a> <a href="#">Temperaturger¼;T</a>	
<a href="#">Ch-4015 Basel 220v 8000w Type:Fh13</a> <a href="#">Nr:228989</a>	
<a href="#">350-100050 Magnetsteuerteil Mit O-Ring, 24v Dc/ 7w 90smart/Rt60 =</a> <a href="#">Ventileinsatz Fur Y2-Ventil</a>	
<a href="#">Rt50 171-045800 Ser. No: 50605149</a>	
<a href="#">171-045811</a>	
<a href="#">Regloplas Model</a> <a href="#">P140m/8/Sm72/Sk/Rt100 Single Zone</a> <a href="#">Temperature Control Unit</a>	
<a href="#">154-044401</a>	
<a href="#">313100093</a>	HEATER
<a href="#">300s/6/Fm25/1k/Rt100</a>	
<a href="#">Rt61</a>	TEMPERATURE CONTROLLER 400V 50HZ
<a href="#">Rk100</a>	
<a href="#">90s/6/Tp20/1k/Rt45</a>	TEMPERATURE CONTROLLER
<a href="#">150smart</a>	
<a href="#">340-070083</a>	
<a href="#">350-100016 Ventilblock O. Spulen 24v</a> <a href="#">Dc, 90smart/Rt60 Inkl. Anschl. U.</a> <a href="#">Rucklaufr. 1x1/2+1x3/8ms</a>	
<a href="#">163-100017/90smart</a>	
<a href="#">Fabrik No :541345 Baujhar :1991 Inhalt</a> <a href="#">:9,6 Lt ,2bar,300 C,24kw,25 L/Min</a>	
<a href="#">90smart/9/Tp20/1k/Rt60</a>	
<a href="#">Rt40</a>	TEMP CONTROL
<a href="#">Mp2003</a>	CONTROL
<a href="#">311-047631</a>	
<a href="#">Pt 100</a>	