



Rego

Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin

info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Rego** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Rego Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
1588 Mh Sauerstoffregler (45-125 Psi) 1	
1586VN (replaces 1586MN)	HP Regulator 3/4"F.NPT, 3-30PSI
1586 MN LP-GAS REGULATORS (3-30 PSI) 3/4	
A3212R250 REGO 2" 2" MNPT	VALVE THREAED INTERNAL
Type Reg0 1586MN (old), 1586VN (new).	Pressure regulator, medium pressure, output max. 247 kg / h, Inlet and outlet 3/4 "NPT IT, Type Reg0 1586MN (old), 1586VN (new), outlet pressure 0.2 to 2.1 bar, with pressure gauge connection 1/4 "NPT, with factory certificate 2.1 according to EN 10204 - GIP: without CE marking according to DGRL 2014/68 / EU
1224WA	
2884D	
3127G	
3127H	
3127P	
3139-38	
3165C	
5547	

597F	
7901T	
8685G	
A2141A6L	
A3196	
A3209D080	
A3209PA	
A3213D400 (24140)	
A3217AR260	
A3217TA	
A7575L4	
A7708L	
A8436G	
AL109	
B3212	
LV5503B6	
PRV 9432F	
TSS3169	
UNI.-NR.830001	
LV4403B4	MG:20 KG/H Pd:28 mbar P : 035-1,4 BAR
001788B	
RegO 1588VN	HP Regulator 1"F.NPT, 3-30PSI
RegO PRV9432TP350	CG Relief Valve 1/4" (24,1 bar)
RegO PRV9432TP275	CG Relief Valve 1/4" (19 bar)
RegO 14000	Male Quick Disconnect Vent Metric in US, M20 x 1.5 Bulkhead - 10 GPM
RegO 13620 / MFR5008	Male Fuelling Receptacle with inlet 3/4" NPTF 50 GPM
RegO 14405 / MFR5010	Male Fueling Receptacle 37° SAE flare fitting - 50 GPM
RegO A3149:17,6	External Pressure Relief Valve 2-1/2"
RegO PRV9432TP350	CG Relief Valve 1/4" (24,1 bar)
1588VN	

R45/80 FL-Z	HP Regulator 1/2"F.NPT, NH ₃ , 3-25 PSI
A3149:17,6 bar	External Pressure Relief Valve 2-1/2" When ordering, please specify whether multiport or single installation.
7534:17,6 bar	Semi Internal Pressure Relief Valve 2" M.NPT
Ammonia line	4 Pieces Globe Valve DN15 (1/2") threaded connection 2 Pieces Globe Angle Valve DN15 (1/2") threaded connection 6 Pieces Ball Valve DN15 (1/2") threaded connection 4 Pieces Needle Valve DN8 (1/4") threaded connection 1 Piece Safety Relief Valve set for liquid ammonia 22barg DN15 (1/2") threaded connection 2 pcs Safety Relief Valve set for gas ammonia 22barg DN15 (1/2") threaded connection 1 Piece Safety Relief Valve set for gas ammonia 8barg DN15 (1/2") threaded connection 1 Regulator for gas ammonia: Inlet pressure 20.73 barg, flow rate 15Nm ³ /h, outlet pressure 2barg, DN15 (1/2") threaded connection Moreover In addition, 1 piece of strainer DN15 (1/2") threaded connection for liquid ammonia Equipment must be compatible with both liquid and gaseous ammonia, All parts must be stainless 316 quality sealing material and EPDM, Fluid will pass through the equipment in the temperature range of -29°C to +55°C, There will be a fluid flow from the equipment in a pressure range between 1bar and 23bar,
RegO 3165C	Vent Valve 1/4" M.NPT
RegO 3127P	External Hydrostatic Relief Valve 1/4" M.NPT (300 PSI)
RegO A2141A6L	Pull-Away Valves 3/4" F. NPT
RegO 3127J	External Hydrostatic Relief Valve 1/4" M.NPT (350 PSI)
RegO 3129:G (250 psi / 17,2 bar)	External Hydrostatic Relief Valve 1/2" M.NPT
RegO 3135	External Hydrostatic Relief Valve 1/2" M.NPT
RegO A3219FA600L	Flanged Internal Valve 4"
RegO A3213D400	Threaded Internal Valve 3" M.NPT x 3" F.NPT
RegO A3212R250	Threaded Internal Valve 2" M.NPT x 2" F.NPT
RegO 7591UT	Chek-Lok Valve 1-1/4" M.NPT x 1-5/8" UNF
RegO A8574G	Multiport 4"
RegO A8564G	Multiport 3"
PRV9432T300	CG Relief valve 1/4", 20,7 bar
RegO A8563G	Multiport 3" with 3x safety valves 250 PSI
RegO 1588VN	HP Regulator 1"F.NPT, 3-30PSI
RegO 1788A	CG Regulator 1" NPT 5-55 PSI
RegO A3212R-50	Repair Kit for A003212R Series

RegO_1788B	CG Regulator 1" NPT 40-110 PSI
RegO_3129G	External Hydrostatic Relief Valve 1/2" M.NPT
RegO_3127G	External Hydrostatic Relief Valve 1/4" M.NPT
excess flow valve	We want to use our approximately 125 m3 cylindrical tank as an ammonia tank. We have outlets on the tank. We want to use excess flow valve on these lines. At the same time, we want to open and close pneumatically with a directional valve. The dimensions of the valves we need for this are; 1 piece DN100 1 piece DN80 1 piece DN65 2 pieces DN50 4 pieces are DN25. Our working pressure is around 9 bars. If possible, can you send the price, delivery time and data sheets of the above-mentioned valves with socket connection?
8865.1309	HSK-A 63/ER 16 X260 XL
8865.1317	HSK-A 63/ER 16 X340 XL
TA7034P	Globe Valve 1/2" F.NPT with Teflon Seat
RS3131:17,2 bar	Pressure Relief Valve 3/4" NPSM
SS8002G	External Hydrostatic Relief Valve 1/2" M.NPT Note: ending "G" = 250 PSI / 17.2 bar
A9092R	Rotogage 1
A9091-18L	Rotogage Dial
RS3145:17,2 bar	Pressure Relief Valve M45X2 METRIC
3282C	Excess Flow Valve 1-1/4" M.NPT x 1-1/4" F.NPT
A3400L4	Back Pressure Check Valves 2" M.NPT
FI7579CT	Low Liquid Emission Double Back Check Filler Valve
A3500P4	Excess Flow Valve 2" NPT
5769H	Adapter brass, 3-1/4" M.ACME x 2" M.NPT
A3500V6	Excess Flow Valve 3" NPT
A8017DP	Multipurpose Valve 1-1/4" M.NPT x 1" F.NPT
AA1586VW	HP Regulator 3/4"F.NPT, NH ³ , 3-25PSI
7490.225	SET FWR 225 BALANCE RING SET Ø 22 (MAX 80,000 RPM)
7490.28500	SET FWR 285 BALANCE RING SET Ø 28 (MAX 70,000 RPM)
7490.40500	SET FWR 405 BALANCE RING SET Ø 40 (MAX 50,000 RPM)
7159.09000	TSD 0.9 BALANCE RING TORQUE WRENCH 0.9 NM
7490.32500	SET FWR 325 BALANCER RING SET Ø 32 (MAX 60.000 RPM)

Service valve GS50	
Filler valve VRN20	
Liquid reclaiming valve VL25	
3129g Fas-Nr. 90100	
Ss9434	
8684g Fas-Nr. 90351	
Typ Rego A3149mg	Safety valve 2 1/2 "NPT AG, type RegO A3149MG, made of steel, SV for multiport, setting pressure 17.6 bar (255 PSI), without component testing, with plastic protective cap
A9091-18lx	
Fas-Nr. 10012	
Uni.-Nr.830001	
Fx E32	
7141m Fas-Nr. 13062	
3135	
9560ca	
Cwf40xxxx	
A3213tl	
3127	
Rego A9092r	
Fas-Typ Cg500ssl	
Prv9432t	
3149 2,5quot;	
Fas-Nr. 16007	
Lv4403b46	
9101p5h Fas-Nr. 28123	
Fas-Nr. 13055	
Typ Rego A3212r250	
3131 ¥;	
3282c Fas-Nr. 12015	
Hp9560ca (598658)	

DrG108
Prv9432t-P-435
Fas-Typ Cg250ssl
Aa3135
A3212 R250 2quot;
3149
3129
Fas-Nr. 28119