



Renishaw

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Renishaw** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Renishaw Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
sensor IMM code A-2028-7572-06 or 10 m	
A-1371-0270	Probe module for TP20 with "standard" probing force
A-9523-6250	RGS20-S Self-adhesive tape measure Grating period 20µm Length 2500mm
RGH22D30F00A	Digital readhead, Resolution 5.0 µm, Cable length 3 m, without plug
A1047-3485	
A1047-7085	
A1051-0417	
A-1207-0010	

A-1371-0272	
A-1371-0290	
A-1371-0640	
A1371-0642	
A-2008-0288	
A-2008-0927	
A-2008-5072	
A-2063-6098	
A-2063-6098, LP2	
A-2098-0933	
A-2197-0049	
A-2237-1001 SP25M	
A-2253-5120	
A-2275-1063	
A-4012-0516	
À-4012-0583	
A-4038-0234	
A-4071-2001	
À-4113-0001	
A-4114-3100	
A-4114-5015	
A-5000-3551	
A-5000-3552	
A-5000-3553	
A-5000-3609	
A-5000-3627	
A-5000-3709	PS3-1C Straight styli with ceramic stem and ruby ball Ø 6 mm x 50 mm; M4 threaded connection.
A-5000-7098	
A-5000-7522	
A-5000-7557	
A-5000-7630	

A-5000-7800	
A-5000-7805	Stylus with ruby ball Ø0.5mm. Overall length 10mm. Usable length EAL 3mm. Carbide shank Ø0.4mm. Connection thread M2.
A-5000-7806	
A-5000-7807	
A-5000-7810	
A-5000-7812	
A-5000-8663	
A-5000-8876	
A-5000-8877	
A-5003-0044	
A-5003-0077	
A-5003-0233	
A-5003-1345	
A-5003-2280	
A-5003-2300	
A-5003-2764	
A-5003-3461	
A-5003-3822	
A-5003-3822 M2 STY D2R L20 EWL12 D1TC	
A-5003-4797	
A-5003-5743	
A-5004-7402	
A-5004-7591	
A-5004-7611	
A-5004-7620	
A-5004-7621	
A-5004-7624	
A-5314-0015	
A-5555-0297	
A-5627-0001	

A-5863-0100 PHC10-3PLUS
A-8014-0182
A-8014-0280
A-8014-1500
A-8014-1530
A-8014-1540
A-8014-1610
A-9517-0004
A-9517-0043
A-9585-0035
A-9586-2049
A-9586-2050
Art. Nr. A-8014-0551
E201-9Q
FCR25
HPMA CV-94C0
LM13ASC00
M-2045-0065
M2xCAP7 A-500T-D7BA-0A
M-5000-3647
M-5000-4163
M-5000-6460
MB049DCC19BDNT00
MB053DCC19BENT00
MB064DCC19BDNT00
MHA7DCG18BT50F00
MHA7SCB15BT20F00
MHA8SPS16BT10F00
MRA049BC025DSE00
MRA053BC030DSE00
MRA064BC040DSE00

MS10
MS10AM450B0000
PH10MA
PH200, 780MM
RA26BTA075B15F
RA26BTA150B15F
RESA30USA075B
RESA30USB150B
RESR20USA200
RGC-F A-9523-4015
RGH20F
RGH24B15L00A
RGH24Z15A00A
RGH25F
RGH41G30D05A (3m)
RGH41X05F06A
RGS20-PC A-9517-0045
RGS20-S 4,5m
RMP600
RMP60-Q A-5742-0001
R-PV-W-13250250-12-6
SR015A
TS20
V2BBQ10D50B
V2BBR10D50B
A-2008-5072
A-4038-0232
A-4071-0001
A-5003-4865
A-5004-1508
A-5004-2016

A-5004-7623	
A-9661-0100	
A-2237-1112	SM25-2 scanning module for stylus lengths from 50 mm - 105 mm, without stylus holder
A-2237-1112 RBE	SM 25-2 MOD¼L
A-5003-2283	Straight M2 stylus extension, overall length L = 90.0 mm, carbon fiber shaft D = 3.0 mm
A-5003-0042	M2 straight stylus, ruby ball D=3.0 mm, total length L = 50 mm, working length L = 42.5 mm, HM shank D = 2.0 mm (PS63R)
A-5003-4865	Just M3 key insert extension Overall length L = 100 mm, carbon fiber D = 4.0 mm
OMP 60 OM 12 KİT	
OMM-2C	A5991-0001
A-5000-3712	PROBE TIP 200MM M4
TP200	Highly accurate recording with Strain gauge technology without button module.
A-5003-5171	Break kit suitable for the probe TS27R OTS and RTS consisting of: 1x A-5004-7443 breaking piece 1x M-5003-5084 retaining strap 3x P-SC11-0404 threaded pin M4x4 DIN914 2x P-SC01-0406 screw M4x6 DIN912 1x P-TL09-0007 open-end wrench 5mm 1x P-TL01-0200 Allen key 2mm 1x P-TL01-0300 Allen key 3mm 1x M-2008-0372 pin wrench D=2.5mm
QC-20W	Ball-bar 150mm 150MM EXTENSION BAR A-8014-0144
A-5000-3409	PS3-1C Straight styli with ceramic stem and ruby ball Ø 6 mm x 50 mm; M4 threaded connection.
HPMA A-2181-0425	
A-2237-1112 / SM25-2	
PH10T Probe Head	
A-5000 7829 M4 Stylus Kit	
A-5000 7534 M2 Prob	
A-2045-0003	MP11 measuring probe with integrated interface without tool holder
A-2045-0051	Spiral cable 765-1695mm long for MP11 measuring probe with 4pol. Connection plug.
A-5000-3709	PS3-1C Straight stylus with ceramic shaft and ruby ball Ø 6 mm x 50 mm; M4 thread connection.
A-5004-7621	Predetermined breaking piece M4/M4 length = 12 mm
A-1371-0270	Probe module for TP20 with "standard" probing force

A-5000-3709	PS3-1C Straight stylus with ceramic shaft and ruby ball Ø 6 mm x 50 mm; M4 thread connection.
RL32BUT050B15V	RESOLUTE scanning head BISS-C interface Vacuum version Resolution 50 nm ADTa compatible Length of position word 32 bits Max. travel speed 100 m/s Cable length 1.5 m Without connector
56-6155	Breaking piece for TL25
A-2181-5200	TSI3-P interface for controlling a measuring arm HPMA or HPGA. Pulse modulation to relieve the gear preload when the measuring position is reached.
A-5500-1000	HSI - interface with SSR output. Power supply 12-24VDC; DIN rail mounting; for operating wired measuring probes. (MP250 LP2 or TS27R)
TP20 4P2Y77	
STD FORCE 50PL34	
TS27R A-5003-5171	
Rh200z15a00a	
A-1070-0003	PROBE HEAD MANUALLY INDEXABLE REPEATABLE 720POS
Ms10b0560q0000	
Tp2-5w	PROBE TOUCH 5WAY FOR CMM APPLICATION
A-5000-7545	
A-5000-3614	
T20001081s	TRAINING
P-Sc04-0306	
A-2063-6098-13	PROBE KIT LP2
A-4038-2001	
A-5000-7549	
A-1036-0001	PROBE HEAD
P/Na20337034	
Qc20-W	CALIBRATOR BALLBAR VOLUMETRIC TESTING CAPABILITY
Lp2	
M-9653-0189	
A-2028-8819	
A-5863-4000	
A-5863-0100 Phc10-3plus	

A-5003-5234	
A-5180-2001	
A-5000-7801	
A-5003-1358	
Lm101c001ba50a00	
Ts27r	CONTACT TOOL SETTING PROBE
A-1025-0050	PROBE HEAD
A-5003-2290	
Mp700	PROBE MACHINE TOOL 6M OPERATING RANGE
A-5003-4794	
U3-M2 Ext L5ss	
Mp10	
A-5003-0037	
A-4038-1002	PROBE MODULE OMP60M
A-5000-4161	
A-5003-2289	
M-5000-9712	
A-5003-0075	
A-1025-1520	PROBE HEAD
A-1371-0284+a-1371-0419(Exa10421789)	
A-5000-4154	
A-1371-0641	
A-2008-0365-10	TOOL SETTER 3AXIS TYPE-TS27R
A-2197-0159	
Lp2hna20640002	
A-5191-0050	OMI-2 optical transmission module machine side with integrated interface and diagnostic indicators. Modulated signal transmission. 15 m connection cable; Cable outlet on the side with Protective hose screw connection and 2 Allen screws M5x16.
A20750141	
A-5003-0049	

Tp6a -Sonde	
M-9908-0313	
A-2064-0002	
A5000-3553	
A-5004-7583	
Rgh22b30s18a	
Qc20-W Standard	
Lf80-200	
Resa30usa350b	
Ms10bm320am170	
A-4113-0001	RADIO MACHINE PROBE 15M RANGE 2400-2483.5MHZ
Rgh22z05d00a	ENCODER
A-5003-0033	
A-1047-3484	
Rqa22 (A-9531-0265)	
Rgs20-S (A-9517-0004) Teilungsperiode 20?M Preis Pro Meter	
A-5069-0001	OMP400 PROBE ONLY KIT
A-5003-4784	
Mp10r	
A-8003-4224	ENVIRONMENTAL COMPENSATOR KIT US/JAPAN EC10
Rp2dd	PROBE
A-5191-0001	OMI-2 OPTICAL MACHINE INTERFACE (8 METER)
A-5003-4781	
Dsi-Qml	
Sr050a	
A-5000-7754	
A-1207-0002	TP200 KIT2 LOW FORCE MODULE
Rch22z50d00a	
A-5000-8156	
A-4113-0001-15	RADIO MACHINE PROBE 15M RANGE 2400-2483.5MHZ
A-5003-0042	

A13710291	PROBE
A-5004-7585	
A-2237-1113	
A-5003-0066	
A-4071-0001	PROBE OPTICAL ULTRA COMPACT 50MM OMP40
A-1207-0011-10	
A-5687-0049	RMI-Q RADIO MACHINE INTERFACE (8 METER)
A-1042-1890	PROBE TOUCH
A-2107-0070	
Omp405a40712001	PROBE
A-2237-1112	SM25-2 scanning module for stylus lengths from 50 mm - 105 mm, without stylus holder.
Ps58r	
Ms10b560g0000	
Lp2a20636098	
A-5687-0050	RMI-Q RADIO MACHINE INTERFACE (15 METER)
A-2066-0001	
A20636098	PROBE
Ms10b0085ad080	
A13710419	PROBE
Sm25-1	SCANNING MODULE KIT
A-5003-0065	
Sr015a - 1.5 M Cable	
A13710430	PROBE
A-4038-1002-01	PROBE MODULE OMP60M
A-5003-0035	
Rgs20-S (A-9517-0004)	
OlP40	
A-4038-2001	OMP60 probe with optical signal transmission; programmable via a trigger logic; modulated signal transmission; adjustable touch pressure; Degree of protection IP X8; complete with 2 Batteries, tool kit and instruction manual. Preset to optical on; optical turn off
Resr20usa229	

A2008012105	PROBE
A-1207-0055	
A13710392	PROBE
A-2008-0389	
A-2238-0414-Rbe	
Trs2	CNC LASER BROKEN TOOL DETECTOR
A-5000-7727	SE30 ceramic extension M4a/M4i Length L= 100mm.
A-5003-0036	
A10421890	
A-1047-3486	
M-2045-0311	
A-4038-0001	OMP60 PROBE ONLY KIT
A-5003-1075	
?-5003-4799	
Acc2	CONTROLLER AUTOCHANGE 85-140/175-275V 46-66HZ 50W
A-5003-6512	
A-5000-7555	
A-5003-0790	
Rmm44a3c00	
Resm20usa206	RING 206MM AFORM 20UM
A-5004-2290	
A-5003-5221	
50003709ps31c	
Sr-005a	
A-5003-0577	
Hsk-A63-Ren-Mp10-S	
Ree0100e10b	
A-5000-3712	PS3-2C Straight stylus with ceramic stem and ruby ball Ø 6 mm x 100 mm; M4 threaded connection.
Tre004a00	
A-5003-0938	

A-4192-0053	
Tp 200	PROBE
A-4113-0050	
A-5003-4785	
A-5003-0040	
A-1371-0284	
A/5000/6350	
A-5555-0227	
A-5000-4160	Straight M2 stylus, ruby ball D = 3.0 mm, Total length L = 20 mm, working length L = 17.5 mm, Steel shaft D = 1.5 mm (PS16R)
RI37fat050b30f	
A-2237-1003	SP25M SCANNING PROBE KIT3
Si-Nn0100-04-1-Fn-403-003-3	
A80140551	KIT
A-2107-0070-07	PROBE MOTORIZED HEAD MP700 70DEG OMP
M112	
A-9537-3010 Rqs40-S	
Lm15icd50aa10a100	
A-4014-0050	
A-5003-0045	
Rch24z30f00a	
A-5003-0063	
Tsa	MOTORISED TOOL SETTING ARM
Ph10m	PROBE HEAD
Ph10t	PROBE HEAD
A-5036-0005	
A9651150607	BRIDGEPORT
A-2033-0830	
A-5000-7547	
T12050 Aparat M4 15 Mm A-5004-7607	
A-9570-2001	Signum readhead without interface, Cable length 1.0 m, IN-TRAC reference brands and Limit switch identifier

A-5003-4788	
A-2237-1102	SM25-2 SCANNING MODULE KIT
OMP40-2	probe with opt. signal transmission; programmable via a trigger logic; 2 lithium batteries, tool kit and Operation manual. Preset to optical on/off and modulated signal transmission
A-2028-7572-06	PROBE IMM ASSEMBLY
A-2030-0227	
A20330576	
A-4192-0011	
40044289	
A-5003-0050	
Lm13icd40bb10d00	
Re36va0609b40f2b00	
A80141540	ACCESSORY KIT
Rgp22s	
A-1207-0056	
Rgh41q15d05a	
Rmb20ic12bc10	
A94200600	KIT
A-1207-0020	
A20980104rbe	PROBE
Rgh22y30f00a	READ HEAD LINEAR 0.1 MM RESOLUTION RE-TIMED
M-2085-0069	
Rgh22y30f15a	READ HEAD LINERA 0.1 MM RESOLUTION RE-TIMED
Rmp60	RADIO MACHINE PROBE 15M RANGE 2400-2483.5MHZ
M-2045-0188 Old Code M-2045-0188 New Code	
A-5004-7586	
Mha8scb18bt10f00	
A20980105	PROBE
A-5439-0049	OMI-2T OPTICAL MACHINE INTERFACE (8METER)
A-5863-1000 , By A-5863-4000	

A-500-7522	
Lp2hdda20640032	
? 5000/3721	
Trs2a-5450-1000	
A-2075-0746	CIRCUIT BOARD
A-5000-3604	
Rmh06a2a00	
Se26	
Rgh20b30f00a	
A-5003-5228	
A-5000-7792	
A20190006	
A-1039-0028	
A-1207-0001	TP200 PROBE KIT 1
A-1371-0270	PROBE MODULE FOR TP20 PROBE
A20300330	PROBE
A-2075-0009-03	PROBE TRANMISSION MACHINE TOOL W/O SHANK MP12
A-2115-0001	OMI OPTICAL MACHINE INTERFACE (8 METER)
Lm10ic001ba10f00	
Rlm2hda13ba00a00	
A10473485	
A-1368-0100	PROBE HEAD CONTROLLER
A-1047-3485	
A-5742-0001	RMP60 Q PROBE ONLY KIT
Mp10a-5000-3709	
A-1333-0010	MOTION CONTROL SYSTEM UNIVERSAL CMM
A-8014-0417	
A-1371-0271	
A-5003-0041	
XI-80	
A-5000-7629	

A-5003-4795	
A-5000-7632	
Ms10b0893g0000	
A-5000-9860	
A-9541-0037	
K-2045-0188	
A13710431	PROBE
Rp1	TRANSMITTER PROBE
A-9908-0405	
Scm A-2048-0202	
A-5003-5171	
A-4113-1003	
A-5000-7755	
Rgh24z30f00a	OPTICAL INCREMENTAL READ HEAD 0.5UM
A-5000-7802	
?5003- 8663	
A13710271	PROBE
Rgm22s	
A-500-7521	
A-5000-7796	
Rgh20b30l00a	
A-2075-0142	MACHINE INTERFACE MODEL MI-12
A-1051-0417	
A-2008-0368	TS27R KIT
A-5000-3709 Ps3-1c Gerader Tastereinsatz Mit Keramikschaf Und Rubinkugel Å216; 6 Mm X 50 Mm; M4 Gewindeanschluss	
Mi12-B	CIRCUIT BOARD
A-2053-5358	
M-2033-7091	
A13710272	PROBE
Rmp40	

A-2116-0150-03	PROBE TOOL KIT TYPE-RP2DD
A-5003-0064	
A-8014-1510	
A-5439-0050	OMI-2T OPTICAL MACHINE INTERFACE (15METER)
M5000-3647	
Mra8d080aa055b00	
A-9523-6130 Rgs20-S Selbstklebendes Maß223;Band Teilungsperiode 20?M Lõ;Nge 1300mm	
A-8014-1281	
A-5003-2291	
A-1025-6050-Rbe	
A-5004-7592	
Pi200	
M-5000-3648	
Ommre	
A-5003-1325	
Resm20usa150	
Pi9	TOUCH PROBE INTERFACE
A-2008-0382	
A-2030-0218	
Tp200 Sonde	
M5000-4164	
M-2045-0031	
A51910049	RECEIVER
A-8014-0551	
Ph1	PROBE HEAD KIT 5PIN DIN M/F CONNECTOR RED LED
A-5036-0040	
A-9908-0510	
Ra26bea350b50a	
Trs100a00	
A-5000-7804	

A-5003-4177	
A-5000-4158	
Mi12	MACHINE INTERFACE MODEL MI-12
Omp60 A-4038-0001	SENSOR
A-1207-0046	
A-1371-0370	
Renishaw-Rgh41x50d05a-F3;R-40-M- Renishaw-Maã223;Band-Kabellö;Nge-50- M-15-Poliger-Sub-D-Stecker-Fehlersignal- Single-Ended-Istanbul-Turkiye	
A-2008-0368-13	TOOL SETTER 3-AXIS TYPE-TS27R