

R¼mheld

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
R¼mheld Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız R¼mheld T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
2174160	Swivel clamping element double acting with manual override, overload protection and position monitoring Clamping force: 60 kN at 400 bar Swing stroke: 13 mm Clamping and lowering stroke: 5 mm max volume flow: 10 cm ³ / s for clamping edge: 18 mm max.operating pressure: 400 bar with pipe connection G1 / 4 according to data sheet WZ 4.2170 Net single weight: 4.13kg
Artikel-Nr. 0460729	Coupling nipple NW5 long built-in version for Ø20 H7 mm max.flow 12 l / min can only be coupled without pressure max. 300 bar, as per data sheet F9.428 Net single weight: 0.0483kg
1896608VMH36	Swing clamps with reinforced swing mechanism Flange below with O-ring connection, double-acting Pivoting angle 90° left Piston Ø 50 mm, rod Ø 40 mm Clamping stroke 20 mm, swing stroke 16 mm with shift rod, without metal scraper max. 500 bar, according to data sheet B1.8811 Net single weight: 4.524kg
	Swing clamps with reinforced swing mechanism Flange below with O-ring connection, double-acting Pivoting angle 90° left

1895608VMH35	Piston Ø 40 mm, rod Ø 32 mm Clamping stroke 22 mm, swing stroke 13 mm with shift rod, without metal scraper max. 500 bar, according to data sheet B1.8811
1543516	Block cylinder, double-acting with aluminum housing Piston Ø 25 mm, stroke 50 mm Connection pipe thread G1/4, seals NBR 2 transverse and 4 longitudinal bores max. 350 bar, according to data sheet B1.554 Net single weight: 0.902kg
Article No. 1801230a	RGR: V Compact clamp size 1 2.5 kN, flange below with long cocking lever (blank) with pneumatic relaxation control Max. 250 bar, according to data sheet B1.828
1843 A090 R23	
0460-659	
1475011	
Artikel-Nr. 1462100	Screw-in cylinder, ew Ø20 x 15 mm stroke 500 bar, according to sheet B1.461
0460-776	
Article No. 1942900	RGR: R Screw-in support element M26 x 1.5 mm, single-acting, Metal wiper edge, bolt Ø 16 mm, bolt stroke 6.5 mm, Max. Loading force 4 kN, type of function: oil pressure with spring force, Max. 350 bar, according to data sheet B1.9405.
Piston Hidrolik Ø12-10 1460001 - 12dx 10 Hub 500 Bar	
0460-682	
Artikel-Nr. 1802131	RGR: V Compact clamp size 2 4.0 kN, without cover with long cocking lever (blank) with pneumatic tension control Max. 250 bar, according to data sheet B1.827
1843 A090 L23	