



Rohde & Schwartz Inc

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Rohde & Schwartz Inc Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Rohde & Schwartz Inc T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

| ¼r¼n | A¼ıklama |
|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| Fs300 | POWER ANALYZER ROHS COMPLIANT: NA |
| Smjb13 | MODULE |
| Smj100a | SIGNAL GENERATOR BASE UNIT |
| Fsh626 | SPECTRUM ANALYZER, AMPLITUDE ACCURACY :0.5DB, AMPLITUDE RANGE:TO +20DBM, ANALYZER POWER SUPPLY:BATTERY/AC, BANDWIDTH MAX:1MHZ, BANDWIDTH MIN.:100HZ |
| Am300 | SIGNAL GENERATOR, SIGNAL GENERATOR TYPE:ARB, BANDWIDTH MAX:35MHZ, MODULATION TYPE:AMPLITUDE/FREQU¼NCY/PHASE/ASK/FSK, SWEEP TIME RANGE:10 MSEC TO 1 SEC |
| Smb-B103 | , SIGNAL GENERATOR TYPE:RF, BANDWIDTH MAX:3.2GHZ, MODULATION TYPE:AMPLITUDE/FREQU¼NCY/PHASE/PULSE, SWEEP RATE RANGE:9 KHZ TO 3.2 GHZ |
| Fsl3.13 | FSL SERIES SPECTRUM ANALYZER, AMPLITUDE RANGE:-80DBM TO 20DBM, AMPLITUDE SCALE UNITS:DBMDBMVDBUVDUAUAVW , ANALYZER |

| | |
|-----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| | FEATURES:CHANNEL/TIME POWER MEAS.OCC |
| He300hf | LOOP ANTENNA 9KHZ-20MHZ |
| Fsh-B1 | SOFTWARE, FOR USE WITH:FSH SERIES HAND-HELD SPECTRUM ANALYZERS ROHS COMPLIANT: NA |
| Nrp-B3 | EXTERNAL PLUG-IN POWER SUPPLY, POWER SUPPLY TYPE:PLUG IN EXTERNAL, NO. OF OUTPUTS:1, FEATURES:CONSISTS OF NIMH BATTERY BUILT-IN QUICK CHARGERALLOW IN |
| Nrp-Z23 | POWER SENSOR, FEATURES:FOR UNIVERSAL USEHIGH-MEASUREMENT ACCURACY SPEEDHIGH DYNAMIC RANGE OF 90DBOPERATES DIRECTLY FROM PC VIA USB INTERFACE MULTIPA |
| Fsh-Z2 | VSWR BRIDGE/POWER DIVIDER, FOR USE WITH:FSH SERIES HAND-HELD SPECTRUM ANALYZERS ROHS COMPLIANT: NA |
| Fsh-Z44 | POWER SENSOR, FREQUENCY MEASURING RANGE:200MHZ TO 4GHZ ROHS COMPLIANT: NA |
| Smb-B106 | , SIGNAL GENERATOR TYPE:RF, BANDWIDTH MAX:6GHZ, MODULATION TYPE:AMPLITUDE/FREQUENCY/PHASE/PULSE, SWEEP RATE RANGE:9 KHZ TO 6 GHZ |
| Nrp-Z51 | POWER SENSOR, FEATURES:THERMOCOUPLE SENSOR TECHNOLOGYHIGH-MEASUREMENT ACCURACY SPEEDHIGH DYNAMIC RANGE OF 90DB OPERATES DIRECTLY FROM PC VIA USB INT |
| Nrp-Z21 | POWER SENSOR, FEATURES:FOR UNIVERSAL USEHIGH-MEASUREMENT ACCURACY SPEEDHIGH DYNAMIC RANGE OF 90DBOPERATES DIRECTLY FROM PC VIA USB INTERFACE MULTIPA |
| Fsh3.03 | , AMPLITUDE ACCURACY :0.5DB, AMPLITUDE RANGE:TO +20DBM, ANALYZER POWER SUPPLY:BATTERY/AC, BANDWIDTH MAX:3GHZ, BANDWIDTH MIN.:100HZ, FREQUENCY MEASUR |
| Nrp-Z3 | I/O CONNECTOR, SERIES:NRP, FEATURES:FOR APPLICATIONS REQUIRING EXTERNAL TRIGGERING OF NRP-Z SERIES SMART SENSORS, ALSO OFFERS A SEPARATE AC POWER SUPP |
| 828.6746.02 | INSERTION UNIT 890-960MHZ FEMALE CONNECTOR |
| Smjb11 | GENERATOR |
| Fsh313 | SPECTRUM ANALYZER, AMPLITUDE ACCURACY :0.5DB, AMPLITUDE RANGE:TO +20DBM, ANALYZER POWER SUPPLY:BATTERY/AC, BANDWIDTH MAX:1MHZ, BANDWIDTH MIN.:100HZ |
| 10903000k13 | SIGNAL GENERAT |
| Cmw270 | COMMUNICATION TESTER WIMAX |
| Fsl-B4 | OXCXO REFERENCE FREQUENCY, FOR USE WITH:FSL SERIES |

| | SPECTRUM ANALYZERS ROHS COMPLIANT: NA |
|-------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| Fsh18 | SPECTRUM ANALYZER, ANALYZER POWER SUPPLY:AC, BANDWIDTH MAX:1MHZ, SPECTRUM ANALYZER TYPE:HAND HELD ROHS COMPLIANT: NA |
| Fsl303 | FSL SERIES SPECTRUM ANALYZER, AMPLITUDE RANGE:-80DBM TO 20DBM, AMPLITUDE SCALE UNITS:DBMDBMVDBUVDDBUAAVW, ANALYZER FEATURES:CHANNEL/TIME POWER MEAS.OCC |
| Up300 | AUDIO ANALYZER, BANDWIDTH MAX:80KHZ, MODULATION TYPE:DISTORTION ANALYSIS, DISPLAY TECHNOLOGY:TFT COLOR, EXTERNAL DEPTH:350MM, EXTERNAL HEIGHT:147MM, E |
| Cmu200 | UNIVERSAL RADIO COMMUNICATION TESTER |
| Nrvs | POWER METER DC ANALOG OUTPUT 40GHZ |
| He300 | DIRECTIONAL ANTENNA 20MHZ-7.5GHZ |
| Fsh-Z3 | , FOR USE WITH:FSH SPECTRUM ANALYZER ROHS COMPLIANT: NA |
| Nrp | POWER METER DISPLAY AND CONTROL UNIT, EXTERNAL DEPTH:267MM, EXTERNAL HEIGHT:112MM, EXTERNAL WIDTH:274MM ROHS COMPLIANT: NA |
| Smjb103 | SIGNAL GENERAT |