



Roland Electronic

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Roland Electronic Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Roland Electronic T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	A¼ıklama
1000006517	
1000006736	
1000012719	
6701409010	
6701409200	
A100	
E20-PN-S	
KISE-G	
KISS-G	
NS11	
P42AGS	
SCPWS-GG	

SHS42GS	
SKOISE-GG	
SKOISS-GG	
SL-CL	
SND40-EC-MF-IO	
UDK20-B-R-S	
T08	
E20-4P-B-O	P.N.S0047902 Double sheet detector 24 VDC for FE materials, microcontroller-supported - Connection for a maximum of 4 identical P-type sensors that can be controlled sequentially (no sensor switch box required) - Measuring programs for 255 different sheets can be programmed via keyboard and called up via keyboard or PLC - Password protected - Setting without sheet pattern - Alphanumeric display of sheet thickness and operating parameters - LED displays for the actual value as well as the lower and upper limit and Enable (ready for operation) - Signal output for undersize, actual value within the limit values, oversize and Enable (ready for operation) via potential-free 4-bit parallel interface with optocoupler (+24V) - External control via potential-free 9-bit parallel interface with optocoupler (+24V) - Device system test via external input - Cable connection via PG screw connection - Wall housing with protection class IP 65
P42AGS	P.N.S0002800 Sensor Ø 42mm -for FE sheets up to 4.0 mm single sheet thickness -for evaluation device E20 -without cable, with M12 device plug for sensor cable connection - Sensor with threaded sleeve M 42 x 1.5 and 2 flat nuts
CPM12S-G	P.N.S0004511 Sensor cable, 20 meters - Oilflex drag chain compatible - between device and sensor - one cable end for terminal connection - the other with axial cable socket for connecting the sensors, P30GS, P42AGS - or for connecting EM-SH-EC15 or EM-SH-EC30
SCPWS-GG P.N.S0002084	PNS0002084 cable, 5 meters -Superflex - suitable for drag chains -between device UDK10/UDK20 and sensor PW42(A)GS or between Sensor switch box SSB-UDK10 and sensor PW42(A)GS -both cable ends pluggable Delivery length: 30 m -with axial cable plug for connecting the device and axial cable socket for connection of the sensor
P42ag-2-S1m	
Ms42ags	
Skoise-Gg	
Kise-G	
I20-4-Pr-S-Fp	

2395109
I20-2-Pn-S
E20-4p-Bo-Z
E20-4p-Pn-S
Ie42-30gs
Snd8s-Ns11 Sensor
R1000-I10-Pr-S-Fp
Snd8s-Ns11 Induktiver Sensor
Sm12cpm12s-Gg
2276007
E20-B-O
R100 A100 Detektor Des Doppeltes Blattes (Mit Sensor To8 ,2 Meter)
Shx42
E20-4p-Pr-S
Shs42g-Fb
Udk20-Dnt-S
Pw42ags Sensor
E10-4p-B0-Z
Me42ags
S54s
P42ags Sensor
E20-4p-B-O
Shs42g-Fb-01
E20-Pr-S
120-2-Pr-S
P30gs
E20-Pn-S Double Workpiece Inspection Unit
E54s
Shs42gs Vakuum-Dual-Sensor-Kopf

2276116
Udk20-2pw-Et-S-Fp
Udk20-B-R-S Modul
I20-4-Dnt-S
Shs42gfb
E20-C-O
Scbi10-42a
E20-4p-Dn-S-Fp
I20-2-Pn-S-Fp
2395110
Pw42ags
2277704
I20-2-Dnt-S
Snd8s Ns11
Is42-30gs
Ns 11
Ssbe10
P75vgs
Kiss-G
Shx-Az2-25
Snd40-Ec-Mf-Pn
Udk20-B-O-S