

Rosemount



Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

Rosemount Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Rosemount Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
644hai1j5q4g2	644 Product Description: Smart Temperature Transmitter H Transmitter Type: Head Mount - DIN A A Output: 4-20 mA with Digital Signal based on HART protocol I1 Product Certifications: ATEX Intrinsically Safe J5 Enclosure Options: Remote/Integral Mount Universal Hd; Alum Alloyw/2"; SST Pipe Bkt (M20 Entries) Q4 Calibration Certificate: Calibration Certificate (3-Point Calibration) G2 Cable Gland Option: Cable Gland (7.5mm-11.9mm)
113 369 S29/644hana/Zpxxxx	Thermoelectric rod temperature sensor with ceramic protective tube with thermocouple S, B or K without converter, type 113 36
644hanaj5m5q4	TEMPERATURE TRANSMITTER SERIES 644H
403-11-20- - - -	Rosemount™ 403 PUR-Sense™ Conductivity Sensor
2090PG2S22C2Q4	Rosemount 2090P pressure transmitter for paper and pulp applications
1-CFR-23967 OUTPUT PRESSURE: 0-125 PSI With gauge	
CONTROL PRESSURE REDUCING VALVE	TYPE:95H SIZE: 1" MATERIAL:316SS BARG SET PRESSURE: 9, RANGE: 4.8-10.3 BARG , END CONNECTION: ANSI 300# RF NIPPLE FLANGE
CFR-224 67 OUTPUT PRESSURE: 0-35 PS	
TRANSMITTER MICROMOTION : 2700R11EFFEZA	
TRANSMITTER MICROMOTION: 2700I11EBFEZA	
RTD - TYPE OF SENSOR: RTD, SPRING LOADED	, PIPE DIAMETER: 9MM; SENSOR DIAMETER: 6MM ; MAT: 316L , LEMGHT:395MM RTD WIRE; MEAS. RANGE; CLASS; DUPLICATE 2XPT100 WW ; 3; -200/600 C ; (A);

	-200/600 C (B)
2120D1BG1NAAA0000	Rosemount 2120 Level Switch 2120 Product Description: Vibrating Fork Level Switch D Materials of Construction: 316/316L Stainless Steel (1.4401/1.4404) dual certified 1B Process Connection Size / Type: 1-in. BSPP (G) Thread G Electronic Type: PNP/PLC Low Voltage (3-wire) 24 to 60 VDC 1 Surface Finish: Standard surface finish NA Product Certifications: No Hazardous Locations Certifications A Housing: Glass Filled Nylon, M20 conduits/cable threads A Fork Length: Standard Length (44mm / 1.7 inches) 0 Specific Extended Fork Length: Factory default length (only if Fork Length A or H is selected) Description: Certificate; DIBt overfill protection certificate `U1` option;
Pressure transmitter 2088G322B3	0-50 bar
3051TG2A2B21AB4K5Q4D4M5	
644HANAJ5M5Q4 +	0065N37F0150N0500A1XA Flanged Thermowell TW 10, solid machined
0399-09-62	
1151 DP4S5AB2P2	
8800 Reducer Vortex Flow Meter - 3 Inch (DN80)	
RTG31157312	
SN: 09844892	
2051CD2A22A1AL4	2051C Transmitter Type: Pressure Transmitter D Measurement Type: Differential 2 Pressure Upper Range Limit: CD/CG: 250 inH2O (623 mbar) A Transmitter Output: 4-20 mA with Digital Signal Based on HART Protocol 2 Materials of Construction: Coplanar SST SST 2 Isolating Diaphragm: 316L SST A O-Ring: Glass-filled PTFE 1 Sensor Fill Fluid: Silicone A Housing/Conduit: Polyurethane-covered Aluminum 1/2-14 NPT L4 Bolting Material: Austenitic 316 SST Bolts Cal : 0 to 1500mmH2O
List attached	
MODEL:2051CD2A02A1BH2L4D4	
Seri: 2404701	Enduser: Trkei
Model: 1056	
Model: 0228-04-21-56-61	
2120	2120D1HV1E1XM0200Q8Q25QTSerial: JBE1291867Year - 2019Supply 20-264 Vac50-60 Hz20 -60 Vdc 0,5WMax Power 2WMax WP AT 20 derece (bar) 49,6Max Process Temp (T) 150

9603430	
2088G2S22A1M5D4Q4	Rosemount 2088 Gage and Absolute Pressure Transmitter
TRANSMITTER 3144PD1A1E5B4M5F5C4Q4	
WC3000	
CONDUCTIVITY SENSOR - ENDURANCE SCREW-IN	(400) 400-12-_-_-_-_-
5081 Explosion-proof	Transmitter 5081--C-HT-21-60-_-
8750WDMR1A2FN5A015CDHM4C1Q4	
PT100 J01310 3051TG3A2A21A2AB4C6	
PT100 4-pin temperature sensor, probe length 22cm	
142-01-14-54-SP	
09948855	
8705THA020CEW0EMB3Q4+8732EST1P1EMM4	
8705THA030CEW0EMB3Q4+8732EST1P1EMM4	
3051 Coplanar™ Pressure Transmitter	3051CD2A22A1AB4K5M5Q4D4 Measurement Type D:Differential Pressure Range 2:-250 to 250inH2O(-623 to 623 mbar) -250 to 250inH2O(-623 to 623 mbar) 0 to 150 psia(0 to 10.34 bar) Transmitter Output A:4-20 mA with Digital Signal Based on HART Protocol Process Flange Type Flange Material Drain Vent 2:Coplanar SST SST Isolating Diaphragm 2:316L SST O-Ring A:Glass-filled PTFE Sensor Fill Fluid 1:Silicone Housing Material Conduit Entry Size A:Aluminum 1/2-14 NPT Mounting Bracket B4:Coplanar Flange Bracket for 2-in. Pipe or Panel Mounting,all SST Product Certifications K5:USA Explosion-proof, Dust Ignition-proof, Intrinsically Safe, and Division 2 Display and Interface Options M5:LCD Display Calibration Certification Q4:Calibration Certificate Configuration Buttons D4:Analog Zero and Span RANGE : 0 to 620 mBAR
PT-100 (20")	0065N19N0000N0335I1 CLASS A-December 60 to 600 °C -- Ø=6mm-- L=335mm 4 with probes
PT-100 (12")	Range -60 TO 600 °C Ø=6mm L=220mm 4 with probes
1CSD287382-2	
144PD1A1E5B4M5Q4	TEMPERATURE TRANSMITTER \ 4-20 MA
5301HA2S8E4AM00133CBKCM1Q4Q8QTR3013	Tag number: LIT - 0005
632795	

01984-0283-0030	Power Cable P 916
2051cg2a33a1jh7b3l4m5	Pressure URL: 250 inH2O
03031-1045-0022	
644ranaf6q4	Smart Temperature Transmitter
Dh7001	POWER BOARD ASSEMBLY COM PROVOK SERIES 10
636857	
2051cg5f33a1jh3b1l1l4	Pressure URL: 2000 psi
2051cg5f33a1jh2b3i1l4m5	Pressure URL: 2000 psi
3051cd1a52a1ab4	Differential Pressure Transmitter
2051cd2a02a1ah2b1dfd4	Pressure URL 250 inH2O
2051cg5f33a1jh2b4kcl4	Pressure URL: 2000 psi
Oxt4a 640011110000	
01984-2761-0001-C-Mei	OI Drive Rack
861040	
3055 Cg 4a02a1bs5b4i1l4m5q4q8p1 V5 + 0305rc22b11	
2051cd1f33a1jh7b4l4m5	Pressure URL: 25 inH2O
2051cg2a33a1jh7b3kcl4m5	Pressure URL: 250 inH2O
0305rt32a11b1l4	
305 It G 5 A 2b 2 1 B B4 11 Q4 M5	
2051cg4a22a1jh7b4kcl4	Pressure URL: 300 psi
1199dac58dpfwjgda00	
2051cd3a22a1bb4e1m5	
2088g2s22a1m7b4q4	
2051cg2a33a1jh7b3l4	Pressure URL: 250 inH2O
2051cg2a33a1jh7b3k5l4	Pressure URL: 250 inH2O
3900vp-02-10	
0058cn1200nnn	Cut to Fit RTD Sensor
2051cg2f22a1ah2b1k5l4m5	Pressure URL: 250 inH2O
03031-0332-0011	
2051cg2a33a1jh7b2l4m5	Pressure URL: 250 inH2O

2051cd3a02a1bcnm5i1s5q4q8 2051c	
2051cd3a02a1ah2s6b3e1m5+1151ap5e22m1b1	
2051cg5f33a1jh2b4kcl4m5	Pressure URL: 2000 psi
2051cg4a22a1jh7b1l4	Pressure URL: 300 psi
3051cd2a22a1ab4k5m5	Differential Pressure Transmitter
2051cg5f33a1jh2b3i1l4	Pressure URL: 2000 psi
2051cg2a33a1jh7b4k5l4m5	Pressure URL: 250 inH2O
2140aha1ms1nnna00001e5m4	Vibrating Fork 1"NPT, EXP Class 1, Fork=1.7", LOI
CI7011x1-A2	COMPUTING CTRL
2088g1s22a1s1q4+119w2a95dfesjglaoo	
2051cg4a22a1jh7b3l4	Pressure URL: 300 psi
8732esr1a1nada1da2	
1151dp4s22b1	
2051cg5f33a1jh2b4k5l4	Pressure URL: 2000 psi
2051cg2a33a1jh7b4kcl4	Pressure URL: 250 inH2O
642804	
01151-0034-0204 - Obsolete	
2051cd2a02a1ah2s6b3e1m5+0304rt32b11	
1501511z3aeaa	
2051cg2a33a1jh7b4l4m5	Pressure URL: 250 inH2O
1199mdf59aefw71dc401	
1151-(Reply By)3051	
3051tg3a2b21ab4m5	0-16 BAR // 0-16 Bar 1/2 NPT Female Pressure Transmitter
2051cg2f22a1ah2b1i1l4m5	Pressure URL: 250 inH2O
2051cg4a22a1jh7b4kcl4m5	Pressure URL: 300 psi
2051cd4a02a1bs5i1m5cnq8 2051c	
8711tsa020p1n5	FLOW TUBE MAGNETIC 740PSI 5.10MPA 40VDC 0.5AMP 20W
2051cg5f33a1jh2b4i1l4	Pressure URL: 2000 psi
1199dcc59defwjgda60	

Model 3144p	
2051cg4a22a1jh7b2i1l4m5	Pressure URL: 300 psi
1680-01-071-1628	
03031-2101-3142	
3051tg2 A 2 B 2 1 B B4 I1 Q4 M5	
2051cg5f33a1jh2b3k5l4m5	Pressure URL: 2000 psi
0065n310000n0100	
2051cd2a22a1ah2b1i1l4	Pressure URL: 250 inH2O
2002557	
3051cg5a22a1am5b4e5	Gage Pressure Transmitter
0065 D01z005040115g38aixai1	
2051cg2f22a1ah2b1i1l4	Pressure URL: 250 inH2O
2051cg5f33a1jh2b2k5l4	Pressure URL: 2000 psi
03031-1045-2052	
03151-9018-0001	
2051cg4a33a1ah2b1k5l4m5	Pressure URL: 300 psi
620321	
2051cd2a02a1as5e5m5q4	d/p xmtr: Pressure URL, HART 250 inH2O
815187	
0065d23d0080n0315e1g3	
2051cg2f22a1ah2b2kcl4	Pressure URL: 250 inH2O
3052 Cd 4a02 A1bs 5b4i 1l4m 5p1q 4q8 V5+ 0305 Rc32 B11	
3051sal1cg2aa2a1020dffjgca00	3051SAL Product Description: Scalable Advanced Level Transmitter 1 Performance Class: Ultra: 0.055% span accuracy, 150:1 range down, 15-year limited warranty C Configuration Type: Liquid Level Transmitter G Sensor and Module Type: Gage, Coplanar 2 Main Pressure Range: Coplanar: 250 in.H2O (623 mbar) Inline: 150 psi (10.3 bar) A Multivariable Static Pressure Range: None, Single-Variable Device A Transmitter Output: 4-20 mA with digital signal based on HART protocol 2A Housing Style: Junction Box, Aluminum, 1/2-14 NPT 1 Seal System Type: Direct-Mount Diaphragm Seal System - Welded Repairable 0 Transmitter Extension: Capillary or No Extension 2 Low-Pressure Connection: 316L SST Isolator / 316 SST Transmitter Flange 0 Capillary Length: N/A D

	Diaphragm Seal Fill Fluid: Silicone 200 FF Process Connection Style: Flush Flanged J Process Connection Size: DN 80 EF: 3-in. / DN80 (2.99-in. [76mm] extension diameter) G Max Pressure / Flange Rating: PN 40
2051cg5f33a1jh2b3k5l4	Pressure URL: 2000 psi
2051cd2a22a1ah2b2k5l4	Pressure URL: 250 inH2O
90003223	
0304rt52b11_Vs_Df	
2051cg5f33a1jh2b2kcl4	Pressure URL: 2000 psi
5302ha1s1v4ae00806aae5	Guided Wave Level Transmitter
2051cg4a22a1jh7b4i1l4	Pressure URL: 300 psi
5402ah1na2ppvhbc	
3054 Cd 4a02 A1bs 5b4i 1l4m 5p1q 4q8 V5+ 0305 Rc32 B11	
2051cg4a22a1jh7b2kcl4m5	Pressure URL: 300 psi
76x00110ch	
0zttl1501	
2051cd2a22a1a	d/p xmtr: Pressure URL, HART 250 inH2O
03031-1045-0012	
2088a1s22b1b4q4	2088 Product Description: 2088 Pressure Transmitter A Transmitter Type: Absolute 1 Pressure Range: -14.7 to 30 psi (-1,01 to 2,1 bar) 1.5 psi (144,8 mbar) 30 psi (2,1 bar) S Output: 4-20 mA dc/Digital HART Protocol 22 Material of Construction: 316L SST 316L SST Silicone B Process Connection: DIN 16288 G 1/2 Male 1 Conduit Thread: 1/2-14 NPT B4 Mounting Brackets: SST Mounting Bracket with SST Bolts Q4 Calibration Certification: Calibration certificate Cal : 0 to 1200mBar A Please note the A before the 22 is now an S, but is identical.
2051cg4a22a1jh7b3kcl4	Pressure URL: 300 psi
Dm6003	INVALID PART NUMBER
3051s-2-T-G-4-A-2	
2051cg5f33a1jh2b2l4m5	Pressure URL: 2000 psi
2051cg5f33a1jh2b4l4m5	Pressure URL: 2000 psi
Model 2180	
2051cg5f33a1jh3b1kcl4m5	Pressure URL: 2000 psi

0305rc32b11b4	
1199wdf59aefw91dc401	
248hae5a2q4	248 Product Description: Smart DIN B Head Mount Temperature Transmitter H Mounting Style: DIN B Head Mount A Output Protocol: HART E5 Product Certifications: USA Explosionproof and Dust Ignition Proof A Enclosure: Rosemount connection head, DIN, IP68, aluminium 2 Cable/Conduit Entry: 1/2-inch NPT Q4 Calibration Certificate: Transmitter Calibration Certificate 3-Point standard (use codes C4 with Q4 for 5-point cal cert) 4 wire PT100/0 to 100deg C
2051cg4a22a1jh7b2l4	Pressure URL: 300 psi
39a0727x042	PROCESSOR BOARD
0306rt22aa11	Manifold Style: Threaded
2120	
0066n01n0000n0 Sn:03216275	
2051cd2a02a1ah2b1e5d4	Pressure URL 250 inH2O
3900vp-01-10	
2051cd2a22a1bs2i1d4p1q4a0227 + 1199ddb64affwg2daa9	
3d39645q03	
3056 Cg 4a02a1bs5b4i1l4m5q4q8p1 V5 + 0305rc22b11	
0065j01v0000n0151xam89 It : -50 To 450 C So : 49440062 / 25	
03031-0234-0002	
1195s015a3s1022cg2	
00753-9220-0001	
2051cd2a22a1ab4k5m5l4	Pressure URL: 250 inH2O
333u	
Oxymitter 4000	
3051s1ta1a2e11a1ab	
12p0818x012	8 Slot Carrier Rack KJ4001X1-
2051cg2a33a1jh7b2l4	Pressure URL: 250 inH2O
2051cg2a33a1jh7b2k5l4	Pressure URL: 250 inH2O
03031-1045-2042	

3051tg3a2b21ab4q4	
3051t-G-3-A-2b-2-1	
0306rt22ba11	Manifold Style: Threaded
01984-4186-9100	Termination Panel Cable
2051cg4a22a1jh7b3k5l4m5	Pressure URL: 300 psi
0185d003k1d0035n1300kai1	
644hanaxacaq4	
2051cg4a33a1ah2b1kcl4	Pressure URL: 300 psi
3051cd1a02a1am5b7h2d4q4	
372-02	
2051cg4a22a1jh7b4k5l4m5	Pressure URL: 300 psi
2051cg4a22a1jh7b2k5l4m5	Pressure URL: 300 psi
Es-72-70574	ACTUATOR/BODY/VALVE NPS 667 HEAD3IN BODY CL300VALV
2051cd2a22a1ah2b2kcl4	Pressure URL: 250 inH2O
2051cd3a02a1ah2s6b3e1m5p9+0304rt32b11	
2051cd2a22a1ah2b2k5l4m5	Pressure URL: 250 inH2O
0305rc22b11b4 (Est. Weight (Lbs) Per Unit: 7 Eccn: 2b999 Hts:8481.80.3090)	
2051cd2a02a1ah2b2e5	d/p xmtr: Pressure URL, HART 250 inH2O
2051cg4a33a1ah2b1k5l4	Pressure URL: 300 psi
2088g3s22a1b4edq4	
0065c01d0135y0150t46i1q8xa	
2051cd1a02a1bs5i1m5cnq8	
2051cd2a22a1ah2b1kcl4m5	Pressure URL: 250 inH2O
3051-Cg4a52a1ab4m5	PRESS TRANS M. W.P. 300 PSI 10.5 TO 55 VDC 0-15P
01984-2503-0001	GENERATOR I/O GRAPHICS VIDEO
1151lt5sa0a12d	4-20mA
3052 Cg 4a02a1bs5b4i1l4m5q4q8p1 V5 + 0305rc22b11	
01984-0283-0010	Power Cable P 916
2051cd2a22a1ah2b2l4m5	Pressure URL: 250 inH2O

Oxt4a 531511110000	
305rc53b11	
2051cg4a22a1jh7b1k5l4m5	Pressure URL: 300 psi
2051cd1a22a1am5	
622351	CONNECTOR BOARD
90001026	
2051cd2a22a1ah2b1l4	Pressure URL: 250 inH2O
876776	
3051tg5a2b21ab4	
3051cd3a02a1am5b7h2d4q4	
2051cg5f33a1jh2b2kcl4m5	Pressure URL: 2000 psi
1151dp5s22m4b1q4	
2051cg4a22a1jh7b1l4m5	Pressure URL: 300 psi
36a3439-L5b	PARALLEL I/O INTERFACE BOARD W/34PIN MALE CONNECT
2051cg4a22a1jh7b4l4	Pressure URL: 300 psi
0065l29d0035n0305i1xa_0065	
2051cd2a02a1afam5	d/p xmtr: Pressure URL, HART 250 inH2O
3054 Cg 4a02a1bs5b4i1l4m5q4q8p1 V5 + 0305rc22b11	
107542	
0305rc92b21b4l8	
2051cd2a22a1ah2b2i1l4m5	Pressure URL: 250 inH2O
2051cg2f22a1ah2b2kcl4m5	Pressure URL: 250 inH2O
8711tsa030p1n0	FLOW TUBE MAGNETIC 740PSI 5.10MPA
0304rt32b11vs	
2051cd2a02a1ah2s6b3e1m5p9+0304rt32b11	
2051cg4a22a1jh7b2l4m5	Pressure URL: 300 psi
2051cg2a33a1jh7b2kcl4m5	Pressure URL: 250 inH2O
2051cg2f22a1ah2b1l4	Pressure URL: 250 inH2O
228-04-21-56-61	

2051cd2a22a1ah2b1i1l4m5	Pressure URL: 250 inH2O
Cl6003	IAC MPU/ROM CARD
1199ddf59aefw71dc401	
0306rt32ba21	Manifold Style: Threaded
01984-0373-0020	Power Cable
01984-1613-0001	Trackball with Keypad
2051cg4a22a1jh7b2kcl4	Pressure URL: 300 psi
2051cg2a33a1jh7b4k5l4	Pressure URL: 250 inH2O
2051cg2a33a1jh7b4l4	Pressure URL: 250 inH2O
03031-1145-0022	
2051cg5f33a1jh2b3l4	Pressure URL: 2000 psi
1151gp7e22s1m1	TRANSMITTER
2088g2s22a1b4kh	Gage Pressure xmtr -14.7 to 150 psi/1.5 psi
1151-0011-0053 (Part Obsolete)	
2088g2s22a1m5b4	Gage Pressure xmtr -14.7 to 150 psi/1.5 psi
2051cg4a22a1jh7b3kcl4m5	Pressure URL: 300 psi
2051cd2a22a1ah2b2kcl4m5	Pressure URL: 250 inH2O
01984-2783-9015	15" Flexterm Cable P167
2051cd2a22a1ah2b2i1l4	Pressure URL: 250 inH2O
2051cg4a22a1jh7b2k5l4	Pressure URL: 300 psi
8606b2b2d08	
888693	
2051cg4a33a1ah2b1kcl4m5	Pressure URL: 300 psi
3101la1frcna	Ultrasonic Level Transmitter
5402 Ah 2n A4p Pvc Am 1qg	
2140aha1ms1nnne00601e5m4	Vibrating Fork 1"NPT, EXP Class 1, Fork = 6", LOI
2051cg2a33a1jh7b4kcl4m5	Pressure URL: 250 inH2O
2051cg4a22a1jh7b3l4m5	Pressure URL: 300 psi
8711asa30fr1no	MAGNETIC FLOWMETER FLOWTUBE .3INCH
1151lt4sc0a22d	TRANSMITTER LIQUID LEVEL 4/20MA 12/24VDC 285PSI
3144pd1a1e5b4q4	Smart Temperature Transmitter

634380	
Model 3051/3001	
2051cg2f22a1ah2b1kcl4	Pressure URL: 250 inH2O
12687-01	PH SENSOR 0-14PH
2051cg5f33a1jh2b3kcl4m5	Pressure URL: 2000 psi
2088g4s33a1kh	Gage Pressure xmtr -14.7 to 4000 psi/40 psi
10p56840001	Power Supply Connection Cable
0185I203k1v0000n0435/49062644/017002,Exi	
2051cg2f22a1ah2b1l4m5	Pressure URL: 250 inH2O
3051cg4a22a1am5b4dfi5	
1151ap8s52b1m3	PRESSURE TRANSMITTER
1151dp3s22b1	
CI7675x1-A10	PROVOX I/O DRIVER MUTILAYER
2051cg4a22a1jh7b3i1l4	Pressure URL: 300 psi
2051cd2a02a1bh2i1m5cnq8	
8711tsa010r1e5	FLOWTUBE MAGNETIC
9150025-548	BARRIER BOX
Dm7051	RAM BOARD 32K
Cp6121x1-A1	POWER CONVERTOR ASSEMBLY
Oxt4a-6-4-0-0-12-1-1-00-00-00	
2051cg2a33a1jh7b2k5l4m5	Pressure URL: 250 inH2O
3051 Cg 4a02a1bs5b4i1l4m5q4q8p1 V5 + 0305rc22b11	
3051cd0a02a1ah2e8l4m5	
2051cd2a22a1ah2b1kcl4	Pressure URL: 250 inH2O
2051cg4a22a1jh7b4k5l4	Pressure URL: 300 psi
CI6923x1-A1	PC BOARD IDI DUAL CONTROL 200MA 21-29VDC
2088g2s22a1e5m5	
3051-Cg4a22a1aj3a0078m551	TRANSMITTER 10.5/55VDC 0/300PSI
654793	
01151-0112-0092	

3051-Cd2a52a1ab4	PRESSURE TRANSMITTER 3626PSI 4-20MA 316SS
0306-R-T-2-2-Ba-1	
2051cg2a33a1jh7b3i1l4	Pressure URL: 250 inH2O
2051cg5f33a1jh2b2i1l4	Pressure URL: 2000 psi
644hahaj6m5q4	
3144pd1a1e5m5q4	Smart Temperature Transmitter
2051cg4a33a1ah2b1i1l4m5	Pressure URL: 300 psi
5402ah1na2ppvhbc1q4	
2051cg5f33a1jh2b2i1l4m5	Pressure URL: 2000 psi
3051l3aaofd21aa504	
30b7248x022	MPU/ROM COMMUNICATION INTERFACE
2051cg5f33a1jh2b2l4	Pressure URL: 2000 psi
546s	TRANSDUCER ELECTRO PNEUMATIC
8711tpe005r1e5	FLOWTUBE MAGNETIC
3051cd2a02a1am5b7h2d4q4	
3660	PNEUMATIC VALVE POSITIONER SIGLE ACTING
2051cg2a33a1jh7b3i1l4m5	Pressure URL: 250 inH2O
2051cd2a22a1ah2b1l4m5	Pressure URL: 250 inH2O
01984-0158-0002	Interface Cable 2'
42a5711x0a2	MODULE TYPE KM1303 SIGNAL CHARACTERIZER
636850	
2051cg2a33a1jh7b3k5l4m5	Pressure URL: 250 inH2O
617900	
2051cg5f33a1jh2b3kcl4	Pressure URL: 2000 psi
3051cd3a02a1am5b7	
01984-1630-9901	Power Cable P978
2051cg5f33a1jh2b1k5l4m5	Pressure URL: 2000 psi
2051cg5f33a1jh3b1kcl4	Pressure URL: 2000 psi
2051cg4a22a1jh7b3k5l4	Pressure URL: 300 psi
3051-Ca1a22a1bs1q4	PRESSURE TRANSMITTER ABSOLUTE 4.20MA 0-30PSI

2051cg2a33a1jh7b3kcl4	Pressure URL: 250 inH2O
03031-2102-3122 (Part Not Recognised)	
5945s-1	Streaming Cartridge Tape Drive. R603
2051cg2f22a1ah2b2i1l4	Pressure URL: 250 inH2O
3144pd1a1e5b4	Smart Temperature Transmitter
36a3557x012	MUX BOARD
2051cd2a22a1ah2b1k5l4m5	Pressure URL: 250 inH2O
0065n31n0000n0315	
2051cd2a02a1ah2e5b1	Pressure URL 250 inH2O
Dpr-900x1-A8	PROCESS CONTROLLER PV SP
2051cg5f33a1jh2b1k5l4	Pressure URL: 2000 psi
499a0z	ozon prob
211001bna	Vibrating Fork Level Switch
2051cg2f22a1ah2b2i1l4m5	Pressure URL: 250 inH2O
Pwa79056-01	System Monitor Extender
248hanau2nsq4	248 Product Description: Smart DIN B Head Mount Temperature Transmitter H Mounting Style: DIN B Head Mount A Output Protocol: HART NA Product Certifications: No approvals U Enclosure: Universal Connection Head, DIN IP68, Aluminium 2 Cable/Conduit Entry: 1/2-inch NPT NS Sensor Type: No Sensor NA NA Q4 Calibration Certificate: Transmitter Calibration Certificate 3-Point standard (use codes C4 with Q4 for 5-point cal cert) 4 wire PT100/0 to 100deg C
3051cd3 A 0 4 B 1 A H4 E8 D4 Hr5	
Dh7631x1-A1	VME CIA CARD
2051cg2a33a1jh7b4i1l4m5	Pressure URL: 250 inH2O
619802	
2051cg4a22a1jh7b4i1l4m5	Pressure URL: 300 psi
2051cg5f33a1jh2b1l4m5	Pressure URL: 2000 psi
3053 Cd 4a02 A1bs 5b4i 1l4m 5p1q 4q8 V5+ 0305 Rc32 B11	
2051cg5f33a1jh2b3l4m5	Pressure URL: 2000 psi
3051tg4a2b21ab4d4m	
Cd5613x1-Cd5	MASTER PROCESSOR UNIT UNIVOX DISPLAY

2051cg5f33a1jh2b4k5l4m5	Pressure URL: 2000 psi
5945 C	Streaming Cartridge Tape Drive. LR 49250
01984-1140-0001	PC BOARD HOST ADAPTER
1199wda95defwgjda40	
1151ap7e22m1b1	PRESSURE TRANSMITTER 0-300PSIA 4-20MA 45VDC
620346	
2051cd1f33a1jh7b4k5l4m5	Pressure URL: 25 inH2O
2051cd4a52a1bi1m5d4q4q8 2051c	
13718615	
2051cg2f22a1ah2b1k5l4	Pressure URL: 250 inH2O
Esg92-01	
2051cd2a22a1bs2b4e1m5q4	
01984-1691-0100	Communication Cable
852553	
1151-0011-0043 (Part Obsolete)	
Dm6001x1-Ka15	MPU ROM MODULE
36a2654x02r	DC RAM CARD DH6003 8K/16SWITCH
Smn1	Mobrey M-Switch
0185 D003k1d0035n1800xai1	
2051cg2f22a1ah2b1kcl4m5	Pressure URL: 250 inH2O
403-13-21-50	PROBE CONDUCTIVITY SENSOR
3144pd1a1e5b4m5	Smart Temperature Transmitter 3144PD1A1E5B4M5
Cl6821x1-A3	POWER CONNECT ANALOG I/O CARD P1.3
3051tg3a2b21ab4m5p8q4	
2051cg4a22a1jh7b4l4m5	Pressure URL: 300 psi
3051smv5m12a4r2a11a1bc32e1m5q4q8	
2000734	
41b5229x042	I/O POWER CONVERTER CARD
2051cg5f33a1jh2b4i1l4m5	Pressure URL: 2000 psi
G3s22a1m7b4q4	

2051cg4a22a1jh7b3i1l4m5	Pressure URL: 300 psi
Oxt4a-6-3-1-5-12-1-1-00-00-00	
644hanaj6m5q4	
3102ha1frcna	Ultrasonic Level Transmitter
03031-0001-2001	FOUNDATION MODEL 3051 ELECTRONICS FIELDBUS OUTPUT
2051cd1a22a1ab4l4m5df	Gage Pressure Transmitter 25"H2O
Fs3610j-150	
8711tsa030u1n0	FLOW TUBE MAGNETIC 1000AMP 660VAC 740PSI
2051cd2a22a1ab4k5m5	d/p xmtr: Pressure URL, HART 250 inH2O
624207	P C BOARD DUAL ALARM
30b8625x01r	RAM INTERFACE DM6004 VIOC CARD
0305-R-C-5-2-B-1-1	
2051cg5f33a1jh2b1l4	Pressure URL: 2000 psi
3051-Cg4a22a1ab4e5m5	TRANSMITTER 0-50PSI 300PSI MAX
701pgnkf	Smart Power Green Power Module
222-01-54	
636340	
36a4586x012	CIA BOARD
2051cg4a22a1jh7b2i1l4	Pressure URL: 300 psi
2051cg5f33a1jh2b2k5l4m5	Pressure URL: 2000 psi
Dm7051x1-A1	RAM BOARD 8K/0SWITCH
620494	
13a1-Mk2w	
3095-Fh23baa12aa1100a	FLOW TRANSMITTER
0305rc62b11l4b4	
90001112	
Pp205-1001	LINEAR ACTUATOR HAGAN 5INCH STROKE
3051s1cd1a2e12a2akab4	Scalable Pressure Transmitter
0065c01c0035n0181a1i1xa 0065	
3053 Cg 4a02a1bs5b4i1l4m5q4q8p1 V5 +	

0305rc22b11	
2051cg4a33a1ah2b1i1l4	Pressure URL: 300 psi
6003x1-Fa1	I/O MASS DCV BOARD DATA CONCENTRATOR
1054blc-01	ANALYZER 115/230VAC 50/60HZ MAX PWR 4.0 W
2051cd1f33a1jh7b4l4	Pressure URL: 25 inH2O
Dpr-960	PROCESS CONTROLLER
2051cd2a22a1ab4	Differential Press.Transmitter 250"/H2O
3051smv-5-M-1-2-A	
90001110	
2088ais22a1b4	PRESSURE TRANSMITTER 0-25PSI
2051cd4a22a1ai1m5	
400-1	ACTIVE INPUT KIT, 460V, REFER TO PRICE B
400-11	ACTIVE INPUT KIT, 460V, REFER TO PRICE B
1199wdf59aefw72dc401	
1151gp3e12m2b1	TRANSMITTER OUTPUT 4-20MA SUPPLY 45VDC MAX
0305rc52b11b4l4.	
3051-Tg3a2b21ab4e5s1	PRESSURE TRANSMITTER 0-500PSI 10.5-55VDC
2051cd2a22a1ah2b2l4	Pressure URL: 250 inH2O
01984-0474-0005	Interface Cable
3302ha1s1e2am2290abi5m1q4	
1151dp3e22m1b1	TRANSMITTER ALPHALINE
8712-Hr12n0b6	HIGH-SIGNAL MAGNETIC FLOWMETER TRANSMITTER
3051smv3m12a3r2a11a1ac33e1m5q4	
2051cd1f33a1jh7b4k5l4	Pressure URL: 25 inH2O
602-156	FISHERSCOPE MMS SIGMASCOPE .8A 11VAC 40-60HZ
TI173	CONTROLLER ADDER- SUBTRACTER
2051cg2a33a1jh7b4i1l4	Pressure URL: 250 inH2O
Etco1138	
2051cg5f33a1jh3b1i1l4m5	Pressure URL: 2000 psi
2700-C11effezaz	

1151-Gp0-E22-C1	PRESSURE TRANSMITTER
0065c01z0140y0200g38x1	
268	INTERFACE HAND-HELD CONFIGURATOR /CALIBRATOR
2051cd3a52a1bi1m5d4q4q8 2051c	
37a1530x032	EXPANSION ROM CARD MUX CONTROL UNIT
01151-0035-0002	
0305rc62b11b4I4	
03144-1133-0001	
2051cd5a02a1bs5i1m5cnq8 2051c	
4101am3	CHANNEL BOARD
2051cd2a22a1ah2b1k5I4	Pressure URL: 250 inH2O
3244mvf1e5b4m5c4q4	TRANSMITTER TEMPERATURE
2051cd2a02a1ah3e1d4q4	
2051cd3a02a1bs5i1m5cnq8	
01984-0344-0001	16 Pin IDC Cable Apdater 87133-6
Dh6003x1	PC BOARD
1199ddf59aefw72dc401	
66-Zz63	PRESSURE REDUCING REGULATOR
Dvc5010-513/G60	CONTROLLER DIGITAL FOR VALVE
620345	
3051 Cd 4a02 A1bs 5b4i 1I4m 5p1q 4q8 V5+ 0305 Rc32 B11	
41b5222x36r	I/O CARD P1.5 ANALOG
3051-Cd3a02a1ae5s5	TRANSMITTER
1151dp4e12s2m1b3	TRANSMITTER 4-20MA 45VDC WITH 2 TRANSDUCERS
2051cg5f33a1jh2b4I4	Pressure URL: 2000 psi
0304rt32b11	