

Ross



Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Ross Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Ross T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

| ¼r¼n | A¼ıklama |
|---|---|
| 265k77 | |
| 1776F5307Z | 4/2-WAY VALVE MAGNETIC BET. PAC 110/50 Weight: 3.3000 kg / 3.3000 kg Lot number: 84812090 Country of origin: US |
| D517C79 | PILOT HEAD SER. 27 Weight: 0.6500 kg / 1.9500 kg Lot number: 84819000 |
| 1"C5111-B6009 MAX.10BAR | |
| 1010K77 | |
| 1762L77 | |
| 1968B5007 | |
| 1968B6017 | |
| 2676 B-5001 | |
| 2771A4002 | |
| 2771A8958W | |
| 2773B6001Z | |
| 2776B5001 | |
| 334B33 | |
| 387C93 | |
| 411B0410 | |
| 421 | |
| 5021B5008 | |
| 503K87 | |

| |
|-------------------------------------|
| 515K87 |
| 5500A6003 |
| 697K87 |
| 698K87 |
| 942K77 |
| C5011B4008 |
| C5021B5008 |
| C5022B4005 |
| C5022B9018 |
| C5112A7005 |
| C5211B4017 |
| C5H00C6412 |
| D2153A5929 |
| D2153B5001 |
| D2154A6905 |
| D2171A5926 |
| D2171B4011 ROSS |
| D2259L77 |
| D2753A4011 |
| D2772B6011 |
| D2773B4011 |
| D2774B4011 |
| D2776B4011 |
| D2776B5001 |
| D365G97 |
| D366G97 |
| D9576K2001Z |
| J3573A8871 |
| J3573B5259 |
| MR 2IV 100 UO2A 511 |
| MR 2IV 64 UO3A 511 |

| | |
|--|--|
| R 3/8" 220V | |
| RESK0599.1 | |
| RESK4015.10 | |
| ROSS 503K87 | |
| W1613B2825 | |
| W517C7916 24 VDC 14W 150PSI + CUERPO 2773B5001 | |
| W6076A4934 | |
| W6076B5417 | |
| W6377S4407 | |
| W6476B2402 | |
| W6476B3401 | |
| W6476B3402 | |
| W7476B2331 | |
| YD1523C6002 | |
| D2783A6912 | G1 3/2-WAY ON VALVE. N.G. LOX/EEZ-ON 3LEGS. SEALED |
| D9576K1002 | COMPACT VALVE G1/8 5/2 WAY MAGNET BET. DOUBLE MAGNET 24 VDC |
| D9576K1001W | COMPACT VALVE G1/8 5/2 WAY SOLENOID OPERATED 24VDC; 4 pieces 81.67 326.68 SPRING RETURN |
| D2773B4001 | G1/2 3/2-WAY VALVE N.G. MAGNETIC ACTUATED PAC |
| W7076C6331 | |
| W6076B4417 | |
| 3031218 - AIR MONORAIL PRESSURE REGULATOR | \ 9 KW \ 1 1/2" \ ROSS:C5X00B8029 |
| C5X00B8029A | C5X00B8029 G1-1/2 PRESSURE REGULATOR REMOTE CONTROLLED WITHOUT PRESSURE GAUGE |
| C5X00B6056A | G1 PRESSURE REGULATOR REMOTE CONTROLLED WITHOUT PRESSURE GAUGE |
| DM2DXA5XA2X | DOUBLE VALVE SZ8 24VDC WITHOUT BASE PLATE MAGNETIC RETURN |
| 946K87 | PILOT REPAIR KIT |
| Valve 2771B3001 | NPT3/8 2/2-WAY MV N.G.PAC |

| | |
|---|--|
| 306K33165 | MAGNETIC COIL 48/50-60; 24VDC; 5.8 WATTS Drawing no. 0558 14.1-10/5392 |
| D2776B6011 | G1PL 4/2 WAY VALVE MAGNETIC ACTUATED PACER |
| 946K87 | PILOT HEAD REPAIR KIT |
| D9576K1001W | COMPACT VALVE G1/8 5/2 WAY MAGNETIC ACTUATED 24VDC; |
| W7476B2331 | 5/2-WAY VALVE NG 1.5 AIR RETURNED 110/50 |
| 3126A5010 | NPT3/4 4/3 HAND VALVE RATCHING, CLOSED CENTERST. |
| C5022B5005 ROSS FILTER | |
| C5112B5009 ROSS LUBRICANT | |
| C5112B7109 ROSS CONDITIONER | |
| C5211B4017 ROSS REGULATOR | |
| C5211B5027 ROSS CONDITIONER | |
| C5211D5017 ROSS REGULATOR | |
| D1968B4007 ROSS FLOW CONTROL VALVE | |
| D1968B4107 ROSS CHECKVALF | |
| D1968B7007 ROSS FLOW CONTROL VALVE | |
| D1968D3001 ROSS CHECKVALF | |
| D2751A4915 ROSS CHECKVALF | |
| D2751B703001 ROSS VALVE | |
| D2773B5001 ROSS ENABLA VALVE | |
| D2773B7001 ROSS VALVE 24V DC | |
| D2776B7003 ROSS VALVE 24V DC | |
| D5500A8001 ROSS SUSPENDER | |
| D9576K4001 ROSS VALVE 24 V | |
| M5076B2401 ROSS VALVE DIRECTION VALVE | |
| W6077B3401 ROSS VALVE 24V DC | |
| W6077B4401 ROSS VALVE 24V DC | |
| W6077B4407 ROSS DIRECTION VALVE | |
| D2776B5001 ROSS VALVE 24V DC | |

| | |
|---|---|
| 3126A5010 | NPT3/4 4/3 HAND VALVE RATCHING, CLOSED CENTERST. |
| D2771B6011 | G1PL 2/2-WAY VALVE N.G. MAGNETIC ACTUATED PAC |
| MANUAL OPERATED 4/3 DIRECTIONAL VALVE | 3126A5010 |
| C5211D6007A | C5211D6007 G1 PRESSURE REGULATOR REMOTE CONTROLLED WITHOUT MANOMETER |
| W 6077B5411 | 5/3-WV ISO 4,MAGN. BET. CLOSED AVERAGE |
| SOLENOID VALF-ROSS-D3573A 8831 | D3573 A8759 2-8,5 BAR-R 1 1/2" Air pilot controlled double coil VA 26/26 VOLT HZ=110V / 50V AC 110-120 / 60V AC 100 % ED Pressure switch type under valve 0420 JN3 1,5 -805803 R1/8 |
| W 6476B4417 | 5/2-WV ISO 3 IMPULSE MAGNET BET REST |
| C5211B9007A | C5211B9007 PRESSURE REGULATOR G2 WITHOUT REMOTE CONTROLLED MANOMETER |
| C5112B5008 | G3/4PL OIL NEBULIZER |
| C5022B5015 | FILTER WITH AUTOMATIC DRAIN G 3/4PL |
| C5211B5027A | G3/4 PRESSURE REGULATOR WITHOUT PRESSURE GAUGE TYPE O-125 PSI |
| C5022B4005 | FILTER WITH AUTOMATIC DRAIN G 1/2 AND METAL CONTAINERS |
| C5211B4017A | C5211B4017 G1/2 PRESSURE REGULATOR TYPE 0-125 PSI WITHOUT MANOMETER |
| C5112B4008 | G1/2 OIL NEBULIZER |
| D2776B5001 | G3/4 4/2-WAY VALVE SOLENO OPERATED PAC 24 VDC |
| D1968B5904 | G3/4 SPEED CONTROL VALVE FOR HIGH TEMP. |
| 1968B8017 | NPT1-1/2PL SPEED CONTROL VALVE |
| 961K77 | REP. SET 2" CONTROLLER REMOTE CONTROLLED |
| 3573A5142 | NPT3/4PL PRESS VALVE CF8 |
| D3573D8753Z | G1-1/2 PRESSURE VALVE CF30; FLANGE,PRESSURE,110/50 SILENCER,WITH BG, NEW VERSION OUTSIDE FORECAST. |
| RESK 3478.26.3-06 | |
| 9-12-056 | |
| D3573D7630W | G1-1/4 PRESSURE VALVE CF30; FLANGE,PRESSURE,24 VDC SOUND,WITH BG, NEW VERSION |
| 435K77 | VALVE REPAIR KIT |

| | |
|-------------------------------------|--|
| P-800 | 3/2-WAY PILOT VALVE FOR 21 VALVE BLOCK |
| D2776B4001 | VALVE,1/2" |
| 5/2, W6476B4417 | |
| D2153b6012 | |
| 411b04105 110v/50hz | |
| 494k87 | |
| 1523c4002 | |
| 3573-8012 | |
| D2783a4065 | |
| W7076c6332 | |
| Fc.3018 | |
| 2776b6001 | |
| 2776a6002 | |
| 2273b6011 | |
| D2773b4001 | |
| Fc.1309 | |
| Fc.3020 | |
| 1131a2002 | |
| C5211b3017 | |
| 306k33 | |
| 886k87 | |
| 936k87 | |
| C5321h3042 | |
| D2783a4903 | |
| 2753.3001 | |
| D2783a6903 | |
| D5500b9001 2quot; | |
| 2753.6001 | |
| J3573d8015 | |
| Art. Nr. 2773b7930 | |
| W1616b2020 | |

| |
|---|
| 2771b4011, 501k87 |
| 2773a7930,24vdc (250-0280)(Mp) , 250-0260-S |
| D1968d4001 |
| 512k87 |
| 2753.4011 |
| 2771b3001 |
| 3573a5161 |
| W6476b2417 |
| 2753.4001 |
| D1968d3001 |
| W1618b2020 |
| 1776f5307z |
| 946k87 |
| 2776b6011 |
| 2774b4001 |
| 2276b4011 |
| 497k87 |
| 436 K77 |
| 2752a7001 |
| 02752a7001 |
| 2783a8016 |
| D2776b5011 |
| C5022b5005 |
| C5111b8009 |
| D1968d3014 |
| 2273b4011 |
| 2753.6011 |
| Fc.3019 |
| 2754 A-5001 3 Way N.O. 3/4 |
| C5211d5017 |

| |
|--|
| 1quot;C5111-B6009 Max.10bar |
| C5022b3005 |
| C5022b6005 |
| 1quot;C5111 ?B7009 Max.10bar |
| W6476b3411 |
| 1968e3007 |
| 1776f7305z |
| D517c79 |
| 434k77 |
| D2176c5003 |
| 501k 87 |
| 445 K77 |
| 2753.8011 |
| 2776b6011w |
| 2772b5001z |
| 2776b8012 |
| D2773b5001 |
| 435k77 |
| Dm2cda54a21 |
| 170k83 |
| 2773b4011 |
| D1968b4007 |
| 3573-6161 |