

Rossi Motoriduttori



Garanti: 12 ay

Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

Rossi Motoriduttori Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Rossi Motoriduttori T¼rkiye Distrib¼t¼r¼ veya temsilcisi deęildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	A¼ıklama
Cod.1122110	12.110A / 2R ground. Bevel pinion
Cod.1162175	16.175B / 2R ground. Bevel gear
380-50 / 400-50 / 415-50 / 460-60 /480-60	Helical-bevel geared motor catalog G MR C2I 160 UO2A - 48x350 - 32.5 Type B3 Coupled with motor Motor catalog TX (ErP) HE3 180L 4 400-50 B5 Pn [kW] = 22 Energy efficiency class.IE3 Your project (only on documents) LACRP3016004300
80a 4 Type 3 Phase Asynchronous Electric Motor:	Power: 0,55 kW Operating voltage: 400 V 50 Hz (Y) Current: 1.4 A Speed: 1405 rpm cos ϕ : 0.78 Working class: S1 Connection type: B5:
90s 4 Types 3 Phase Asynchronous Electric Motor:	Power: 1.1 kW Operating voltage: 400 V 50 Hz (Y) Current: 3 A Speed: 1410 rpm cos ϕ : 0.70 Working class: S1 Connection type: B5
Mrc2 I 160u02a	TYPE B3 i= 65,2 P(1400 min-1)= 15 kw \emptyset =42-350
MR E85FC1CN İ=10 19X40 -M6-100-80	
P/N:41297/08 4/08	TYPE:HF 132M 4 B5 ELECTRIC MOTOR(FOR GEARMOTOR) 7.5KW-1455RPM-230/400V-27.5-15.9A PF:0.80-IP 55 INS.CL:F-DUTY:S1
TERMINAL FOR ELECTROMOTOR(15KW),95*60	
TP 9201 Tripper	
MR V 81 UO3A / 10 - P07 24x50	Worm servo gearbox catalog SR13 Design B8 Drive coupling dimensions (M1, N1, F1): 165, 130, M10 Without motor
MR IV 50 UO3A	Worm gear motor A cat. MR IV 50 UO3A - 14x160 - 101 Design B3-B8 Without motor
	Brake motor with DC brake Catalog TX (ErP) Pn [kW] = 1.5 Energy efficiency class IE3 Type plate 220.380-50 / 230.400-

HB3Z 90L 4 230.400-50 B3	50 / 240.415-50 / 265.460-60 / 277.480-60 Direct brake supply 110 ÷ 440 V DS Customs fee number. = 85015220 Country of origin = Italy
HF 63E4 B5	
MR C2I 225 UO2HS Without motor	Bevel helical geared motor Catalog G MR C2I 225 UO2HS - 60x450 - 36.2 Type B6 Without motor
MRV63U	
MR 2IV 50 UO3A - Without motor	Worm gear motor A cat. MR 2IV 50 UO3A - 11x140 - 437 Design B3-B8 Without motor
MRIV 63 UO3A	
MR 2I 101 UC2A - 42x350 - 8,67 (without motor)	Coaxial spur gear motor E cat. Type B6 Without motor
MR 3I 180 UP2A - 48x350 - 39,9 (Without motor)	Spur gear motor catalog G Type B3 Without motor
MR CI 64 UO3A / 10,4 - P07 24x50	Bevel-helical servo gears catalog SR13 Type B8 Drive coupling dimensions (M1,N1,F1) : 165, 130, M10 Without motor***
R V 40 UO3A - 20	Worm gear A cat. Design B3-B8 Input speed n1 = 280 - 1800 rpm
spur gear motor	Catalog G MR 4I 100 UP2A - 19x200 - 163 Type B6 Without moto
Motor Catalog TX (ErP)	HB 80C 6 230.400-50 B5 Pn [kW] = 0.75 Intermittent duty S3-70% Identification plate 230.400-50 / 265.460-60
UT.D115	
R CI 160 UO2A - 6,27	Design V6 Drive speed n1 1400 rpm Fluorinated sealing rings on high-speed shaft (TV1) Bearing lubrication pump (P) Version for agitators External cooling with fan (RV) Painting cycle 1H color blue RAL 5010 (corrosivity class C4) metal screws; filling screw with filter and valve (TM3)
(Cod.1049786) 4.52D / 32 WORM WHEEL	
MR IV 50 UO3A - 19x200 - 50,8	Worm gear motor A cat. Design B3-B8 Without motor
MRCI63 UO3A,I:6.31,24,145 TF07 SHUTTLE	
TYPE MRV 63U03A HBZ80B4	MOTOR 380 V 0.75 Kw 50 Hz (ROSSI) - B5 - 43.8 WITHOUT SHAFT
R V 100 UO2A - 40	Design B3 Worm gear A cat
MR 2I 100 UP2A - 38x300 - 10.2	Helical geared motor catalog G MR 2I 100 UP2A - 38x300 - 10.2 Design V5 B5 flange (F1) Coupled with engine Motor catalog TX (ErP) HB3 132M 4 230.400-50 B5 Pn [kW] = 7.5 Energy efficiency class IE3 Nameplate 220.380-50 / 230.400-

	50 / 240.415-50 / 265.460-60 / 277,480-60
MR 2I 125 UP2A - 42x350 - 19.3	Helical geared motor catalog G MR 2I 125 UP2A - 42x350 - 19.3 Design V5 B5 flange (F1) Without motor
R V 63 UO3A - 10	Design V5 Worm gear A cat. High drive speed Reinforced storage of slow speed. Wave (SP2)
Worm gear A cat.	R IV 160 UO2A - 319 Bauform B3
MR CI 100 UO3A - 38x300 - 24,1	Non-oscillating design B8 +- 20° B6/B7 Drive speed n1 1400 min-1 Fluorinated sealing rings on high-speed shaft (TV1) Double seal that runs slowly. Shaft (DT2) Oil level on both sides Gearbox with synthetic oil based on polyalfaolefins ISO VG 220 (Design B8-20° B6 + B8-20° B7) Filler screw with valve with angle connector Without motor Oil filling with gearbox in installation position B8-20°B6 / Filled with oil in m.p.B8-20°B6
MR V 63 UO3A / 13 -P06 24x50 B3-B8	M1,N1,F1): 130,110,M8
MR C 125 PO1H - D. 38-300 / 2	Bevel gear motor L99 Kat Design B3 Without motor
Rci 100 U 03ai 9,81	
:Mr G21 225 U02 + Mr G21 225 U02 Gear Motor	
R Ci 100 Uo3a / 12,4	
1031007 Hohlwelle	
Mrci 63u03a 605 ? Q: 19/200	
Lp050m01-10	
Mriv100uo2a Pam100b5	
Schneckengetriebemotor A04 Kat.	
Mrv 63 U03aá; 607-B6	
Spare Parts For R Ci 180 Uo2a/9.33 V5	
Teeth For Mrv 63 Y03a 207 Fq2 Gr B3	
1044072	
Stirradgetriebe G05 Kat.	
Mr Iv 100 Uo2a	Worm geared motor A Cat. MR IV 100 UO2A - 28x250 - 80 Type B6 High drive speed A Consumption container (SB) Without motor
Zc06178075	
02-10577 75040836	
Mrc1 100 Uo 3a	
1253011 As 30x55x8	

Mrci 63u03a 505 ? Q :24/200	
Type:Mvsi 15/1410-S90 P=0,7kw; V=1500t/Min	
Mrv 50 Uo2a	
Mrv 80 Uo2a B6	
Mrv 32 U03a 63b4	
Hf71b4b14	MOTOR 1.2/2.08AMP 230/277/400/480VAC 50/60HZ
Mrci 63 U03a-A80-A4-B5	
Rv63uo3d 213	
Mrci 125 U03a 696 B7	
Mrv 80uo 3a B3 6,7 Kw	
Hb2 112m 4 230.400-50 B5 Pn (Kw) = 4 Energie Wirkungsgradklas.Ie2	
Rv-50-U03a	
1200131 16.95a-12.159 A/4	
R Ci 100 Uo3a - 9,81	Helical bevel gearbox Catalog G Type B3 Oversized hand-. low speed. Hollow shaft diameter 50 H7 (HM50)
Motor Ma 90 L4 B5 1,50 Kw - 1395 D/D	
132s 4 230.400 B5	
Mr Iv 63 Uo3a 511	
112m4 B5r	
Mrv 40 U03a	
Hbz 112m 4 230.400-50 B5r	Brake motor with Gs brake Catalog TX (ErP) Pn [kW] = 4 Energy efficiency class.IE1 Type plate 230.400-50 / 265.460- 60 Direct brake supply 200 ÷ 440 V DS
Type Hf 100la Sn 03492/092/09 4, 2,2kw 1425d/D B5	
Type Hr21 63 Up2a	
Hrv 80 Uo3a - 5 03	1,28 kW
Mrv 32 U03a	
Mr V 50 Uo3a - 80a 4 ... B5 / 87,5	
2.295/4.92 D=28	
Mrci 80u03a 605 ?Q : 28/250	

Mrci63-U03a Fo90lg4480b5 ,135 Rpm	
Italy R V 80 Uo3a 509 - 1799636 B3 - P(1400min):1,1kw I:63	
Mrci100uo3a-19x200-114	
Mrv 80u 03a	
Rv 125 Uo2a , I = 20	
Type: Ls180lr-T P =22kw , V=1450t/Min	
Hf-71b-4-B5	GEAR MOTOR 2.08A .37-.44KW 1405-1685RPM 230-480V
Type:Mvsi 15/3810-S02 P=2,2kw; V=1500t/Min	
Mr 2i 4 Pc3a - Hb2 112m 4 230.400-50 B5r / 173	
Mr Ci 80 Uo3a - 100l 4	PLEASE SEE ATTACHED PHOTO
008200600	
Mrv 63 Uo3a 506	
(Cod.1202018) 16.92 -12.241 2 Kegelradparr	
R 4e 354 Fc2c / 313	
Mrv 40 Uo3a	
Rci 80 U 03ai 8,33	
Mr Ci 225 Uo2h	Helical bevel geared motor Catalog G MR CI 225 UO2H - 65x550 - 20.3 Type B6 Disc for slow-speed. Hollow shaft (R) Without motor
Mrci63 Uo3a-90lc4	
Mrci 64 U03a 506	
Mrci63-U03a Fo 90lg4480b5	
Rv 80 U O 3a 60	
Rv40u03a511	
Mv 3i 40 Pc1a-C16-71 B/4 0.37kw, 16.4 ? 98.5rpm.	
2040068 As 45x62x8	
1.1-120150-3 Gost 8752-79	
0.37kw 1400d/D Hb 71b 4 230.400-50 B5	

Mr3150uc2a	
1.2-40?52-1 Gost 8752-79	
Mrv 81 Uo3a- Hbz	
R V 40 Uo3a 511	
1.1-120?150-3 Gost 8752-79	
Rv200 U02a/13	
1050906 Stimrad	
Sn:37755/085/08 Type:F0132m4 , 7,5kw , 1455r/M , B5r	
R Ci 80 Uo3a - 8,33	Helical bevel gearbox Catalog G Type B3
Mrv 63 Y03a 207 Fq2 Gr B3	
Mr314 Opo/A 2187	
Rv 125 Uo2a/32 V5	
Mriv50uo2a I127 ?14	
1150735	
(Cod.1301030) 10.160 - 10.545 Gehäuse-Satz	
Type:Rvsi 15/1710-S90 P=1,1kw; V=1500t/Min	
Mriv100u02a Pam90b5	
Type Hf 100lb Sn 03491/092/09 4, 3kw 1430d/D B5	
16.181-12.185/3.15	
Hf112m4/4kw/Frame 112m, 1700rpm, 220/380volts, 19.6/11.4amps, 60 Cycles, 3-Phase	
Mrv 63 Uo3a-B3 I=50	
Gear For Mr V 50u02a 90	
132sa4 Ac Motor	
Mr2 4 Pc3a	
1.2-4052-1 Gost 8752-79	
Mrv 125 Uo2a 11ma B5	
Rv 125 Uo2a I = 32	
R C2i Uo2a 2000/35 3 B7 Hi3, Tv3, Dt3,	

Tm3, 2
Mrv80 Uo I=25
Mr742.45.2c.4/1 24vdc
Mrci 80 U03a 506
16.181-12.185?/3.15
R V 80 Uo3d 213
12.207/2,5r Adjusted Bevel Pinion
R 2i 160 Up2a-8,03 Bauform B3