

## Rubig

Garanti: 12 ay  
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Rubig** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

*Firmamız Rubig Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.*



rn	Aıklama
<a href="#">01552000</a>	DIN linch pin 6x42 (5.5mm) according to DIN 11023 galvanized and yellow thick-film passivated
<a href="#">01122200</a>	DIN clip pin 12x55 + (11.5mm) according to DIN 11023 galvanized and yellow thick-film passivated
<a href="#">01752400</a>	
<a href="#">02550000 Safety Linch Pin 5,5 (6x42)</a>	Drop forged steel shaft with safety-catch with third hole for fixing the safety chain Hardened to 1.200-1.400 N/mm <sup>2</sup> the spring is made of spring steel wire shaft and spring galvanized and thick film passivated The minimum values required by DIN 11023 are considerably exceeded by all RUBIG Safety Linch pin -HF (high-strength): Made of tempered steel, forged in the die, tempered, assembled and tested. -HV (highly wear-resistant): Made of boron steel, forged in the die, tempered, assembled and tested. For applications with increased wear resistance requirements. -E (engineering steel): Made of chrome molybdenum steel, forged in the die, tempered, assembled and tested. Very good wear and strength values with slightly increased corrosion resistance. -INOX (stainless): Made of stainless

	steel, forged in the die, tempered, assembled and tested. For applications with increased corrosion resistance requirements.
<a href="#">RUBIG chain T59</a>	EXECUTION / TYPE: HF SIZE: T59 HF (high-strength) Made of tempered steel, forged in the die, tempered, assembled and tested.
<a href="#">01752900</a>	DIN folding connector 8x62 (7.5mm) according to DIN 11023 galvanized and yellow thick film passivated
<a href="#">01552000</a>	
<a href="#">06122504</a>	
<a href="#">Nf 59 8</a>	
<a href="#">06752900</a>	
<a href="#">Hss-E 89946/10</a>	
<a href="#">Din-Klappstecker 8x62 (01752900)</a>	
<a href="#">Hf 49 01iii</a>	
<a href="#">06122504z</a>	
<a href="#">1081022845, ?67</a>	
<a href="#">06752900z</a>	
<a href="#">Hf59 08 Iii</a>	
<a href="#">Hf 49 03 Iiii</a>	
<a href="#">1081022844, ?67</a>	
<a href="#">Kette T 59mm Hf</a>	
<a href="#">02550000</a>	
<a href="#">02950000</a>	