

## Rueger

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Rueger** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Rueger T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunulmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*



¼r¼n	A¼ıklama
<a href="#">0-60°C, TGL=400mm, TWL=250mm,</a>	Swivelling Cap Connection U TI113-611 TH1130U/0-60°C/TGL=400mm/TWL=250mm
<a href="#">Modell S80-TC</a>	S80=S=T=K=N=1=2=3=7=O=R=C3=15000=350=_=5P=T S80 thermocouple sensor with mineral insulated cable S Version TC standard T Diameter measuring insert 1/4" or 6.35 mm K Type K thermocouple - measuring range: -200 ... +1100°C N Accuracy class according to ANSI MC 96.1: Standard class 1 sensor element isolated 2 measuring circuit double 3 Sheath material Inconel 600/ 2.4816 7 Cable connection not stripped O Extension cable PTFE (Teflon) R Extension cable: armored outer sheath, without anti-kink spring C3 process connection compression fitting 1/2 NPT, AISI 316 15,000 cable length Lc= 15,000 mm 350 sensor length L= 350 mm _ Without certificate 5P calibration certificate 5 points T marking with stainless steel tag without transmitter
	100=AM=074=E=255=0_160C=_=EAYW=EN Class 1 according to EN 13190 Case, connection and stem stainless steel Bayonet style case, protection IP66 100 Dial size 100 mm AM Thermometer model A, stem

<a href="#">ASHCROFT® Bimetal Thermometer Model A</a>	diameter 6 mm 074 Adjustable union connection 1/2 NPT female E Every angle connection 255 Stem length 255 mm Standard instrument glass window EA External zero adjustment YW Case and ring material stainless steel 316L EN Product documentation in English Range: 0/160 °C
<a href="#">THERMOMETER,RUEGER,THI100A+AMU,380 MM</a>	Thermometers, Dial, Bi metal Diameter, dial 100 mm Type, dial connection 1/2 inch NPT Material specification, case AISI 303/1.4305 Diameter, stem 6 mm Length, stem 380 mm Calibration units, scale Degrees Celsius Temperature range from 0 to 160 Manufacturer RUEGER Manufacturer's catalog No. THI100A+AMU
<a href="#">Pbx100xa</a>	
<a href="#">Pmd150xk General Purpose Gauge</a>	
<a href="#">Pbx100xa Rohrfedermanometer</a>	
<a href="#">Tmi100a Amx+ Tw10412</a>	
<a href="#">Tmi100a+amx</a>	
<a href="#">Tmi100a + Amu</a>	
<a href="#">Ppc 96x192mm</a>	
<a href="#">Pbx150xa Rohrfedermanometer</a>	
<a href="#">Tco075</a>	
<a href="#">Pmd100xk Differential Pressure Indicator</a>	
<a href="#">Typ Tmi100a + Amx, L1 = 350 Mm</a>	
<a href="#">Pmd150xk</a>	
<a href="#">Pbx150xa</a>	
<a href="#">Pmx150xa,Ip55</a>	
<a href="#">S01.1.81baba.B--X-.-.-.-.-</a>	
<a href="#">Thi130a+amx</a>	
<a href="#">Pmd100xk</a>	
<a href="#">R1/2quot;Npt,4quot;,8x470mm</a>	
<a href="#">Tmi100u</a>	
<a href="#">Tta070/770</a>	
<a href="#">Tmi100a + Amx, L1 = 250 Mm</a>	
<a href="#">Rppy -1 - +3.5 Barg 2? Npt Female 150 Rf</a>	
<a href="#">Pbx150xa,(Dial 150mm),Ip67</a>	